

The automultiplechoice package*

Alexis Bienvenue
paamc@passoire.fr

October 18, 2023

Abstract

This package helps designing multiple choice exams ready for automated marking from papers scans.

Answers and questions are optionally shuffled, creating different sheets for every student.

1 Introduction

The package `automultiplechoice` helps formatting multiple choice questionnaires with automated marking from papers scans in mind:

- The package can produce different copies of the question sheet for each student, optionally shuffling answers and questions for each student.
- Markers can be printed on each sheet, so as to be able to analyse scans after examination. All the needed information about the position of the markers and the boxes to be checked by the students is given in an auxiliary file during \LaTeX run.

See Auto Multiple Choice (AMC) software (<https://www.auto-multiple-choice.net/>) for an integration of this package, with user interface for automated marking.

2 Samples

We begin with several samples to see what can be done with the `automultiplechoice` package. All `automultiplechoice` commands and options will be detailed further.

For all these samples, two sets of questions are used: a group of geography questions, and a group of history questions. These are defined in a common \LaTeX file named `questions.tex`:

```
\element{geography}{  
  \begin{question}{Ghana}  
    What is the capital of Ghana?  
    \begin{choiceshoriz}  
      \correctchoice{Accra}  
      \wrongchoice{Addis Abeba}  
      \wrongchoice{Ankara}  
      \wrongchoice{Apia}
```

*This document corresponds to version revision: `r:5fe89f35` from AMC 1.6.0+git20231018211451

```

        \end{choiceshoriz}
    \end{question}
}

\element{geography}{
    \begin{question}{Thailand}
        What is the capital of Thailand?
        \begin{choiceshoriz}
            \correctchoice{Bangkok}
            \wrongchoice{Banjul}
            \wrongchoice{Beijing}
            \wrongchoice{Beirut}
            \wrongchoice{Berlin}
        \end{choiceshoriz}
    \end{question}
}

\element{geography}{
    \begin{question}{Egypt}
        What is the capital of Egypt?
        \begin{choices}
            \correctchoice{Cairo}
            \wrongchoice{Caracas}
            \wrongchoice{Cayenne}
            \wrongchoice{Chisinau}
            \wrongchoice{Conakry}
        \end{choices}
    \end{question}
}

\element{geography}{
    \begin{question}{Ireland}
        What is the capital of Ireland?
        \begin{multicols}{3}
            \begin{choices}
                \correctchoice{Dublin}
                \wrongchoice{Dili}
                \wrongchoice{Djibouti}
                \wrongchoice{Doha}
                \wrongchoice{Dakar}
                \wrongchoice{Dhaka}
            \end{choices}
        \end{multicols}
    \end{question}
}

\element{history}{
    \begin{questionmult}{1901}
        Which of the following events are taking place during the year

```

```

1901?
\begin{choices}
  \correctchoice{Funeral of Queen Victoria in London}
  \correctchoice{Official end of the Caste War of Yucat\'an}
  \wrongchoice{King George of Greece becomes absolute monarch of Crete}
  \wrongchoice{The first line of the Paris M\'etro is opened}
\end{choices}
\end{questionmult}
}

\element{history}{
  \begin{questionmult}{1850}
    Which of the following events are taking place during the year
    1850?
    \begin{choices}
      \correctchoice{American Express is founded by Henry Wells \& William Fargo}
      \wrongchoice{Napoleon Bonaparte crosses the Alps and invades Italy}
      \wrongchoice{Kwang-su becomes emperor of China}
      \wrongchoice{First horse-drawn omnibuses established in London}
    \end{choices}
  \end{questionmult}
}

\element{history}{
  \begin{questionmult}{1971}
    Which of the following events are taking place during the year
    1971?
    \begin{choices}
      \correctchoice{Apollo 14 lands on the Moon}
      \correctchoice{The Soviet Union launches Salyut 1}
      \correctchoice{Death of Louis Armstrong}
      \wrongchoice{The first commercial Concorde flight takes off}
    \end{choices}
  \end{questionmult}
}

```

We will ask automultiplechoice package to include two geography questions and two history questions at random for each student, shuffling questions and answers, with the following code:

```

\cleargroup{all}
\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

```

You can read these commands as “clear group **all**, shuffle questions inside group **geography** and copy the first two to group **all**, do the same for group **history**, shuffle the four questions copied into **all** and print them”.

2.1 Standard layout

A set of 30 students sheets can be produced from the following L^AT_EX source named `sample-amc.tex`:

```
\documentclass{article}
\usepackage{automultiplechoice}
\usepackage{multicol}
\begin{document}

\input{questions.tex}

\onecopy{30}{

\noindent{\bf AMC \hfill SAMPLE TEST}

\vspace{3ex}
```

For this test, package `{\sf automultiplechoice}` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `{\tt nowatermark}` option.

Commands from `{\sf automultiplechoice}` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

```
\vspace{3ex}

\cleargroup{all}

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

}
\end{document}
```

producing a 30-pages document (every page has number 1), from which we show the first pages on page 7.

Note that “DRAFT” indications can be cancelled using option `nowatermark`, or using AMC software.

You can see on each page markers that can be used for automated completed answer sheets scans analysis:

- Four circles ● are printed in the corners, to be able to analyse any rotation or scaling of the scans.
- Binary boxes are printed in the header area, so as to be able to read student sheet number and page number. On page 2 for example, you can see that these binary boxes are coding 2/1/59:



+2/1/59+

Here, 2 is the student sheet number, 1 is the page number for this student, and 59 is a checking value that can be used for checking correct identification from a scan.

If you also use `calibration` option, `automultiplechoice` will produce a `.xy` file with informations about the exact position in the page of all the markers, and all the boxes. This option is automatically set by AMC software, which then use the information in the `.xy` file for automated marking.

2.2 Separate answer sheet

In some situations, you may need a separate answer sheet:

- this makes cheating even more difficult;
- this can reduce the number of pages to scan.

This is done using `separateanswersheet` option of `automultiplechoice` package. You also have to use commands `\AMCformBegin` to indicate the beginning of this separate answer sheet (usually after a `\clearpage` or `\AMCcleardoublepage` command), and `\AMCform` to insert the form to be completed by the students, as in the following example (`sample-separate.tex`):

```
\documentclass{article}
\usepackage[separateanswersheet]{automultiplechoice}
\usepackage{multicol}
\begin{document}
```

```
\input{questions.tex}
```

```
\onecopy{30}{
```

```
\noindent{\bf AMC \hfill SAMPLE TEST}
```

```
\vspace{3ex}
```

For this test, package `{\sf automultiplechoice}` is used with `{\tt separateanswersheet}` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `{\tt nowatermark}` option.

Commands from `{\sf automultiplechoice}` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

```
\vspace{3ex}
```

```
\cleargroup{all}
```

```

\shufflegroup{geography}
\copygroup[2]{geography}{all}
\shufflegroup{history}
\copygroup[2]{history}{all}
\shufflegroup{all}
\insertgroup{all}

```

```

\clearpage

```

```

\AMCformBegin

```

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

```

\vspace{2ex}

```

```

\AMCform

```

```

}
\end{document}

```

First pages of the result are shown on page 8. There are now 2 pages per student: the first with questions, and the second for answers. Only the second will be completed by the students, and scanned for analysis.

2.3 Without markers

With the `nopage` option, package `automultiplechoice` does not include any page markers for scan processing. I'm afraid you can't use any automated marking software with this layout, but you can still use answer sheet and corrected answer sheet (option `indivanswers`, added here) for a manual marking...

The \LaTeX source `sample-plain.tex` that only differs from `sample-amc.tex` by its options passed to `automultiplechoice`:

```

\usepackage[nopage,indivanswers]{automultiplechoice}

```

produces a 30-pages document, from which we show the first pages on page 9.

First pages from L^AT_EX source detailed in section 2.1 – see sample-amc.pdf


1/1/60

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ The first commercial Concorde flight takes off
☐ Death of Louis Armstrong
☐ Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ Cayenne
☐ Caracas
☐ Cuito
☐ Conakry
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ American Express is founded by Henry Wells & William Fargo
☐ Kwang-on becomes emperor of China

Question 4 What is the capital of Ghana?

☐ Accra ☐ Addis Ababa ☐ Ankara ☐ Apia

For your examination, preferably print documents compiled from `automultiple-choice`.


2/1/60

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1901?

☐ The first line of the Paris Metro is opened
☐ Official end of the Caste War of Yucatán
☐ King George of Greece becomes absolute monarch of Creta
☐ Funeral of Queen Victoria in London

Question 2 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Dhaka
☐ Dili ☐ Dili ☐ Dakar

Question 3 What is the capital of Ghana?

☐ Apia ☐ Accra ☐ Addis Ababa ☐ Ankara

Question 4 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ American Express is founded by Henry Wells & William Fargo
☐ Kwang-on becomes emperor of China

For your examination, preferably print documents compiled from `automultiple-choice`.


3/1/52

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ The first commercial Concorde flight takes off
☐ Apollo 14 lands on the Moon
☐ The Soviet Union launches Salyut 1
☐ Death of Louis Armstrong

Question 2 Which of the following events are taking place during the year 1850?

☐ First horse-drawn omnibuses established in London
☐ Kwang-on becomes emperor of China
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ American Express is founded by Henry Wells & William Fargo

Question 3 What is the capital of Ireland?

☐ Dhaka ☐ Dhaka ☐ Dakar
☐ Dili ☐ Dili ☐ Djibouti

Question 4 What is the capital of Thailand?

☐ Beijing ☐ Bangkok ☐ Bangkok ☐ Beirut ☐ Berlin

For your examination, preferably print documents compiled from `automultiple-choice`.


4/1/52

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used without any option. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `\nocancelmark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The Soviet Union launches Salyut 1
☐ Apollo 14 lands on the Moon
☐ Death of Louis Armstrong
☐ The first commercial Concorde flight takes off

Question 2 What is the capital of Egypt?

☐ Caracas
☐ Cayenne
☐ Cuito
☐ Conakry
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☐ American Express is founded by Henry Wells & William Fargo
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ Kwang-on becomes emperor of China

Question 4 What is the capital of Ireland?

☐ Djibouti ☐ Dhaka ☐ Dakar
☐ Dili ☐ Dili ☐ Dublin

For your examination, preferably print documents compiled from `automultiple-choice`.

First pages from L^AT_EX source detailed in section 2.2 – see sample-separate.pdf

•  • +1/1/60+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used with `separateanswersheet` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ A The Soviet Union launches Salyut 1
☐ B The first commercial Concorde flight takes off
☐ C Death of Louis Armstrong
☐ D Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ A Cayenne
☐ B Caracas
☐ C Cairo
☐ D Cusack
☐ E Chisum

Question 3 Which of the following events are taking place during the year 1850?

☐ A Napoleon Bonaparte crosses the Alps and invades Italy
☐ B First horse-drawn omnibuses established in London
☐ C American Express is founded by Henry Wells & William Fargo
☐ D Kwang-on becomes emperor of China

Question 4 What is the capital of Ghana?

☐ A Accra ☐ B Addis Ababa ☐ C Ankara ☐ D Apia

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +1/2/60+

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

Question 1: ☐ A ☐ B ☐ C ☐ D
Question 2: ☐ A ☐ B ☐ C ☐ D
Question 3: ☐ A ☐ B ☐ C ☐ D
Question 4: ☐ A ☐ B ☐ C ☐ D

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +2/1/60+

AMC SAMPLE TEST

For this test, package `automultiplechoice` is used with `separateanswersheet` option, so that all answers are to be filled on a separate sheet by students. Page markers are printed in view of an automated marking from papers scans. DRAFT indications can be cancelled using `nowatermark` option.

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1901?

☐ A The first line of the Paris Metro is opened
☐ B Official end of the Cato War of Yunán
☐ C King George of Greece becomes absolute monarch of Crete
☐ D Funeral of Queen Victoria in London

Question 2 What is the capital of Ireland?

☐ A Djibouti ☐ B Dhaka ☐ C Doha
☐ D Dublin ☐ E Dili ☐ F Dakar

Question 3 What is the capital of Ghana?

☐ A Apia ☐ B Accra ☐ C Addis Ababa ☐ D Ankara

Question 4 Which of the following events are taking place during the year 1850?

☐ A Napoleon Bonaparte crosses the Alps and invades Italy
☐ B First horse-drawn omnibuses established in London
☐ C American Express is founded by Henry Wells & William Fargo
☐ D Kwang-on becomes emperor of China

• For your examination, preferably print documents compiled from `automultiple-choice`. •

•  • +2/2/60+

This is the answer sheet: all answers are to be ticked on this page to be taken into account.

Question 1: ☐ A ☐ B ☐ C ☐ D
Question 2: ☐ A ☐ B ☐ C ☐ D
Question 3: ☐ A ☐ B ☐ C ☐ D
Question 4: ☐ A ☐ B ☐ C ☐ D

• For your examination, preferably print documents compiled from `automultiple-choice`. •

First pages from L^AT_EX source detailed in section 2.3 – see sample-plain.pdf

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☒ The Soviet Union launches Soyuz 1
☐ The first commercial Concorde flight takes off
☐ Death of Louis Armstrong
☒ Apollo 14 lands on the Moon

Question 2 What is the capital of Egypt?

☐ Cayenne
☐ Caracas
☒ Cairo
☐ Cusco
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☒ American Express is founded by Henry Wells & William Fargo
☐ Kwang-su becomes emperor of China

Question 4 What is the capital of Ghana?

☒ Accra
☐ Addis Ababa
☐ Ankara
☐ Apia

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1901?

☐ The first line of the Paris Metro is opened
☒ Official end of the Cretan War of Vassilata
☐ King George of Greece becomes absolute monarch of Crete
☒ Funeral of Queen Victoria in London

Question 2 What is the capital of Ireland?

☐ Djibouti
☐ Dhaka
☒ Dublin
☐ Dili
☐ Dakar

Question 3 What is the capital of Ghana?

☐ Apia
☒ Accra
☐ Addis Ababa
☐ Ankara

Question 4 Which of the following events are taking place during the year 1850?

☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☒ American Express is founded by Henry Wells & William Fargo
☐ Kwang-su becomes emperor of China

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☐ The first commercial Concorde flight takes off
☒ Apollo 14 lands on the Moon
☒ The Soviet Union launches Soyuz 1
☒ Death of Louis Armstrong

Question 2 Which of the following events are taking place during the year 1850?

☐ First horse-drawn omnibuses established in London
☐ Kwang-su becomes emperor of China
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☒ American Express is founded by Henry Wells & William Fargo

Question 3 What is the capital of Ireland?

☐ Dhaka
☐ Dili
☐ Dhaka
☒ Dublin
☐ Djibouti

Question 4 What is the capital of Thailand?

☐ Beijing
☐ Banjul
☒ Bangkok
☐ Beirut
☐ Berlin

1

AMC

SAMPLE TEST

For this test, package `automultiplechoice` is used with the following options:

- `nopage`, so that no page markers are printed: nothing is planned for future automated marking from papers scans.
- `indivanswers`, so that correct answers are indicated (this is the corrected answer sheet. Without this option, you get the question sheet).

Commands from `automultiplechoice` are used to print, for each student, two geography questions and two history questions, at random. Questions and answers are shuffled.

Question 1 Which of the following events are taking place during the year 1971?

☒ The Soviet Union launches Soyuz 1
☒ Apollo 14 lands on the Moon
☒ Death of Louis Armstrong
☐ The first commercial Concorde flight takes off

Question 2 What is the capital of Egypt?

☐ Caracas
☐ Cayenne
☒ Cairo
☐ Cusco
☐ Chisinau

Question 3 Which of the following events are taking place during the year 1850?

☒ American Express is founded by Henry Wells & William Fargo
☐ Napoleon Bonaparte crosses the Alps and invades Italy
☐ First horse-drawn omnibuses established in London
☐ Kwang-su becomes emperor of China

Question 4 What is the capital of Ireland?

☐ Djibouti
☐ Dili
☐ Dhaka
☐ Dakar
☒ Dublin

1

3 Usage

3.1 Package options

The following options are available for package `automultiplechoice`:

`noshuffle` cancels answers shuffling for all questions.

`noshufflegroups` cancels groups shuffling.

`answers` produces a common corrected answers sheet.

`indivanswers` shows the boxes that corresponds to correct choices on the question sheet.

`box` includes every question in a \LaTeX box, so that they can't be cutted on two different pages.

`asbox` does the same for questions in the separate answer sheet.

`separateanswersheet` asks for a separate answer sheet (see section 2.2 for an example). Commands `\AMCformBegin` and `\AMCform` must be used to describe the separate answer sheet (see section 3.6).

`digits` puts digits instead of letters in the boxes, when `separateanswersheet` (or `insidebox`) is used.

`outsidebox` prints boxes labels outside the boxes on the answersheet when `separateanswersheet` is set.

`init` initializes the random generator from time. *This option is only for testing: don't use it for a real exam!*

`completemulti` adds an answer "None of these answers are correct." at the end of each multiple question (question with no, one or several correct answers), so as to make the difference between "I don't know" and "I think none of the answers are correct".

`insidebox` puts a letter (or a digit if `digits` option is used) inside the boxes, even if `separateanswersheet` is not used. The `insidebox` option is implicitly called when using `separateanswersheet`: no need to call it then.

`calibration` asks for logging positions of boxes and markers in the `.xy` file. Without this option, a \LaTeX run updates the document but not the `.xy` file.

`nowatermark` cancels the "DRAFT" indications above pages.

`catalog` is used for formatting a catalog of questions, not an exam. Then the question identifiers will be printed.

`keys` defines the way the question identifiers will be printed on the catalog file. With `keys=next` (the default), the question identifiers will be printed next to the questions numbers. With `keys=line`, the question identifiers will be printed on one line before the question text, so that the question will look close to the final result on the exam copies.

`français` asks for french localisation.

`lang=XX` asks for localisation in XX language. At present, only CA (Catalan), DE (German), ES (Spanish), FR (French), IT (Italian), JA (Japanese), NO (Norwegian) and NL (Dutch) are available.

`plain` cancels `environ` and `etex` automatic loading. The default behaviour is to load `environ` and `etex` packages if available, as they improve `automultiplechoice`. This is not done when `plain` option is set.

`nopage` cancels markers print and page layout definition (see sample in section 2.3).

`automarks` , when used with `separateanswersheet`, cancels markers print on the subject page (they are only shown on the answer sheet pages).

`postcorrect` tells that correct answers won't be given in the LaTeX source. The teacher will fill one answer sheet for AMC to analyse the scan and set correct answers from it.

`fullgroups` cancels the use of the optional parameter of `\insertgroup` and `\copygroup`, so that each group is always fully inserted and fully copied.

`storebox` asks to use `\storebox` instead of `\savebox` to handle ovals (when using oval shape). The package `storebox` will be loaded.

`pdfform` use this option to produce PDF forms. The PDF sheet won't be printed, but filled by each student with a PDF reader. The completed PDF will then be sent to the teacher, and given to AMC for data capture.

See also section 3.8 for a french version of some of these options.

3.2 Questions and answers

We make a difference between two kind of multiple choice questions:

- **Simple questions:** there is one and only one correct choices among the proposed choices, *and this is announced to the student*. Thus, the student is asked to check one answer if he thinks this is the good one, and to check none if he has no idea.
- **Multiple questions:** there can be zero, one or several correct choices among the proposed choices. This is also announced to the student (using the `\multiSymbole` sign, with default ♣), so that the student is asked to check all the boxes corresponding to correct choices, and to let unchecked all boxes corresponding to wrong choices.

`question (env.)` Simple questions are enclosed in a `{question}{<id>}` environment, and multiple questions `questionmult (env.)` are enclosed in a `{questionmult}{<id>}` environment. These environments contain the question text, and the proposed choices inside a `choices`-like environment (see next). The `<id>` argument is a question identifier. Each question must have a unique identifier, different from the other questions identifiers.

Questions environments

Question 1 What is the elevation of Mount Everest?

- ☐ 8,253 m
☐ 8,810 m
☐ 8,848 m

Question 2 ♣ Which contries are in the Americas?

- ☐ Cambodia
☐ Guatemala
☐ Canada
☐ Switzerland

```
\begin{question}{everest}
  What is the elevation of
  Mount Everest?
  \begin{choices}
    \correctchoice{8,848\,m}
    \wrongchoice{8,253\,m}
    \wrongchoice{8,810\,m}
  \end{choices}
\end{question}

\begin{questionmult}{americas}
  Which contries are in the Americas?
  \begin{choices}
    \correctchoice{Guatemala}
    \correctchoice{Canada}
    \wrongchoice{Switzerland}
    \wrongchoice{Cambodia}
  \end{choices}
\end{questionmult}
```

`\AMCcompleteMulti` For multiple questions, it is sometimes useful to make the difference between a student who thinks that none of he choices are correct, and a student who did not answer the question. `\AMCnoCompleteMulti` The use of package option `completemulti` can be used in this case: it adds a choice to all multiple questions. Commands `\AMCcompleteMulti` and `\AMCnoCompleteMulti` can also be used to change this behaviour for a single question.

Additional answer “none” for a single question

Question 3 ♣ Which contries are in the Americas?

- ☐ Guatemala
☐ Cambodia
☐ Canada
☐ Switzerland
☐ *None of these answers are correct.*

```
\begin{questionmult}{americas}
  \AMCcompleteMulti
  Which contries are in the Americas?
  \begin{choices}
    \correctchoice{Guatemala}
    \correctchoice{Canada}
    \wrongchoice{Switzerland}
    \wrongchoice{Cambodia}
  \end{choices}
\end{questionmult}
```

`choices` (*env.*)
`choiceshoriz` (*env.*)
`choicescustom` (*env.*)

Depending on the formatting style for answers, one can choose one of the following ones:

- Environment `choices` is usually chosen for long answers:

The `choices` environment

Question 4 ♣ What are the possible uses of latex?

- ☐ Latex is used as a fuel for some space launch vehicles.
- ☐ Latex from the chicle and jelutong trees is used in chewing gum.
- ☐ Natural rubber is the most important product obtained from latex.

```
\begin{questionmult}{latex}
What are the possible uses of latex?
\begin{choices}
\correctchoice{Natural rubber is
the most important product
obtained from latex.}
\correctchoice{Latex from the chicle
and jelutong trees is used in
chewing gum.}
\wrongchoice{Latex is used as a fuel
for some space launch vehicles.}
\end{choices}
\end{questionmult}
```

- environment `choiceshoriz` is chosen for short answers:

The `choiceshoriz` environment

Question 5 How many legs for an insect?

- ☐ 2 ☐ 6 ☐ 8

```
\begin{question}{insect}
How many legs for an insect?
\begin{choiceshoriz}
\correctchoice{6}
\wrongchoice{2}
\wrongchoice{8}
\end{choiceshoriz}
\end{question}
```

- environment `choicescustom` is provided to customize answers formatting. See 3.9.3 for details.

`\correctchoice` As you have seen in these examples, the `choices`-like environments contain `\correctchoice{<text>}` and `\wrongchoice` and `\wrongchoice{<text>}` commands, with the text of the proposed choice as argument.

3.3 Scoring

`\scoring` Scoring strategies can be given in the L^AT_EX source. They don't have any impact on the question sheet: they are only transmitted to the analysis software through the `.amc` file. See AMC `\scoringDefaultM` documentation to write proper commands for your needs. `\scoring{<score>}` can be used inside a `\question` or `questionmult` environment to describe the scoring strategy for the question, or after a `\correctchoice` or `\wrongchoice` command to describe score associated to a particular choice. `\scoringDefaultM{<score>}` and `\scoringDefaultS{<score>}` define default scoring strategies for multiple and simple questions. `\QuestionIndicative` tags a question that is not taken into account to compute the mark – for example, it can be used for a question about the way students have enjoyed the course.

3.4 Groups of questions

Several commands are available that allows shuffling questions for each question sheet. They handle groups of questions. These groups will usually contain questions, but can be made of any L^AT_EX content.

\element The command `\element{<groupname>}{<content>}` adds element with content `<content>` to the group named `<groupname>`. The command `\shufflegroup{<groupname>}` shuffles elements of group named `<groupname>`. The command `\insertgroup[<n>]{<groupname>}` inserts elements of group `<groupname>` one after one. If optional parameter `<n>` is given, only the first `<n>` elements of the group are inserted in the document. If not, or if `<n>` is negative, all the elements are inserted. The command `\insertgroupfrom[<n>]{<groupname>}{<i>}` does the same, starting from element at index `<i>` (the first element has index 0).

As an example without questions in groups elements, let us create a small group named **serie**, containing five elements, and play with it:

Managing groups	
Numbers: one two three four five. Three numbers from the second (index=1) one: two three four. Two of them after shuffling: two four.	<pre> \element{serie}{ one} \element{serie}{ two} \element{serie}{ three} \element{serie}{ four} \element{serie}{ five} Numbers:\insertgroup{serie}. Three numbers from the second (index=1) one:\insertgroupfrom[3]{serie}{1}. \shufflegroup{serie} Two of them after shuffling:\insertgroup[2]{serie}. </pre>

\cleargroup The command `\cleargroup{<groupname>}` clears all the elements of group `<groupname>`, making an empty group. The command `\copygroup[<n>]{<from>}{<to>}` copies the elements of group `<from>` to group `<to>` – if optional parameter `<n>` is given, only the `<n>` first elements are copied. If not, or if `<n>` is negative, all the elements are copied. The command `\copygroupfrom[<n>]{<from>}{<to>}{<i>}` does the same, starting from element at index `<i>` (the first element has index 0).

As an example again without questions:

Three digits from 2 to 4 and two letters: A 2 3 F 4.

Three digits and two letters: 2 8 4 E D.

Three digits and two letters: 4 E 2 5 A.

```
\element{digits}{ 1}\element{digits}{ 2}\element{digits}{ 3}
\element{digits}{ 4}\element{digits}{ 5}\element{digits}{ 6}
\element{digits}{ 7}\element{digits}{ 8}\element{digits}{ 9}
\element{letters}{ A}\element{letters}{ B}\element{letters}{ C}
\element{letters}{ D}\element{letters}{ E}\element{letters}{ F}

\shufflegroup{letters}
\cleargroup{mixed}
\copygroupfrom[3]{digits}{mixed}{1}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits from 2 to 4 and two letters:\insertgroup{mixed}.

\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.

\shufflegroup{digits}\shufflegroup{letters}
\cleargroup{mixed}
\copygroup[3]{digits}{mixed}\copygroup[2]{letters}{mixed}
\shufflegroup{mixed}
Three digits and two letters:\insertgroup{mixed}.
```

You can find an example involving questions in [section 2](#).

3.5 Students identification

`\namefield` There are two ways to associate students to their sheets.

`\AMCcodeGrid`
`\AMCcodeGridInt`

- Always add to one page of each copy some place for the student to write down his name. If you want AMC software to be able to cut the scan around this area to present it to you and ask you to read the written name (this is called manual association), you must use the `\namefield{<descr>}` command. The `<descr>` argument contains the \LaTeX code used to format the name field on the page. For example:

The name field

Name and surname:

.....

```
\namefield{\fbox{
  \begin{minipage}{15em}
    Name and surname:\vspace*{3ex}\par
    \noindent\dotfill\vspace{2mm}
  \end{minipage}
}}
```

You can see that the `\namefield` command has no effect on the produced document. In fact, its only purpose is to log in the `.xy` file information about the position of the name field on the page, to be used by the software analysing the scans.

- For automated student identification, if for example students have a 6-digits student number, you can ask them to code it somewhere on the question sheet. This can be done using the `\AMCcodeGridInt[⟨opts⟩]{⟨key⟩}{⟨ndigits⟩}` command, where `⟨key⟩` is the key identifier, that can be used to retrieve coded student numbers from the scans, and `⟨ndigits⟩` is the number of digits for numbers to be coded.

Student ID												
<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<input type="checkbox"/> 0	<code>\AMCcodeGridInt{student}{6}</code>						
<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1	<input type="checkbox"/> 1							
<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2	<input type="checkbox"/> 2							
<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3	<input type="checkbox"/> 3							
<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4	<input type="checkbox"/> 4							
<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5	<input type="checkbox"/> 5							
<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6	<input type="checkbox"/> 6							
<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7	<input type="checkbox"/> 7							
<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8	<input type="checkbox"/> 8							
<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9	<input type="checkbox"/> 9							

For smaller number of digits, the “horizontal” form can be preferred:

Student ID, horizontal form												
<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9			
<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9			
<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9			

`\AMCcodeGridInt[h]{student}{3}`

3.6 Separate answer sheet

`\AMCformBegin` To produce separate answer sheets as seen in section 2.2,

`\AMCform`

`\AMCcleardoublepage`

1. use the `separateanswersheet` package option.
2. use the `\AMCformBegin` command at the beginning of the answer sheet description. This command usually follows a command to get a new page. This command can be the classical `\clearpage` for single-sided question sheets, or the `\AMCcleardoublepage` command, that

go to the next odd numbered page, so that the answer sheet is on a separate sheet even when printing in duplex mode.

3. use the `\AMCform` command to insert all boxes for all questions.

See section 2.2 for an example.

3.7 Random computation questions

One can use the \LaTeX package `fp` to make random computation questions, as can be seen in the following example (don't forget to load package `fp`):

Random computation questions

Question 6 How much are 2 plus 8?

☐ 9 ☒ 10 ☐ 16 ☐ -6

```

\begin{question}{\simplesum}
  \FPeval\VQa{trunc(1+random*8,0)}
  \FPeval\VQb{trunc(4+random*5,0)}
  \FPeval\VQsum{clip(VQa+VQb)}
  \FPeval\VQnoA{clip(VQa+VQb-1)}
  \FPeval\VQnoB{clip(VQa*VQb)}
  \FPeval\VQnoC{clip(VQa-VQb)}
  How much are \VQa{} plus \VQb{}?
  \begin{choiceshoriz}
    \correctchoice{\VQsum}
    \wrongchoice{\VQnoA}
    \wrongchoice{\VQnoB}
    \wrongchoice{\VQnoC}
  \end{choiceshoriz}
\end{question}

```

In this example, `\VQa` and `\VQb` are used to store two random integers (the first between 1 and 8, and the second between 4 and 8). Then `\VQsum` stores the sum of these two integers, and `\VQnoA`, `\VQnoB` and `\VQnoC` are other values that will be used as distractors in the multiple choice question.

\AMCIntervals In some cases, command `\AMCIntervals{\langle x \rangle}{\langle x0 \rangle}{\langle x1 \rangle}{\langle \delta \rangle}` from `automultiplechoice` can be useful. It adds a sequence of choices made of intervals $[x_i, x_i + \delta[$ of length $\langle \delta \rangle$ covering the interval $[\langle x0 \rangle, \langle x1 \rangle[$, using `\correctchoice` when $\langle x \rangle$ lies in the interval, and `\wrongchoice` otherwise.

Pick the right interval

Question 7 Let X and Y be two independent random variables, following exponential laws with respective parameters 5 and 8. In which interval lies the probability $P[X < Y]$?

- | | | | | |
|-------------------------------------|--|-------------------------------------|-------------------------------------|-------------------------------------|
| <input type="checkbox"/> [0, 0.1[| <input type="checkbox"/> [0.2, 0.3[| <input type="checkbox"/> [0.4, 0.5[| <input type="checkbox"/> [0.6, 0.7[| <input type="checkbox"/> [0.8, 0.9[|
| <input type="checkbox"/> [0.1, 0.2[| <input checked="" type="checkbox"/> [0.3, 0.4[| <input type="checkbox"/> [0.5, 0.6[| <input type="checkbox"/> [0.7, 0.8[| <input type="checkbox"/> [0.9, 1[|

```
\begin{question}{inf-expo-indep}
\FPeval\VQa{trunc(2 + random * 4,0)}
\FPeval\VQb{trunc(6 + random * 5,0)}
\FPeval\VQr{VQa/(VQa+VQb)}
Let  $X$  and  $Y$  be two independent random variables, following
exponential laws with respective parameters  $\VQa{}$  and  $\VQb{}$ .
In which interval lies the probability  $\text{P}[X < Y]$ ?
\begin{multicols}{5}
\begin{choices}[o]
\AMCIntervals{\VQr}{0}{1}{0.1}
\end{choices}
\end{multicols}
\end{question}
```

One can also use the `\AMCnumericChoices` command to ask the student to enter a numerical value as his answer, as in the following example:

Numeric choices

Question 8

Compute $\sqrt{11}$ and round it with two digits after period.

	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input checked="" type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9
	.									
<input checked="" type="checkbox"/> +	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input checked="" type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9
<input type="checkbox"/> -	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input checked="" type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9

```
\begin{questionmultx}{sqrt}
\FPeval\VQa{trunc(5+random*15,0)}
\FPeval\VQs{VQa^0.5}

Compute  $\sqrt{\VQa}$  and round it with two digits after period.

\AMCnumericChoices{\VQs}{digits=3,decimals=2,sign=true,
borderwidth=0pt,backgroundcol=lightgray,approx=5}
\end{questionmultx}
```

Note the use of `questionmultx` environment: we need this question to be *multiple* as several boxes has to be ticked, but we can't say that *several answers are correct*, so we don't show the ♣.

Available options that can be used in the second argument of the `\AMCnumericChoices` command are the following (`\langle bool \rangle` can be `true` or `false`, and `\langle color \rangle` must be a color known by the `xcolor` package):

`digits=\langle num \rangle` gives the number of digits to request (defaults to 3).

`decimals=\langle num \rangle` gives the number of digits after period to request (defaults to 0). Note that when `decimals` is positive, the LaTeX package `fp` must be loaded.

`base=\langle num \rangle` gives the base for digits and decimals (defaults to 10).

`significant=\langle bool \rangle` if `true`, the numbers to code are the first *significant* digits from the first argument of `\AMCnumericChoices`. For example, the right answer to `\AMCnumericChoices{56945.23}{digits=2,significant=true}` is 57.

`exponent=\langle num \rangle` gives the number of digits for the exponent, when requesting to enter the result in scientific notation.

`nozero=\langle bool \rangle` if `true`, the choice 0 is removed for all digits. May be useful when `\AMCnumericChoices` is used to get a small (< 10) positive value.

`sign=\langle bool \rangle` requests (or not) a signed value (default to `true`).

`exposign=\langle bool \rangle` requests (or not) a signed value of the exponent (default to `true`).

`strict=\langle bool \rangle` if `true`, a box has to be ticked for every digit and for the sign. If `false`, if some digits has no ticked box, they will be set to zero. Defaults to `false`.

`vertical=\langle bool \rangle` if `true`, each digit is represented on one raw. If `false` (default), each digit is represented on one line.

`expovertical=\langle bool \rangle` if `true`, the mantissa is above the exponent. If `false` (default), the mantissa is beside the exponent.

`reverse=\langle bool \rangle` if `true`, place higher values of the digits on the top in vertical mode (defaults to `true`).

`vhead=\langle bool \rangle` if `true`, in vertical mode, a header is placed over all digits rows, made using the command `\AMCncontextVHead` that is originally defined as `\def\AMCncontextVHead#1{\emph{b#1}}`. This default value is useful to number the binary digits. Default value is `false`.

`Tvhead=\langle text \rangle` A coma separated list as `{H,T,0,t,h,th}` for header in `vhead` vertical mode. Needs `vhead` to be set (defaults to the empty list `{}`).

`vheadunitindex=\langle num \rangle` The index of the Ones place in the `Tvhead` list, counting from the right. If zero, changed to `decimals + 1` (defaults to zero). For example, if `Tvhead={H,T,0,t,h,th}`, should be set as `vheadunitindex=4` (at least if `decimals` is not set to 3).

`hspace=\langle space \rangle` sets the horizontal space between boxes (defaults to `.5em`).

`vspace=\langle space \rangle` sets the vertical space between boxes (defaults to `1ex`).

`borderwidth=\langle space \rangle` sets the width of the frame around all the boxes (defaults to `1mm`).

`bordercol=<color>` sets the color of the frame (defaults to `lightgray`).

`backgroundcol=<color>` sets the background color (defaults to `white`).

`Tsign=<text>` sets the text to print at the top of the boxes to set the sign (Can also be redefined by `\def\AMCtextSign{<text>}`, and defaults to be empty).

`Tpoint=<text>` sets the text for the period. Can also be redefined by `\def\AMCdecimalPoint{<text>}`, and defaults to `\raisebox{1ex}{\bf .}`.

`Texponent=<text>` sets the text before the exponent. Can also be redefined by `\def\AMCexponent{<text>}`, and defaults to `\times 10^{\textasciicircum}`.

`scoring=<bool>` if `true`, a scoring strategy is given to AMC for this question. Defaults to `true`.

`scoreexact=<num>` gives the score for an exact answer (defaults to 2).

`exact=<num>` sets the maximal distance to the correct integer value (value without the decimal point) for an answer to be said *exact* and be rewarded to `scoreexact` points (defaults to 0).

`scoreapprox=<num>` gives the score for an approximative answer (defaults to 1).

`approx=<num>` sets the maximal distance to the correct integer value (value without the decimal point) for an answer to be said *approximative* and be rewarded to `scoreapprox` points (defaults to 0).

`scorewrong=<num>` gives the score for a wrong answer (defaults to 0).

`ignoreblank` can be used (only with number base 10) to ignore digits for which no box has been ticked. This way, ticking 5 for the first digit, no box for the second and 3 for the third digit will code the number 53, while this would have coded 503 without the `ignoreblank` option (because the default value for the second digit is 0).

`keepas=<name>` keeps the value entered by the student in variable `{<name>}`, for future use with `alsocorrect` in another question.

`alsocorrect=<expression>` gives another acceptable answer, that can be based on the values entered by the student in the previous questions.

The text added at the end of the questions using `\AMCnumericChoices` when not in the separate answer sheet (and when a separate answer sheet is requested by the `separateanswersheet` package option) can also be set redefining the `\AMCtextGoto` command, as:

```
\def\AMCtextGoto{\par{\bf\emph{Please code the answer on  
the separate answer sheet.}}}
```

3.8 French command names

For backward compatibility, some of `automultiplechoice` commands, environments and package option have their French counterpart. You can always use either the English command or the French equivalent. See table 1 for details.

3.9 Customisation

3.9.1 Boxes

`\AMCboxStyle` The command `\AMCboxStyle{<style>}` can be used to specify the shape, color and dimensions of the boxes to be ticked. The argument `<style>` is a coma-separated list of `<key>=<value>` pairs, with the following possible `<key>`s:

`shape` for the shape to be used: either `square` or `oval`. Note that if `oval` is used, the \LaTeX package `tikz` must be loaded.

`width` for the width of the boxes.

`height` for the height of the boxes.

`size` for the size of the boxes (sets `width` and `height`).

`down` for the length the boxes are to be moved down.

`rule` for the rule width.

`outsideseq` for the distance between the box and the letter when printed outside the box.

`color` for the color (only the box that are to be filled by the students and will be used for data capture). Use something that will be understood by the `xcolor` package.

Default values are

```
\AMCboxStyle{shape=square,size=2.5ex,down=.4ex,
             rule=.5pt,outsideseq=.1em,color=black}
```

Setting the box color allows to print the boxes with some color that won't disturb too much the data capture (for example red, but some light grey can also be considered).

Boxes styling	
<p>Question 9 $2 + 2 =$</p> <p>Ⓐ 1 Ⓑ 4 Ⓒ 10</p>	<pre>\AMCboxStyle{shape=oval,color=red} \begin{question}{sum}\$2+2={}\$ \begin{choiceshoriz}[o] \wrongchoice{1}\correctchoice{4} \wrongchoice{10} \end{choiceshoriz} \end{question}</pre>

3.9.2 Codes

One may adapt the codes rendering from `\AMCcodeGrid` to one's needs modifying the following lengths:

- `\AMCcodeHspace` is the amount of horizontal space between two columns of digits,
- `\AMCcodeVspace` is the amount of vertical space between two rows of digits,

Default values are `\AMCcodeHspace=.5em` `\AMCcodeVspace=.5em`

3.9.3 Answers

Environment `choicescustom` will make use of the three commands `\AMCbeginAnswer` (before the first answer), `\AMCendAnswer` (after the last answer) and `\AMCanswer{\langle box \rangle}{\langle text \rangle}` (for each answer) to format the answers. Redefining them properly, some different answers formatting can be achieved. However, this does not seem to work with non-trivial settings...

The `choicescustom` environment

Question 10 $2+2=$ ☐ 4 ☐ 3 ☐ 2)

```

\begin{question}{add}
  \def\AMCbeginAnswer{\$ \Big{$}
  \def\AMCendAnswer{\$ \Big}{$}
  \def\AMCanswer#1#2{#1 #2\hfill}
  2+2=
  \begin{choicescustom}
    \correctchoice{4}
    \wrongchoice{2}
    \wrongchoice{3}
  \end{choicescustom}
\end{question}

```

4 Implementation

This package uses the following other packages:

```

1 \RequirePackage{xcolor} % \fcolorbox to fill (or not) a box
2 \RequirePackage{fancyhdr} % \pagestyle{empty}
3 \RequirePackage{bophook} % \AtBeginPage
4 \RequirePackage{xkeyval} % \setkeys
5 \RequirePackage{rotating} % \rotatebox
6 \RequirePackage{fancybox} % \boxput
7 \RequirePackage{expl3}
8 \RequirePackage{csvsimple}
9 \RequirePackage{environ}
10 % \end{macrocode}
11 %
12 % First, we read the options that can be given by AMC through the
13 % |jobname-config.tex| file:
14 % \begin{macrocode}
15 \InputIfFileExists{\jobname-config.tex}%
16 {\message{Loading configuration file...^^J}}{}

```

`\AMC@amclog` Informations about questions and choices will be logged to a file with extension `amc`, to be parsed later. Macro `\AMC@amclog` writes to this file.

```

17 \newwrite\AMC@logfile
18 \immediate\openout\AMC@logfile=\jobname.amc
19 \def\AMC@amclog#1{\immediate\write\AMC@logfile{#1}}
20 \def\AMCmessage#1{\AMC@amclog{\string\message{#1}}}

```

`\AMC@LR` Colours management can be faulty in right-to-left mode: in these situations, we will make use of `\LR` from package `bidi` to get back to left-to-right mode. `\AMC@LR` is `\LR` if `bidi` is loaded.

```

21 \AtBeginDocument{\@ifpackageloaded{bidi}{%
22   \PackageInfo{automultiplechoice}{Package bidi loaded: using LR for boxes.}%
23   \let\AMC@LR=\LR}%
24 {\let\AMC@LR=\relax}}%
```

4.1 Variables

Counters and boolean variables defined here are internal and should not be modified by the user.

The package defines the following counters:

`\AMCload@counter` number of choices already loaded for current question.

`\AMCid@quest` current question ID number (see section 4.7).

`\AMCid@etud` current student sheet number.

`\AMCid@etudstart` starting student sheet number of the current `onecopy` bloc.

`\AMCid@check` current page checking number.

`\AMCid@etudfin` last student sheet number for the exam.

`\AMCnum@copies` number of exam sheets to produce.

It also defines the following switches:

`\ifAMC@ordre` if choices are never to be shuffled.

`\ifAMC@shuffleG` if groups shuffling is allowed.

`\ifAMC@fullGroups` if groups are always fully inserted by `\insertgroup` and fully copied by `\copygroup`, irrespective to the optional parameter.

`\ifAMC@correthead` if some correction header is to be printed at the beginning.

`\ifAMC@affichekeys` if questions keys are to be printed.

`\ifAMC@keyslines` if questions keys should be printed on a single line before the question text.

`\ifAMC@correc` if correct choices are to be checked on the produced document.

`\ifAMC@qbloc` if questions are to be included in \LaTeX boxes (so that they can't be splitted on two different pages).

`\ifAMC@asqbloc` if questions are to be included in \LaTeX boxes in the answer sheet (so that they can't be splitted on two different pages).

`\ifAMC@rbloc` if answers are to be included in \LaTeX boxes (so that they can't be splitted on two different columns for example).

`\ifAMC@textPos` if questions and answers positions are to be logged.

`\ifAMC@extractOnly` if the PDF is only built to extract questions and answers images.

`\ifAMCcomplete@multi` if a choice “None of these answers are correct.” is to be added to every multiple question.

`\ifAMCquestionNumber` if AMC should step up the question number for each new question.

`\ifAMC@calibration` if this L^AT_EX run is used to get page layouts.

`\ifAMC@plain` if `automultiplechoice` won’t try to load useful packages (`etex`, `environ`) that extend `automultiplechoice` capabilities.

`\ifAMCune@bonne` if there is at least one correct answer for the current question.

`\ifAMCtype@multi` if the current question is a multiple question.

`\ifAMC@watermark` if the document is a draft, not to be used for exam.

`\ifAMC@ensemble` if answers are to be given on a separate answers sheet.

`\ifAMC@inside@box` if a letter or digit is to be printed inside all boxes.

`\ifAMC@inside@digit` if digits are to be written inside boxes instead of letters (when using a separate answer sheet for example).

`\ifAMC@outside@box` if labels for boxes are to be printed outside the box on the answer sheet.

`\ifAMCformulaire@dedans` is true for questions inside separate answer sheet.

`\ifAMC@zoneformulaire` is true for codes (made by `\AMCcodeGrid`) inside separate answer sheet.

`\ifAMC@pagelayout` is true if the AMC page layout, with signs for scan analysis, is to be used.

`\ifAMC@postcorrect` corresponds to the use of the `postcorrect` package option.

`\ifAMC@automarks` corresponds to the use of the `automarks` package option.

`\ifAMC@invisible` is true is the DVI/PDF output is not important (used for example for scoring strategy extraction).

`\ifAMC@pdfform` is true if the output is a PDF form. This PDF will not be printed but will be filled by the students with a PDF reader and sent back to the teacher.

```

25 \newcount\AMCload@counter
26 \newcount\AMCid@quest\AMCid@quest=-1
27 \newcount\AMCid@check
28 \newcount\AMCid@etud\AMCid@etud=0
29 \newcount\AMCid@etudstart\AMCid@etudstart=0
30 \newcount\AMCid@etudfin
31 \newcount\AMCnum@copies

32 \newif\ifAMC@ordre\AMC@ordrefalse
33 \newif\ifAMC@shuffle\AMC@shuffleGtrue
34 \newif\ifAMC@fullGroups\AMC@fullGroupsfalse
35 \newif\ifAMC@correthead\AMC@corretheadfalse
36 \newif\ifAMC@affichekeys\AMC@affichekeysfalse
37 \newif\ifAMC@keyline\AMC@keylinefalse
38 \newif\ifAMC@correc\AMC@correcfalse

```



```

39 \newif\ifAMC@textPos\AMC@textPosfalse
40 \newif\ifAMC@extractOnly\AMC@extractOnlyfalse
41 \newif\ifAMC@qbloc\AMC@qblocfalse
42 \newif\ifAMC@asqbloc\AMC@asqblocfalse
43 \newif\ifAMC@rbloc\AMC@rblocfalse
44 \newif\ifAMC@complete@multi\AMC@complete@multifalse
45 \newif\ifAMC@questionNumber\AMC@questionNumbertrue
46 \newif\ifAMC@calibration\AMC@calibrationfalse
47 \newif\ifAMC@catalog\AMC@catalogfalse
48 \newif\ifAMC@plain\AMC@plainfalse
49 \newif\ifAMC@bonne
50 \newif\ifAMC@type@multi
51 \newif\ifAMC@watermark\AMC@watermarktrue
52 \newif\ifAMC@inside@box\AMC@inside@boxfalse
53 \newif\ifAMC@outside@box\AMC@outside@boxfalse
54 \newif\ifAMC@ensemble\AMC@ensemblefalse
55 \newif\ifAMC@inside@digit\AMC@inside@digitfalse
56 \newif\ifAMC@formulaire@dedans\AMC@formulaire@dedansfalse
57 \newif\ifAMC@zoneformulaire
58 \newif\ifAMC@pagelayout\AMC@pagelayouttrue
59 \newif\ifAMC@postcorrect\AMC@postcorrectfalse
60 \newif\ifAMC@automarks\AMC@automarksfalse
61 \newif\ifAMC@invisible\AMC@invisiblefalse
62 \newif\ifAMC@pdfform\AMC@pdfformfalse
63 \let\AMC@completeMulti=\AMC@complete@multitru
64 \let\AMC@noCompleteMulti=\AMC@complete@multifalse

```

`\AMCid@name` The package also defines command `\AMCid@name` to be the current question identifier key.

```
65 \def\AMCid@name{}
```

4.2 Dimensions

`\AMCformVSpace` The following dimensions can be modified by the user to adjust questions formatting:

`\AMCformHSpace` `\AMCformVSpace` is the amount of vertical space between two questions in a separate answer sheet.

`\AMCformHSpace` is the amount of horizontal space between two answers boxes in a separate answer sheet.

`\AMCinterIrep` is the amount of vertical space to be added between two answers.

`\AMCinterBrep` is the amount of vertical space between two boxed answers (see `\AMCBoxedAnswers` and `\ifAMC@rbloc`).

`\AMCinterIquest` is the amount of vertical space left after a question, in standard mode (without package option `box`).

`\AMCinterBquest` is the amount of vertical space left after a question, in 'boxed' mode (with package option `box`).

`\AMCpostNquest` is the amount of vertical space left after a numeric question.

`\AMCpostOquest` is the amount of vertical space left after an open question.

```

66 \newdimen\AMCformVSpace\AMCformVSpace=1.2ex
67 \newdimen\AMCformHSpace\AMCformHSpace=.3em
68 \newdimen\AMCinterIrep\AMCinterIrep=\z@
69 \newdimen\AMCinterBrep\AMCinterBrep=.5ex
70 \newdimen\AMCinterIquest\AMCinterIquest=\z@
71 \newdimen\AMCinterBquest\AMCinterBquest=3ex
72 \newdimen\AMCpostNquest\AMCpostNquest=1.5ex
73 \newdimen\AMCpostOquest\AMCpostOquest=7mm

```

4.3 Human readable sheet ID position

`\AMCidsPosition` The position of the human readable sheet ID, near the corresponding binary boxes, is set with the `\AMCidsPosition` command, in the form `\AMCidsPosition{pos=<position>,width=<width>,height=<height>}`, where *<position>* is one of *side* (default), *top* and *none*, *<width>* is the width of the box enclosing the ID (default value is 4cm), and *<height>* is the height of the box enclosing the ID (default value is 3ex).

```

74 \newif\ifAMCids@top
75 \newif\ifAMCids@side
76 \newdimen\AMCids@width
77 \newdimen\AMCids@height
78 \define@choicekey*{AMCids}{pos}[ \AMCidsVar\AMCidsVarN]{none,top,side}{%
79   \ifcase\AMCidsVarN\relax
80     \AMCids@topfalse\AMCids@sidefalse
81   \or
82     \AMCids@toptrue\AMCids@sidefalse
83   \or
84     \AMCids@topfalse\AMCids@sidesettrue
85   \fi
86 }
87 \define@key{AMCids}{width}{\AMCids@width=#1}
88 \define@key{AMCids}{height}{\AMCids@height=#1}
89 \def\AMCidsPosition#1{\setkeys{AMCids}{#1}}
90 \AMCidsPosition{pos=side,width=4cm,height=3ex}

```

4.4 Localisation

In this section, some localised strings or commands are defined, for English, French and Spanish languages.

`\AMCtext` To modify these texts, you can use command `\AMCtext`. For example, `\AMCtext{draft}{<text>}` sets the text to be printed behind each page of a draft exam.

```

91 \def\AMCtext#1#2{\expandafter\def\cename{AMC@loc@#1}\endcsname{#2}}
92 \def\AMClocalized#1{\cename{AMC@loc@#1}\endcsname}

```

4.4.1 English

Text indicating draft exams:

```
93 \def\AMC@loc@draft{DRAFT}
```

Message at page bottom when compiled out of AMC gui:

```

94 \def\AMC@loc@message{For your examination, preferably print
95 documents compiled from auto-multiple-choice.}

```

Announcing a question in a separate sheet (parameter #1 is the question number):

```
96 \def\AMC@loc@qf#1{\textbf{Question #1:}}
```

Announcing a question (parameter #1 is the question number and parameter #2 can be the multiple question symbol, or be empty):

```
97 \def\AMC@loc@q#1#2{\textbf{Question #1} #2}
```

Headers for corrected version and catalog:

```
98 \def\AMC@loc@corrected{Corrected}
```

```
99 \def\AMC@loc@catalog{Catalog}
```

Localization text for Explanation

```
100 \def\AMC@loc@explain{\textit{\textbf{Explanation: }}}}
```

Last choice added at the end for multiple questions when option `completemulti` is used:

```
101 \def\AMC@loc@none{None of these answers are correct.}
```

Word for 'question', singular and plural forms:

```
102 \def\AMC@loc@question{question}
```

```
103 \def\AMC@loc@questions{questions}
```

Default text to write in the students' name box:

```
104 \def\AMC@loc@namesurname{Name and surname:}
```

4.4.2 Catalan

Catalan localisation is called with option `lang=CA`.

```
105 \def\AMC@loc@CA{
106   \def\AMC@loc@draft{PROJECTE}
107   \def\AMC@loc@message{Pel vostre examen, imprimiu preferiblement
108     els documents compilats amb l'ajuda de auto-multiple-choice.}
109   \def\AMC@loc@qf##1{\textbf{Pregunta ##1 :}}
110   \def\AMC@loc@q##1##2{\textbf{Pregunta ##1} ##2}
111   \def\AMC@loc@corrected{Correcci\`o}
112   \def\AMC@loc@catalog{Cat\`aleg}
113   \def\AMC@loc@explain{\textit{\textbf{Explicaci\`o : }}}
114   \def\AMC@loc@none{Cap de les respostes \`es correcta.}
115   \def\AMC@loc@question{pregunta}
116   \def\AMC@loc@questions{preguntes}
117   \def\AMC@loc@namesurname{Nom i cognoms:}
118 }
```

4.4.3 Dutch

Dutch localisation is called with option `lang=NL`.

```
119 \def\AMC@loc@NL{
120   \def\AMC@loc@draft{Ontwerp}
121   \def\AMC@loc@message{Gebruik bij uw proefwerk bij voorkeur die
122     documenten welke door auto-multiple-choice zijn aangemaakt.}
123   \def\AMC@loc@qf##1{\textbf{Vraag ##1 :}}
124   \def\AMC@loc@q##1##2{\textbf{Vraag ##1} ##2}
125   \def\AMC@loc@corrected{Correctie}
126   \def\AMC@loc@catalog{Catalogus}
127   \def\AMC@loc@none{Geen van de antwoorden is juist.}
128   \def\AMC@loc@question{vraag}
```

```

129 \def\AMC@loc@questions{vragen}
130 \def\AMC@loc@namesurname{Achternaam en voornaam:}
131 }

```

4.4.4 French

French localisation is called with option `francais`, or `lang=FR`.

```

132 \def\AMC@loc@FR{
133   \def\AMC@loc@draft{PROJET}
134   \def\AMC@loc@message{Pour votre examen, imprimez de pr\`ef\`erence
135     les documents compil\`es \`a l'aide de auto-multiple-choice.}
136   \def\AMC@loc@qf##1{\textbf{Question ##1 :}}
137   \def\AMC@loc@q##1##2{\textbf{Question ##1} ##2}
138   \def\AMC@loc@corrected{Correction}
139   \def\AMC@loc@catalog{Catalogue}
140   \def\AMC@loc@explain{\textit{\textbf{Explication : }}}
141   \def\AMC@loc@none{Aucune de ces r\`eponses n'est correcte.}
142   \def\AMC@loc@question{question}
143   \def\AMC@loc@questions{questions}
144   \def\AMC@loc@namesurname{Nom et pr\`enom :}
145 }

```

4.4.5 German

German localisation is called with option `lang=DE`.

```

146 \def\AMC@loc@DE{
147   \def\AMC@loc@draft{ENTWURF}
148   \def\AMC@loc@message{Benutzen Sie f\"ur Ihre Pr\"ufung bevorzugt Dokumente die mit
149     auto-multiple-choice erstellt wurden.}
150   \def\AMC@loc@qf##1{\textbf{Frage ##1 :}}
151   \def\AMC@loc@q##1##2{\textbf{Frage ##1} ##2}
152   \def\AMC@loc@corrected{Korrektur}
153   \def\AMC@loc@catalog{Katalog}
154   \def\AMC@loc@explain{\textit{\textbf{Erkl\"arung : }}}
155   \def\AMC@loc@none{Keine dieser Antworten ist korrekt.}
156   \def\AMC@loc@question{Frage}
157   \def\AMC@loc@questions{Fragen}
158   \def\AMC@loc@namesurname{Vor- und Nachname:}
159 }

```

4.4.6 Italian

Italian localisation is called with option `lang=IT`.

```

160 \def\AMC@loc@IT{
161   \def\AMC@loc@draft{BOZZA}
162   \def\AMC@loc@message{Per l'esame, \`e preferibile stampare i documenti
163     a partire da auto-multiple-choice.}
164   \def\AMC@loc@qf##1{\textbf{Domanda ##1:}}
165   \def\AMC@loc@q##1##2{\textbf{Domanda ##1} ##2}
166   \def\AMC@loc@corrected{Correzione}
167   \def\AMC@loc@catalog{Catalogo}
168   \def\AMC@loc@none{Nessuna risposta \`e giusta.}
169   \def\AMC@loc@question{domanda}

```

```

170 \def\AMC@loc@questions{domande}
171 \def\AMC@loc@namesurname{Nome e cognome:}
172 }

```

4.4.7 Norwegian

Norwegian localisation is called with option lang=NO.

```

173 \def\AMC@loc@NO{
174   \def\AMC@loc@draft{UTKAST}
175   \def\AMC@loc@message{Det anbefales {\aa} skrive ut dokumentet
176   for gjennomgang \direkte fra auto-multiple-choice.}
177   \def\AMC@loc@qf##1{\textbf{Oppgave ##1 :}}
178   \def\AMC@loc@q##1##2{\textbf{Oppgave ##1} ##2}
179   \def\AMC@loc@corrected{Rettet}
180   \def\AMC@loc@catalog{Katalog}
181   \def\AMC@loc@none{Ingen svar er riktige.}
182   \def\AMC@loc@question{oppgave}
183   \def\AMC@loc@questions{oppgave}
184   \def\AMC@loc@namesurname{Etternavn og fornavn:}
185 }

```

4.4.8 Portuguese

Portuguese localisation is called with option lang=PT.

```

186 \def\AMC@loc@PT{
187   \def\AMC@loc@draft{RASCUNHO}
188   \def\AMC@loc@message{Para o seu exame, use preferencialmente documentos compilados do auto-multiple-choice.}
189   \def\AMC@loc@qf##1{\textbf{Quest\~ao ##1:}}
190   \def\AMC@loc@q##1##2{\textbf{Quest\~ao ##1} ##2}
191   \def\AMC@loc@corrected{Corrigido}
192   \def\AMC@loc@catalog{Cat\'alogo}
193   \def\AMC@loc@explain{\textit{\textbf{Justifique: }}}}
194   \def\AMC@loc@none{Nenhuma das respostas apresentadas est\'a correta.}
195   \def\AMC@loc@question{Quest\~ao}
196   \def\AMC@loc@questions{Quest\~oes}
197   \def\AMC@loc@namesurname{Nome e apelido:}
198 }

```

4.4.9 Spanish

Spanish localisation is called with option lang=ES.

```

199 \def\AMC@loc@ES{
200   \def\AMC@loc@draft{BORRADOR}
201   \def\AMC@loc@message{Para revisi\'on, preferentemente imprimir documentos compilados
202   desde auto-multiple-choice.}
203   \def\AMC@loc@qf##1{\textbf{Pregunta ##1 :}}
204   \def\AMC@loc@q##1##2{\textbf{Pregunta ##1} ##2}
205   \def\AMC@loc@corrected{Correcci\'on}
206   \def\AMC@loc@catalog{Cat\'alogo}
207   \def\AMC@loc@none{Ninguna de estas preguntas son correctas.}
208   \def\AMC@loc@question{pregunta}
209   \def\AMC@loc@questions{preguntas}
210   \def\AMC@loc@namesurname{Nombre y apellidos:}

```


`\AMCrandomseed` The seed of this generator is set to 1515, but another value can be given using the command `\AMCrandomseed{<seed>}`.

```
243 \AMC@SRset{1515}
244 \def\AMCrandomseed#1{\AMC@SRset{#1}}
```

4.6.2 Uniform random deviates

`\AMC@SRnextByte` This generator is used to build first a 20-bit uniform integer generator (macro `\AMC@SRnextByte`).
`\AMC@SRmax` Then, using modulo, a (nearly) uniform generator on $\{0, \dots, n - 1\}$ is built: command `\AMC@SRmax{n}` puts in `\AMC@SR@count` the random deviate.

```
245 \newcount\AMC@SR@count
246 \def\AMC@SR@time{\AMC@SRset{\time}}
247 \newcount\AMC@SRnum
248 \def\AMC@SRnextByte{\AMC@SRnum=\z@%
249   \AMC@SR@count=20%
250   \loop\multiply\AMC@SRnum\tw@%
251     \AMC@SRtest{\advance\AMC@SRnum\@ne}\}%
252   \ifnum\AMC@SR@count>\@ne\advance\AMC@SR@count\m@ne\repeat%
253 }
254 \newcommand\AMC@SRmax[1]{\AMC@SRnextByte%
255   \AMC@SR@count=\AMC@SRnum%
256   \divide\AMC@SR@count by #1\relax%
257   \multiply\AMC@SR@count by #1\relax%
258   \advance\AMC@SRnum by -\AMC@SR@count%
259 }
```

4.6.3 Tokens shuffling

`\AMCsw@p` The package defines the macro `\AMCsw@p` to swap the values of two token registers given as
`\AMC@shuffletoks` parameters.

After defining n token registers `\foo@i`, `\foo@ii`, `\foo@iii`, `\foo@iv` and so on, you can shuffle them using `\AMC@shuffletoks[<a>]{<n>}{<foo>}`. With optional argument `<a>`, registers are shuffled from number `<a>` to `<n>` (default value for `<a>` is 1).

```
260 \newcount\AMC@sti
261 \newcount\AMC@stil
262 \newtoks\AMCsw@p@
263 \newcommand\AMCsw@p[2]{%
264   \global\AMCsw@p@=#1%
265   \global#1=#2%
266   \global#2=\AMCsw@p@}
267 \newcommand{\AMC@shuffletoks}[3][\@ne]{%
268   \AMC@sti=#2\relax%
269   \AMC@stil=#2\relax%
270   \advance\AMC@stil\@ne%
271   \advance\AMC@stil -#1\relax%
272   \@whilenum\AMC@sti>#1\do{%
273     \AMC@SRmax{\AMC@stil}\advance\AMC@SRnum #1\relax%
274     \AMCsw@p{\csname #3\romannumeral\AMC@SRnum\endcsname}%
275       {\csname #3\romannumeral\AMC@sti\endcsname}%
276     \advance\AMC@sti\m@ne\relax%
277     \advance\AMC@stil\m@ne\relax%
278   }}
```

4.7 Keys numbering

`\AMC@unnumero` This package allocates a unique integer ID to each question key from the questionnaire.
`\AMC@affecte` The counter `\AMC@numerotation` keeps track of the number of keys which already had an ID. Command `\AMC@definitnumero{n}{key}` allocates ID n to the key `key`. Command `\AMC@prepare{key}` looks if an ID had already been associated to `key`, and, if not, makes a new ID allocation for `key`. Command `\AMC@unnumero{key}` returns the ID associated with `key` (creating one if necessary). Command `\AMC@affecte{key}{\cnt}` give to counter `\cnt` the value of the ID associated to `key` (creating one if necessary).

```
279 \newcount\AMC@numerotation\AMC@numerotation=\z@%
280 \def\AMC@definitnumero#1#2{\AMCmessage{NUM=#1=#2}%
281   \expandafter\global\expandafter\def\csname AMC@numtab@#2\endcsname{#1}}
282 \def\AMC@prepare#1{\expandafter\ifx\csname AMC@numtab@#1\endcsname\relax%
283   \global\advance\AMC@numerotation\@ne%
284   \expandafter\AMC@definitnumero\expandafter{\the\AMC@numerotation}{#1}\fi}
285 \def\AMC@unnumero#1{\AMC@prepare{#1}\csname AMC@numtab@#1\endcsname}
286 \def\AMC@affecte#1#2{\AMC@prepare{#1}\global#2=\csname AMC@numtab@#1\endcsname}
```

4.8 Boxes

4.8.1 Character logging

`\AMC@logchar` The command `\AMC@logchar{<char>}{<key>}` logs the character written in the box referenced as `<key>` in the .amc file. This is used in catalog mode, to get understandable references to answers from the statistics tables of the ODS export.

```
287 \def\AMC@logchar#1#2{%
288   \protected@write\AMC@logfile{}{%
289     \string\answer%
290     {\the\AMCid@etud/\thepage:#2}%
291     {#1}}%
292 }
```

4.8.2 Position logging

`\AMC@tracebox` Command `\AMC@tracebox{<trace>}{<key>}{<content>}` makes a L^AT_EX box around `<content>`,
`\AMC@pagepos` and, if `<trace>` is not empty, logs to the .xy file informations to be able to compute exact location of this box on the page, attached to the box identification `<key>`.

Command `\AMC@pagepos` logs page and page size informations at the beginning of each page.

```
293 \def\AMC@shapename@{\ifAMC@invisible none\else\AMC@shapename\fi}
294 \def\AMC@tracepos#1#2{%
295   \ifAMC@calibration\ifx\@empty#1\@empty\else%
296     \pdfsavepos\protected@write\AMC@XYFILE{}{%
297       \string\tracepos%
298       {\the\AMCid@etud/\thepage:#2}%
299       {\noexpand\number\pdflastxpos sp}%
300       {\noexpand\number\pdflastypos sp}%
301       {\AMC@shapename}}%
302   \fi\fi}
303 \def\AMC@traceposx#1#2{%
304   \ifAMC@calibration\ifx\@empty#1\@empty\else%
305     \pdfsavepos\protected@write\AMC@XYFILE{}{%
306       \string\tracepos%
```



```

307     {\the\AMCid@etud/\thepage:#2}%
308     {\noexpand\number\pdflastxpos sp}%
309     {0sp}%
310     {\AMC@shapename}}%
311   \fi\fi}
312 \def\AMC@traceposy#1#2{%
313   \ifAMC@calibration\ifx\@empty#1\@empty\else%
314     \pdfsavepos\protected@write\AMC@XYFILE{}\{%
315       \string\tracepos%
316       {\the\AMCid@etud/\thepage:#2}%
317       {0sp}%
318       {\noexpand\number\pdflastypos sp}%
319       {\AMC@shapename}}%
320 \fi\fi}
321 \newcommand\AMC@tracebox[3]{%
322   \vbox{\AMC@traceposy{#1}{#2}%
323     \hbox{\AMC@traceposx{#1}{#2}#3\AMC@traceposx{#1}{#2}}%
324     \AMC@traceposy{#1}{#2}}}%
325 \def\AMC@pagepos{%
326   \ifAMC@calibration\protected@write\AMC@XYFILE{}\{%
327     \string\page%
328     {\the\AMCid@etud/\thepage/\the\AMCid@check}%
329     {\the\paperwidth}{\the\paperheight}%
330     {\the\pdfpagewidth}{\the\pdfpageheight}}\fi}

```

`\AMCdontScan` The commands `\AMCdontScan`, `\AMCdontAnnotate` and `\AMCretick` write into the `xy` file instructions related to the current question.

`\AMCretick` 331 `\newcommand{\AMCdontScan}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\dontscan{\the\AMCid@etud`
332 `\newcommand{\AMCdontAnnotate}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\dontannotate{\the\AM`
333 `\newcommand{\AMCretick}{\ifAMC@calibration\immediate\write\AMC@XYFILE{\string\retick{\the\AMCid@etud,\th`
334 `%`

`\AMC@tracechar` The macro `\AMC@tracechar{<char>}{<unused>}{<trace>}{<key>}` is used to log (for further processing with AMC), into to `.xy` file, the character used to identify the box.

```

335 \newcommand\AMC@tracechar[4]{%
336   \ifAMC@calibration\ifx\@empty#3\@empty\else%
337     \protected@write\AMC@XYFILE{}\{%
338       \string\boxchar{\the\AMCid@etud/\thepage:#4}{#1}%
339     }%
340   \fi\fi%
341 }

```

`amcxyfile (env.)` The following lines defines an environment to tag positions outputs for a particular part of the document. This is used mainly for documentation or testing.

```

342 \newenvironment{amcxyfile}[1]{%
343   \protected@write\AMC@XYFILE{}\{\string\xyopen{#1}}%
344 }{%
345   \protected@write\AMC@XYFILE{}\{\string\xyclose{}}%
346 }

```

`\AMCzone` The `\AMCzone[<flags>]{<zone name>}{<zone content>}` is a simple call to `\AMC@tracebox`:

```

347 \newcommand{\AMCzone}[3][\AMC@tracebox{1}{__zone:#1:#2}{#3}]

```

`\namefield` The `\namefield{<name field content>}` is a simple call to `\AMCzone`:

```
348 \newcommand{\namefield}[2][id]{\AMCzone[#1]{__n}{#2}}
```

It is used to enclose the page region where students are to write their names, so as to retrieve it easily from the scans.

`\namefielddots` The command `\namefielddots` can be used to fill a line with dots (printed sheets) or use a text field in PDF forms:

```
349 \newcommand{\namefielddots}{%
350   \noindent%
351   \ifAMC@pdfform%
352     \hspace*{\fill}%
353     \TextField[name={\the\AMCid@etud:namefield},width=.95\linewidth,bordercolor=0 0 0]{}%
354     \hspace*{\fill}
355   \else%
356     \dotfill
357   \fi%
358 }
```

As an example,

```
\namefield{\fbox{%
  \begin{minipage}{5cm}
    Name:

    \vspace*{.5cm}
    \namefielddots
    \vspace{2mm}
  \end{minipage}}}
```

produces the following box:

Name:

and outputs information about the position of the box in the `.xy` file, as seen in section 5.1.

4.8.3 Boxes to be checked by students

`\AMC@answerBox@` There are two styles for boxes to be checked by the students. The first one is an empty box, printed beside the answer. The second is a box with a character in it. It is mainly used when answers are to be given on a separate answer sheet.

These boxes can be drawn using command `\AMC@answerBox@{<char>}{<answer>}{<trace>}{<key>}`: `<char>` is the character to print inside the box, `<trace>` is non-empty if you want to log the box position in the `.xy` file, `<key>` is the box identification, and `<answer>` is an answer to be written in the box (or `\AMC@checkbox` for filling the box).

Depending on the required shape for the boxes, the corresponding

`\AMC@shape@xxx{<char>}{<answer>}{<trace>}{<key>}`

command is used.

- `\AMC@answerBox@{K}{1}{test}` produce the box \boxed{K} , writing the lines in the .xy file shown in section 5.2.
- `\AMC@answerBox@{K}{\AMC@checkedbox}{}` produces $\boxed{\blacksquare}$
- `\AMC@answerBox@{}{8}{}` produces $\boxed{8}$
- `\AMC@answerBox@{K}{8}{1}{testb}` produces $\textcircled{8}$ with `\AMCboxStyle{shape=oval,color=red}`

```

359 \def\AMC@checkedbox{}
360 \let\AMC@new@savebox=\newsavebox
361 \let\AMC@save@box=\savebox
362 \let\AMC@use@box=\usebox
363 \newif\ifAMC@draw@cross

```

The `\AMC@smashcentered{<text>}` command shows the `<text>` centered at point.

```

364 \newbox\AMC@smashbox
365 \newdimen\AMC@smashboxheight
366 \newcommand{\AMC@smashcentered}[1]{%
367   \setbox\AMC@smashbox\hbox{#1}%
368   \AMC@smashboxheight=\ht\AMC@smashbox%
369   \advance\AMC@smashboxheight by \dp\AMC@smashbox%
370   \vfuzz=\AMC@smashboxheight\hfuzz=\wd\AMC@smashbox%
371   \hspace*{-.5\wd\AMC@smashbox}\hbox to .5\wd\AMC@smashbox{%
372     \vbox to 0pt{%
373       \vspace*{-.5\AMC@smashboxheight}\vbox to .5\AMC@smashboxheight{%
374         \box\AMC@smashbox}}}%
375 }%

```

`\AMC@setcolors@{<trace>}{<answer>}` sets colours `\AMC@boxcolor@` and `\AMC@fillcolor@` according to its arguments. It also sets the `\ifAMC@draw@cross` switch if AMC should draw a cross instead of filling the box.

```

376 \newcommand\AMC@setcolors@[2]{%
377   \def\AMC@boxcolor@{\AMC@boxcolor}%
378   \ifx\@empty#1\@empty \def\AMC@boxcolor@{black}\fi%
379   \ifAMC@correc\def\AMC@boxcolor@{black}\fi%
380   \def\AMC@fillcolor@{\ifx #2\AMC@checkedbox%
381     \AMC@boxcolor@\else white\fi}%
382   \AMC@draw@crossfalse%
383   \ifKV@AMCdim@cross\ifx #2\AMC@checkedbox%
384     \AMC@draw@crosstrue\fi\fi%
385 }
386 \newcommand\AMC@answerBox@[4]{%
387   \ifAMC@catalog%
388     \AMC@logchar{#1}{#4}%
389     \fi%
390     \AMC@LR{\hspace{0pt}%
391       \lower\AMC@boxeddown\hbox{\csname AMC@shape@\AMC@shapename@\endcsname%
392         {\AMCchoiceLabelFormat{#1}}{#2}{#3}{#4}}}%
393 }
394 \newcommand\AMC@shapeprepare@square{}
395 \newcommand\AMC@shape@square[4]{%
396   \fboxsep=\z@\fboxrule=\AMC@boxedrule%
397   \AMC@setcolors@{#3}{#2}%
398   \ifKV@AMCdim@cross\def\AMC@fillcolor@{white}\fi%

```

```

399 \fcolorbox{\AMC@boxcolor@}{\AMC@fillcolor@}%
400 {%
401   \boxput*(0,0){%
402     \ifAMC@draw@cross\AMC@crosschar\fi%
403   }{%
404     \vbox to \AMC@boxedheight{%
405       \AMC@tracepos{#3}{#4}%
406       \vfill%
407       \hbox to \AMC@boxedwidth{\hfill%
408         \AMC@smashcentered{\textcolor{\AMC@boxcolor@}{#1}}%
409         \AMC@smashcentered{#2}%
410         \hfill}\vfill}}%
411     \AMC@tracepos{#3}{#4}}%
412 }

```

`\AMC@makeovalbox{<trace>}{<answer>}{<box>}` prepares an oval frame in the L^AT_EX box `<box>`.

```

413 \newcommand\AMC@makeovalbox[3]{%
414   \AMC@setcolors@{#1}{#2}%
415   \ifKV@AMCdim@cross\def\AMC@fillcolor@{white}\fi%
416   \AMC@save@box{#3}{%
417     \begin{tikzpicture}%
418       \useasboundingbox (-0.5\AMC@boxedwidth-0.5\AMC@boxedrule,0.5\AMC@boxedheight+0.5\AMC@boxedrule)
419       rectangle (0.5\AMC@boxedwidth+0.5\AMC@boxedrule,-0.5\AMC@boxedheight-0.5\AMC@boxedrule);
420       \draw[\AMC@boxcolor@,fill=\AMC@fillcolor@,line width=\AMC@boxedrule,rounded corners=\AMC@oval@radi
421       (-0.5\AMC@boxedwidth,0.5\AMC@boxedheight)
422       rectangle (0.5\AMC@boxedwidth,-0.5\AMC@boxedheight);
423       \ifAMC@draw@cross
424         \draw[\AMC@boxcolor@,line width=\AMC@crossrule]
425         (-0.5\AMC@boxedwidth,0.5\AMC@boxedheight) -- (0.5\AMC@boxedwidth,-0.5\AMC@boxedheight)
426         (0.5\AMC@boxedwidth,0.5\AMC@boxedheight) -- (-0.5\AMC@boxedwidth,-0.5\AMC@boxedheight);
427       \fi
428     \end{tikzpicture}}%
429 }
430 \newcommand\AMC@shapeprepare@oval[%
431   \ifx\AMC@ovalbox@R\@undefined\else%
432     \AMC@makeovalbox{1}{\AMC@ovalbox@R}%
433     \AMC@makeovalbox{1}{\AMC@checkedbox}{\AMC@ovalbox@RF}%
434     \AMC@makeovalbox{}{\AMC@ovalbox@}%
435     \AMC@makeovalbox{}{\AMC@checkedbox}{\AMC@ovalbox@F}%
436   \fi%
437 }
438 \newcommand\AMC@shape@oval[4]{%
439   \AMC@setcolors@{#3}{#2}%
440   \AMC@tracebox{#3}{#4}{\boxput*(0,0){%
441     \AMC@smashcentered{\textcolor{\AMC@boxcolor@}{#1}}%
442     \AMC@smashcentered{#2}%
443   }{%
444     \ifx\@empty#3\@empty%
445       \ifx #2\AMC@checkedbox%
446         \AMC@use@box{\AMC@ovalbox@F}%
447       \else%
448         \AMC@use@box{\AMC@ovalbox@}%
449       \fi%
450     \else%

```

```

451     \ifx #2\AMC@checkbox%
452       \AMC@use@box{\AMC@ovalbox@RF}%
453     \else%
454       \AMC@use@box{\AMC@ovalbox@R}%
455     \fi%
456   \fi%
457 }}%
458 }
459 \newcommand\AMC@shapeprepare@form{}
460 \newcommand\AMC@shape@form@base[5]{%
461   \ifx #2\AMC@checkbox%
462     \def\AMC@shape@form@ticked{true}%
463   \else%
464     \def\AMC@shape@form@ticked{false}%
465   \fi%
466   \AMC@tracebox{#3}{#4}{%
467     \CheckBox[checked=\AMC@shape@form@ticked,%
468       checkboxsymbol=\ding{110},name={#5},%
469       bordercolor=0 0 0,%
470       width=\AMC@boxedwidth,height=\AMC@boxedheight]{#3}%
471   }%
472 }
473 \newcommand\AMC@shape@form[4]{%
474   \AMC@shape@form@base{#1}{#2}{#3}{#4}{\the\AMCid@etud:#4}%
475 }
476 \newcommand\AMC@shapeprepare@none{}
477 \newcommand\AMC@shape@none[4]{#1 }

```

\AMC@answerBox Command \AMC@answerBox is the same as \AMC@answerBox@, but if $\langle char \rangle$ is empty, it is replaced by an arabic or alphabetical counter, depending on the use of the **digits** package option.

\AMCchoiceLabel To use another way to label the choices boxes, the user can redefine the \AMCchoiceLabel macro, which takes as argument the name of the counter used to number the choices. One can for example use \def\AMCchoiceLabel#1{\alph{#1}} to ask for lowercase letters.

To write these labels with another font, size, or so, the user can redefine the \AMCchoiceLabelFormat macro, which takes as argument the label. One can for example get sans serif bold labels with \def\AMCchoiceLabelFormat#1{\textsf{\textsf{#1}}}.

```

478 \def\AMCchoiceLabel#1{%
479   \ifAMC@inside@digit\arabic{#1}%
480   \else\Alph{#1}\fi%
481 }
482 \def\AMCchoiceLabelFormat#1{#1}
483 \newcounter{AMC@ncase}
484 \setcounter{AMC@ncase}{0}
485 \newcommand\AMC@answerBox[4]{%
486   \AMC@answerBox@{\ifx\@empty#1\@empty%
487     \AMCchoiceLabel{AMC@ncase}%
488     \else #1\fi}{#2}{#3}{#4}}

```

\AMCboxStyle The dimensions of these box are managed by \AMCboxDimensions{ $\langle sizes \rangle$ }, where $\langle sizes \rangle$ is a coma separated list of $\langle name \rangle = \langle dimension \rangle$ constructs. Here, $\langle name \rangle$ can be **size** for the box size, **rule** for the box rule width, **down** for moving the box down, **color** for the box color and **outsidesep** for the distance between the box and the letter (when outside the box).

The $\langle color \rangle$ value given to `color` is a color that should be defined for the `xcolor` package. This color is used only in the case the box will be used for data capture: it is not used on the corrected answer sheet (`answers` or `indivanswers` package option), and not used on the subject part of an exam with a separate answer sheet (`separateanswersheet` package option).

The `\AMCboxColor{ $\langle color \rangle$ }` command is defined as an alias to `\AMCboxStyle{color= $\langle color \rangle$ }`, and `\AMCboxDimensions` as an alias to `\AMCboxStyle`, for backward compatibility.

```

489 \newlength\AMC@boxedrule
490 \newlength\AMC@crossrule
491 \newlength\AMC@boxeddown
492 \newlength\AMC@boxedwidth
493 \newlength\AMC@boxedheight
494 \newlength\AMC@oval@radius
495 \newlength\AMC@outside@sep
496 \define@choicekey{AMCdim}{shape}{square,oval,form,none}{\def\AMC@shapename{#1}}
497 \define@key{AMCdim}{size}{\AMC@boxedwidth=#1\AMC@boxedheight=#1}
498 \define@key{AMCdim}{height}{\AMC@boxedheight=#1}
499 \define@key{AMCdim}{width}{\AMC@boxedwidth=#1}
500 \define@key{AMCdim}{rule}{\AMC@boxedrule=#1}
501 \define@key{AMCdim}{outsidesep}{\AMC@outside@sep=#1}
502 \define@key{AMCdim}{down}{\AMC@boxeddown=#1}
503 \define@key{AMCdim}{color}{\def\AMC@boxcolor{#1}}
504 \define@boolkey{AMCdim}{cross}[false]{ }
505 \define@key{AMCdim}{crosschar}{\textbf{\textsf{X}}}{\def\AMC@crosschar{#1}}
506 \define@key{AMCdim}{crossrule}[1.5pt]{\AMC@crossrule=#1}
507 \def\AMC@shapeprepare{\csname AMC@shapeprepare@\AMC@shapename@ \endcsname}
508 \def\AMCboxStyle#1{%
509   \setkeys{AMCdim}{#1}%
510   \ifnum\AMC@boxedwidth<\AMC@boxedheight%
511     \AMC@oval@radius=\AMC@boxedwidth\divide\AMC@oval@radius\tw@%
512   \else%
513     \AMC@oval@radius=\AMC@boxedheight\divide\AMC@oval@radius\tw@%
514   \fi%
515   \AMC@shapeprepare%
516 }
517 \AMCboxStyle{shape=square,size=2.5ex,down=.4ex,rule=.5pt,outsidesep=.1em,color=black,cross,crosschar,crossrule}
518 \newcommand\AMCboxColor[1]{\AMCboxStyle{color=#1}}
519 \let\AMCboxDimensions=\AMCboxStyle

```

`\AMCboxOutsideLetter` Command `\AMC@box{ $\langle char \rangle$ }{ $\langle answer \rangle$ }` prints a box with character $\langle char \rangle$ inside, showing answer $\langle answer \rangle$ (`\AMC@checkbox` to get a filled box), using global variables to identify the box (`\AMC@formBox@` (question and choice).

`\AMC@formBox` It calls `\AMC@formBox@{ $\langle char \rangle$ }{ $\langle answer \rangle$ }{ $\langle trace \rangle$ }{ $\langle key \rangle$ }` to actually render the box.

`\AMC@formBox@` Command `\AMC@formBox` simply sets the first argument when empty before calling `\AMC@formBox@`.

The command `\AMCboxOutsideLetter{ $\langle box \rangle$ }{ $\langle char \rangle$ }` is called to print the box *and* the character $\langle char \rangle$ outside (and next to) it. The character is formatted using `\AMCoutsideLabelFormat` first: if you need bold characters, redefine it with `\def\AMCoutsideLabelFormat#1{\textbf{#1}}`

`\AMC@keyBox@` is used instead of `\AMC@formBox@` when the text that corresponds to the answer is the letter/character inside the box itself (see `\AMCcodeGrid` and `\AMCnumericChoices`.

```

520 \def\AMCoutsideLabelFormat#1{#1}
521 \newcommand\AMCboxOutsideLetter[2]{#1\nobreak\hspace{.1em}\AMCoutsideLabelFormat{#2}}
522 \newif\ifAMC@printformoutside@%
523 \newcommand\ifAMC@printformoutside{%

```

```

524 \AMC@printformoutside@false%
525 \ifAMC@ensemble\ifAMC@outside@box%
526 \ifAMCformulaire@dedans\AMC@printformoutside@true\fi%
527 \ifAMC@zoneformulaire\AMC@printformoutside@true\fi%
528 \fi\fi%
529 \ifAMC@printformoutside@%
530 }
531 \newcommand\AMC@formBox@[4]{%
532 \ifAMC@printformoutside% letter to be written outside the box
533 \AMCboxOutsideLetter{\AMC@answerBox@{#2}{#3}{#4}}{#1}%
534 \else%
535 \AMC@answerBox@{#1}{#2}{#3}{#4}%
536 \fi%
537 \AMC@tracechar{#1}{#2}{#3}{#4}%
538 }
539 \newif\ifAMC@printkeyoutside@%
540 \newcommand\ifAMC@printkeyoutside{%
541 \AMC@printkeyoutside@false%
542 \ifAMC@ensemble%
543 \ifAMC@outside@box\AMC@printkeyoutside@true\fi%
544 \else%
545 \ifAMC@inside@box\else\AMC@printkeyoutside@true\fi%
546 \fi%
547 \ifAMC@printkeyoutside@%
548 }
549 \newcommand\AMC@keyBox@[4]{%
550 \ifAMC@printkeyoutside%
551 \AMCboxOutsideLetter{\AMC@answerBox@{#2}{#3}{#4}}{#1}%
552 \else%
553 \AMC@answerBox@{#1}{#2}{#3}{#4}%
554 \fi%
555 \AMC@tracechar{#1}{#2}{#3}{#4}%
556 }
557 \newcommand\AMC@formBox[4]{%
558 \AMC@formBox@{\ifx\@empty#1\@empty%
559 \AMCchoiceLabel{AMC@ncase}%
560 \else #1\fi}{#2}{#3}{#4}%
561 }
562 \newcommand{\AMC@box}[2]{%
563 \ifAMC@ensemble%
564 \ifAMC@zoneformulaire% for codes inside form sheet
565 \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
566 \else%
567 \ifAMCformulaire@dedans% for answer boxes inside form sheet
568 \protect\AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
569 \else% outside form sheet: not to be read during data capture
570 \AMC@formBox{#1}{#2}{1}{casequestion:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
571 \fi\fi%
572 \else% no separate sheet for answers: always read
573 \ifAMC@inside@box%
574 \AMC@formBox{#1}{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%
575 \else%
576 \AMC@formBox@{#2}{1}{case:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}%

```

```

577 \fi%
578 \fi%
579 }

```

4.8.4 Scoring zones

\AMCscoreZone The source file can define zones that will be used to print scores when annotating the completed answer sheets. The command `\AMCscoreZone{<zone>}` logs these zones positions on the page.

```

580 \newif\ifAMCsz@logged\AMCsz@loggedfalse
581 \newcommand{\AMCscoreZone}[1]{%
582   \ifAMC@ensemble%
583     \ifAMCformulaire@dedans%
584       \AMC@tracebox{1}{score::\the\AMCid@quest,-1}{#1}%
585     \else%
586       \AMC@tracebox{1}{scorequestion::\the\AMCid@quest,-1}{#1}%
587     \fi%
588   \else%
589     \AMC@tracebox{1}{score::\the\AMCid@quest,-1}{#1}%
590   \fi%
591   \ifAMCsz@logged\else%
592     \AMCmessage{VAR:scorezones=1}%
593     \global\AMCsz@loggedtrue%
594   \fi%
595 }

```

4.8.5 Binary boxes

The package prints on each page some boxes that code (like binary digits) student sheet number, page number and a check number, so as to be read easily from scans after exam.

\AMCid@checkmax The check number is just decreased each page. Its maximum value is `\AMCid@checkmax`.
\AMC@NCBetud The number of binary digits used to print student sheet number, page and check number are `\AMC@NCBetud`, `\AMC@NCBpage` and `\AMC@NCBcheck`. The number of the first page is `\AMC@NCBcheck`.
\AMC@premierecopie The length of zone reserved for binary boxes is `\AMC@CBtaille`.

```

596 \def\AMCid@checkmax{60}
597 \def\AMC@NCBetud{12}
598 \def\AMC@NCBpage{6}
599 \def\AMC@NCBcheck{6}
600 \newlength{\AMC@CBtaille}\setlength{\AMC@CBtaille}{5cm}
601 \def\AMC@premierecopie{1}

```

\AMC@binaryCode The command `\AMC@binaryCode{<options>}{<n>}` prints boxes to represent the number `<n>` in its binary form. Options from `<options>` include:

`ndigits=<ndigits>` for the number of digits to be shown.

`id=<id>` for an ID of the number role (1 for the student number, 2 for the page number, 3 for the checking value).

`hsep=<hsep>` for the space between boxes.

`style=<style>` for some box style options.

\AMCbin@one and \AMCbin@zero print individual digit-boxes.

For example, \AMC@binaryCode{ndigits=12}{367} shows $367 = 000101101111_2$ using 12 boxes:



```

602 \newtoks\AMCbin@sequence
603 \newcount\AMCbin@number
604 \newcount\AMCbin@digit
605 \newcount\AMCbin@id
606 \newcount\AMCbin@did
607 \newcount\AMCbin@ndigits
608 \newdimen\AMCbin@hsep
609 \define@key{AMCbin}{ndigits}{\AMCbin@ndigits=#1}
610 \define@key{AMCbin}{id}{\AMCbin@id=#1}
611 \define@key{AMCbin}{hsep}{\AMCbin@hsep=#1}
612 \define@key{AMCbin}{style}[]{\def\AMCbin@style{#1}}
613 \def\AMCbin@one{%
614   \ifnum\AMCbin@did>\z@%
615     \hspace{\AMCbin@hsep}%
616     \fi%
617     \advance\AMCbin@did\@ne%
618     \ifnum\AMCbin@id>0%
619       \AMC@answerBox@{\AMC@checkedbox}{1}{chiffre:\the\AMCbin@id,\the\AMCbin@did}%
620       \else%
621       \AMC@answerBox@{\AMC@checkedbox}{1}{}%
622       \fi}
623 \def\AMCbin@zero{%
624   \ifnum\AMCbin@did>\z@%
625     \hspace{\AMCbin@hsep}%
626     \fi%
627     \advance\AMCbin@did\@ne%
628     \ifnum\AMCbin@id>0%
629       \AMC@answerBox@{\AMC@checkedbox}{1}{chiffre:\the\AMCbin@id,\the\AMCbin@did}%
630       \else%
631       \AMC@answerBox@{\AMC@checkedbox}{1}{}%
632       \fi}
633 \newcommand{\AMC@binaryCode}[2]{%
634   \setkeys{AMCbin}{ndigits=1,hsep=0pt,style}\setkeys{AMCbin}{#1}%
635   \AMCbin@did=\z@%
636   {\AMCboxDimensions{shape=square,size=.32cm,down=0pt,rule=.2pt,cross=false}\expandafter\AMCboxDimensions\
637   \AMCbin@digit=\z@%
638   \loop%
639   \ifnum\AMCbin@number>\z@%
640     \advance\AMCbin@digit\@ne%
641     \ifodd\AMCbin@number\AMCbin@sequence=\expandafter{\expandafter\AMCbin@one\the\AMCbin@sequence}%
642     \else\AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\fi%
643     \divide\AMCbin@number\tw@%
644     \repeat%
645   \loop\relax%
646   \ifnum\AMCbin@digit<\AMCbin@ndigits\advance\AMCbin@digit\@ne%
647     \AMCbin@sequence=\expandafter{\expandafter\AMCbin@zero\the\AMCbin@sequence}\repeat%
648     \the\AMCbin@sequence%
649   \ifnum\AMCbin@digit>\AMCbin@ndigits\PackageError{automultiplechoice}{Too low AMC@NCB value (got \the\AMC

```

```
650 }}
```

The commands `\AMCbin@begin` and `\AMC@binaryBoxes` are now unused and are defined for backward compatibility.

```
651 \def\AMCbin@begin#1{\setkeys{AMCbin}{id=#1}}
652 \newcommand{\AMC@binaryBoxes}[2][1]{%
653 \AMC@binaryCode{ndigits=#1}{#2}%
654 }
```

4.9 Checking Environment

`\AMCcurrentenv` Sets the current environment as document.

```
655 \def\AMCcurrentenv{document}
```

`\AMCif@env` Checks for the current environment.

```
656 \def\AMCif@env#1{
657   \def\AMC@tempenv{#1}%
658   \ifx\AMC@tempenv\AMCcurrentenv
659     \expandafter\@firstoftwo
660   \else
661     \expandafter\@secondoftwo
662   \fi
663 }
```

4.10 Handling groups of questions

The package allows to handle groups of questions, so as to be able to shuffle them before printing them to the sheets.

`\nouveaugroupe` Command `\nouveaugroupe{<group-name>}{<n>}` creates a new (empty) group with name `<group-name>` (argument `<n>` is present only for compatibility reasons and is ignored). Command `\element{<group-name>}{<text>}` adds to group `<group-name>` a new element that contains `<text>`. `<text>` can be a `question` environment, ore two successive `questions` to be kept together, or anything else. Calling command `\nouveaugroupe` is not compulsory, as `\element` calls it if necessary.

```
664 \newcount\AMCtok@k
665 \newcount\AMCtok@max
666 \newcount\AMCtok@size
667 \newcommand{\nouveaugroupe}[2]{%
668   \expandafter\ifx\csname #1@k\endcsname\relax%
669     \expandafter\newcount\csname #1@k\endcsname%
670     \expandafter\newcount\csname AMC#1@j\endcsname%
671     \csname #1@k\endcsname=\z@\relax%
672     \csname AMC#1@j\endcsname=\z@\relax%
673     \setgroupmode{#1}{\AMCdefault@groupmode}%
674   \fi%
675 }
676 \newcommand\AMC@prepare@element[1]{%
677   \nouveaugroupe{#1}{}%
678   \global\advance\csname #1@k\endcsname\@ne\relax%
679   \AMCtok@k=\csname #1@k\endcsname%
680   \expandafter\ifx\csname #1@romannumeral\AMCtok@k\endcsname\relax%
```

```

681 \expandafter\newtoks\csname #1@\romannumeral\AMCtok@k\endcsname\fi%
682 }
683 \newcommand{\element}[2]{%
684 \AMC@prepare@element{#1}%
685 \global\csname #1@\romannumeral\AMCtok@k\endcsname={#2}%
686 }

```

`\setgroupmode` Command `\setgroupmode{<group-name>}{<mode>}` sets the group mode to `<mode>` for group `<group-name>`. This mode setup the behaviour of `\insertgroup` and `\copygroup` for this group:

1. With mode `fixed`, group's elements will be taken from the beginning.
2. With mode `cyclic`, the elements will be taken from the group following the last call group's use, recycling if necessary.
3. Mode `withreplacement` is the same as `fixed`, but the group is shuffled before each use.
4. Mode `withoutreplacement` is like `cyclic`, adding some shuffling when coming back to the beginning of the group.

The command `\setdefaultgroupmode{<mode>}` sets the group mode to be used for the following created groups (a group is created at the first `\element{<group>}` call). When no `\setdefaultgroupmode` is used, `fixed` is the default mode.

```

687 \def\AMCdefault@groupmode{fixed}
688 \newcommand{\setdefaultgroupmode}[1]{\def\AMCdefault@groupmode{#1}}
689 \newcommand{\setgroupmode}[2]{%
690 \expandafter\ifx\csname AMCgrouppre@#2\endcsname\relax%
691 \PackageError{automultiplechoice}{Unknown group mode for #1 : #2}%
692 {You asked to set group '#1' mode to '#2',
693 but '#2' is not a valid group mode}%
694 \else%
695 \expandafter\global\expandafter\def\csname AMC#1@mode\endcsname{#2}%
696 \fi%
697 }

```

The functions `\AMCgrouppre@xxx{<group-name>}{<n>}{<i>}` are called before using `<n>` elements from group `<group-name>` starting from index `<i>` (negative value for `<i>` stands for the current value of the group index), either with `\insertgroup` or `\copygroup`.

For mode **fixed**, the group index is set to `<i>`, or 0 if `<i>` is negative (take elements from the beginning).

```

698 \newcommand{\AMCgrouppre@fixed}[3]{%
699 \ifnum#3<\z@%
700 \csname AMC#1@j\endcsname=\z@%
701 \else%
702 \csname AMC#1@j\endcsname=#3%
703 \fi%
704 }

```

For mode **withreplacement**, the group is shuffled and the group index is set to `<i>` or 0 (take elements from the beginning) if negative.

```

705 \newcommand{\AMCgrouppre@withreplacement}[3]{%
706 \ifnum#3<\z@%
707 \csname AMC#1@j\endcsname=\z@%
708 \else%

```

```

709 \csname AMC#1@j\endcsname=#3%
710 \fi%
711 \shufflegroup{#1}%
712 }

```

For mode **withoutreplacement**, the group index is set to $\langle i \rangle$, or left unchanged if $\langle i \rangle$ is negative. If there is not enough elements left in the group, the elements before the index and the elements after the index are shuffled.

```

713 \newcount\AMC@imax
714 \newcommand{\AMCgrouppre@withoutreplacement}[3]{%
715 \ifnum#3<\z@%
716 \else%
717 \csname AMC#1@j\endcsname=#3%
718 \fi%
719 \ifnum\AMCtok@ik=\AMCloop@k%
720 \AMCtok@ik=\z@%
721 \fi%
722 \ifnum\AMCtok@ik=\z@%
723 \shufflegroup{#1}%
724 \else%
725 \AMC@imax=\AMCloop@k%
726 \advance\AMC@imax -#2\relax%
727 \ifnum\AMCtok@ik>\AMC@imax%
728 \shufflegroupslice{#1}{\@ne}{\AMCtok@ik}%
729 \ifnum\AMCtok@ik<\AMCloop@k%
730 \advance\AMCtok@ik\@ne%
731 \shufflegroupslice{#1}{\AMCtok@ik}{\AMCloop@k}%
732 \fi%
733 \fi%
734 \fi%
735 }

```

For mode **cyclic**, nothing has to be done, except setting the group index if non-negative.

```

736 \newcommand{\AMCgrouppre@cyclic}[3]{%
737 \ifnum#3<\z@%
738 \else%
739 \csname AMC#1@j\endcsname=#3%
740 \fi%
741 }

```

The function `\AMCgroup@pre{<mode>}{<group-name>}{<n>}{<i>}` calls the right `\AMCgrouppre@xxx` command.

```

742 \newcommand{\AMCgroup@pre}[4]{%
743 \csname AMCgrouppre@#1\endcsname{#2}{#3}{#4}%
744 }

```

`\shufflegroup` Command `\shufflegroup{<group-name>}` shuffles the elements of group $\langle group-name \rangle$, and `\insertgroup` `\shufflegroupslice{<group-name>}{<a>}{}` shuffles elements $\langle a \rangle$ to $\langle b \rangle$ from group $\langle group-name \rangle$. `\insertgroupfrom` It can be called at each student sheet in order to get different student sheets and avoid cheating.

Command `\insertgroup[<n>]{<groupname>}` inserts all the elements of group $\langle groupname \rangle$, or only the first $\langle n \rangle$ elements if $\langle n \rangle$ is given. `\insertgroupfrom[<n>]{<groupname>}{<i>}` inserts all the elements of group $\langle groupname \rangle$ starting from index $\langle i \rangle$ (the index of the first element is 0), or only the first $\langle n \rangle$ elements if $\langle n \rangle$ is given.

```

745 \newcommand{\shufflegroup}[1]{%

```

```

746 \ifAMC@shuffleG{\AMC@shuffletoks{\number\csname #1@k\endcsname}{#1@}}\fi%
747 }
748 \newcommand{\shufflegroupslice}[3]{%
749 \ifAMC@shuffleG{\AMC@shuffletoks[#2]{#3}{#1@}}\fi%
750 }
751 \newcount\AMCtok@ik
752 \newcount\AMCloop@k
753 \newcommand{\AMCgrouploop@prep}[3]{%
754 \AMCtok@size=#1\relax%
755 \ifAMC@fullGroups\AMCtok@size=\m@ne\fi%
756 \ifnum\AMCtok@size<\z@%
757 \AMCtok@size=\csname #2@k\endcsname%
758 \fi%
759 \AMCtok@ik=\csname AMC#2@j\endcsname%
760 \AMCloop@k=\csname #2@k\endcsname%
761 \expandafter\ifx\csname AMC#2@mode\endcsname\relax%
762 \PackageError{automultiplechoice}{No group mode for #2}%
763 {No mode has been defined for group '#2'. This should not occur...}%
764 \fi%
765 \AMCgroup@pre{\csname AMC#2@mode\endcsname}{#2}{\the\AMCtok@size}{#3}%
766 }
767 \newcommand{\AMCgrouploop@next}[1]{%
768 \global\advance\csname AMC#1@j\endcsname\@ne\relax%
769 \expandafter\ifnum\csname AMC#1@j\endcsname>\AMCloop@k\relax%
770 \global\csname AMC#1@j\endcsname=\@ne%
771 \fi%
772 \AMCtok@ik=\csname AMC#1@j\endcsname%
773 \advance\AMCtok@size\m@ne%
774 }
775 \newcommand{\insertgroupfrom}[3][-1]{%
776 \ifnum#1=0%
777 \else%
778 \AMCgrouploop@prep{#1}{#2}{#3}%
779 {\loop%
780 \AMCgrouploop@next{#2}%
781 {\the\csname #2@romannumeral\AMCtok@ik\endcsname}%
782 \ifnum\AMCtok@size>\z@\repeat}%
783 \fi%
784 }
785 \newcommand{\insertgroup}[2][-1]{%
786 \insertgroupfrom[#1]{#2}{-1}%
787 }

```

`\cleargroup` The commands `\cleargroup` and `\copygroup` can also be used to make more complex questions combinations in the exams, allowing for example to ask the package to shuffle 3 questions taken at random from group `groupa` and 5 questions taken at random from group `groupb`.

`\cleargroup{⟨group⟩}` clears the group `⟨group⟩`, ereasing all of its elements.

`\copygroup[⟨n⟩]{⟨from⟩}{⟨to⟩}` copies `⟨n⟩` elements from group `⟨from⟩` to group `⟨to⟩`. If optional parameter `⟨n⟩` is not given, all the questions from group `⟨from⟩` are copied. `\copygroupfrom[⟨n⟩]{⟨from⟩}{⟨to⟩}{⟨i⟩}` copies `⟨n⟩` elements from group `⟨from⟩` to group `⟨to⟩`, starting from element at index `⟨i⟩` (the index of the first element is 0). If optional parameter `⟨n⟩` is not given, all the questions from group `⟨from⟩` are copied.

See section 3.4 for an illustration for these commands.

```

788 \newcommand{\cleargroup}[1]{%
789   \nouveaugroupe{#1}{}%
790   \csname #1@k\endcsname=\z@\relax%
791   \csname AMC#1@j\endcsname=\z@\relax%
792 }
793 \newcommand{\copygroupfrom}[4][-1]{%
794   \ifnum#1=0%
795     \else%
796       \AMCgrouploop@prep{#1}{#2}{#4}%
797       {\loop%
798         \AMCgrouploop@next{#2}%
799         \AMC@prepare@element{#3}%
800         \global\csname #3@\romannumeral\AMCtok@k\endcsname=\csname #2@\romannumeral\AMCtok@ik\endcsname%
801         \ifnum\AMCtok@size>\z@\repeat}%
802       \fi%
803 }
804 \newcommand{\copygroup}[3][-1]{%
805   \copygroupfrom{#1}{#2}{#3}{-1}%
806 }

```

4.11 Questions

To manage multiple choice questions, first set some counters and token registers to handle answers. Token registers `\reponse@i`, `\reponse@ii` and so on will be used for answers – we restrict the number of answers of a single questions to `\AMCload@counter = 199`.

```

807 \newcount\AMCrep@count
808 \AMCload@counter=199
809 \@whilenum\AMCload@counter>0\do{%
810   \expandafter\newtoks\csname reponse@\romannumeral\AMCload@counter\endcsname%
811   \advance\AMCload@counter@m@ne%
812 }

```

`\AMCload@reponse` Command `\AMCload@reponse{<n>}{<text>}` will be used to add answer number `<n>` with text `<text>` (`<text>` will include the box to be ticked and all the layout commands) to the set of answers (in a token register `\reponse@xxx` – counter `\AMCload@counter` keeps track of the number of answers), in order to shuffle them when all answers will be loaded.

When answers are not to be shuffled, command `\AMCrien@deux{<n>}{<text>}` will be used instead, only printing `<text>`.

```

813 \newcommand\AMCload@reponse[2]{%
814   \global\advance\AMCload@counter\@ne\relax%
815   \global\csname reponse@\romannumeral\AMCload@counter\endcsname%
816   =\expandafter{\expandafter\AMCrep@count\expandafter=#2 #1}%
817 }
818 \newcommand\AMCrien@deux[2]{#1}

```

`\shuffle@it` After loading all answers, commands `\shuffle@it` will be used to shuffle them, and `\AMCdump@reponses` to print them.

```

819 \def\shuffle@it{\AMC@shuffletoks{\number\AMCload@counter}{reponse@}}
820 \newcount\AMCnum@questions
821 \newcommand\AMCdump@reponses{%
822   \global\AMCnum@questions=\AMCload@counter%
823   \@whilenum\AMCload@counter>0\do{%

```

```

824 \the\csname reponse@\romannumeral\AMCload@counter\endcsname%
825 \advance\AMCload@counter\m@ne}}

```

4.11.1 Managing answers

`\lastchoices` Command `\AMCrep@init{<mode>}` is called for each question before reading answers. `<mode>` `\AMCrep@init` is `r` for suffled answers, and `o` if answers are not to be shuffled. It sets the number of answers `\AMC@fin@rep` counter to zero, and calls `\AMCrep@o` or `\AMCrep@r` depending on `<mode>`. These commands sets `\AMCload@@reponse` and `\AMCrep@fini` that will be called for each answer and after the last answer respectively, depending on `<mode>`:

- If `<mode>=r`, `\AMCload@@reponse` is `\AMCload@reponse` (loads answer to token register) and `\AMCrep@fini` calls `\shuffle@it` and `\AMCdump@reponses`;
- If `<mode>=o`, `\AMCload@@reponse` is `\AMCrien@deux` (prints answer directly) and `\AMCrep@fini` does nothing.

Command `\lastchoices` is called before giving answers that are to be printed at the end (even when shuffling answers). It closes the answers list calling `\AMCrep@fini` and opens another one in ordered mode. Note that it also saves the value of `\AMCrep@count`, which is the number of the current answer among all answers given in the subject source for the current question.

Command `\AMC@fin@rep` is to be called after the last answer: it adds a “None of these answers are correct.” answer if necessary (package option `completemulti`) with answer number zero, and calls `\AMCrep@fini`.

```

826 \newcommand\AMCrep@init[1]{%
827   \ifAMC@ordre\AMCrep@o\else%
828     \csname AMCrep@#1\endcsname\fi\AMCload@counter=\z@}
829 \newcommand\AMCrep@o{%
830   \def\AMCload@@reponse{\AMCrien@deux}\def\AMCrep@fini{}}
831 \newcommand\AMCrep@r{%
832   \def\AMCload@@reponse{\AMCload@reponse}%
833   \def\AMCrep@fini{\shuffle@it\AMCdump@reponses}}
834 \newcount\AMCrep@count
835 \newcommand\lastchoices{%
836   \AMCrep@count=\AMCrep@count%
837   \AMCrep@fini\AMCrep@init{o}%
838   \AMCrep@count=\AMCrep@count}
839 \newcommand\@aucune{\emph{\AMC@loc@none}}
840 \newcommand\AMC@fin@rep{%
841   \ifAMCcomplete@multi\ifAMCtype@multi%
842     \lastchoices\AMCrep@count=-1%
843     \ifAMC@bonne\wrongchoice{\@aucune}\else%
844       \ifAMC@postcorrect\wrongchoice{\@aucune}\else\correctchoice{\@aucune}\fi%
845     \fi\fi\fi\AMCrep@fini}

```

4.11.2 Separate answer sheet

This package needs some memory to print questions/answers boxes again on a separate answer sheet.

`\AMCformQuestion` First define commands that will announce questions and answers on the separate answer sheet
`\AMCformAnswer` (these commands can be modified by the user): `\AMCformQuestion{<number>}` is responsible

for announcing question, and `\AMCformAnswer{<box>}` is responsible for printing the box to be ticked, given as argument `<box>`.

Commands `\AMCformQuestionA` and `\AMCformAnswerA` set up counter `\AMC@ncase` value before calling their counterparts.

```

846 \def\AMCformBeforeQuestion{\vspace{\AMCformVSpace}\par}
847 \def\AMCformAfterQuestion{\ifAMC@asqbloc\egroup\fi}
848 \def\AMCformQuestion#1{\AMC@loc@qf{#1}}
849 \def\AMCformQuestionN{\AMCformQuestion{\AMC@qaff}}
850 \def\AMCformQuestionA{%
851   \setcounter{AMC@ncase}{0}%
852   \AMCformBeforeQuestion%
853   \ifAMC@asqbloc\vbox\bgroup\fi%
854   \ifx\@empty\AMC@sza@callout\@empty\else%
855     \csname\AMC@sza@callout\endcsname%
856   \fi%
857   \AMCformQuestionN%
858   \ifx\@empty\AMC@sza@callin\@empty\else%
859     \csname\AMC@sza@callin\endcsname%
860   \fi%
861 }
862 \def\AMCformAnswer#1{\hspace{\AMCformHSpace} #1}
863 \def\AMCformAnswerA#1{\addtocounter{AMC@ncase}{1}\AMCformAnswer{#1}}

```

`\AMC@mem@add@ifneeded` These are commands to manage memory for separate answer sheet. `\AMC@mem@add@ifneeded{<code>}`

`\AMCformBegin` adds `<code>` to this memory. `\AMC@mem@answer{<code>}` adds to memory answer code `<code>`, and

`\AMCform` `\AMC@mem@openQuestion` adds to memory question code to announce current question.

`\AMCformS` The command `\AMCformBegin` defines the beginning of the separate answer sheet for the current student sheet, and `\AMCform` prints the whole memory: questions and answers boxes.

`\AMCformS` is a `\AMCform` variant that does not clear the list of answer boxes. It can be used to make the same exact subject for all students, displaying the questions before (outside) `onecopy`, so that `onecopy` contains only the answer sheet.

```

864 \ExplSyntaxOn
865
866 \prg_set_conditional:Nnn \amc_if_separate_question: { p , T } {
867   \ifAMC@ensemble
868     \ifAMC@zoneformulaire
869       \prg_return_false:
870     \else
871       \prg_return_true:
872     \fi
873   \else
874     \prg_return_false:
875   \fi
876 }
877 \cs_new_eq:NN \AMC@ifseparate@question \amc_if_separate_question:T
878
879 \int_new:N \amc_memory_elts_count
880
881 \cs_new:Nn \amc_clear_memory: { \int_gzero:N \amc_memory_elts_count }
882 \cs_new_eq:NN \AMC@mem@clear \amc_clear_memory:
883

```



```

884 \cs_new:Npn \amc_memory_elt_i:n #1 {
885   amc_memory_elts_ \int_to_alph:n { #1 }
886 }
887 \cs_new:Nn \amc_memory_current_elt: {
888   \amc_memory_elt_i:n \amc_memory_elts_count
889 }
890 \cs_new:Npn \amc_memory_vars_i:n #1 {
891   amc_memory_vars_ \int_to_alph:n { #1 }
892 }
893 \cs_new:Nn \amc_memory_current_vars: {
894   \amc_memory_vars_i:n \amc_memory_elts_count
895 }
896
897 \cs_new:Nn \amc_add_memory_elt: {
898   \int_gincr:N \amc_memory_elts_count
899   \tl_gclear_new:c { \amc_memory_current_elt: }
900   \tl_gclear_new:c { \amc_memory_current_vars: }
901 }
902 \cs_new_eq:NN \AMC@mem@next \amc_add_memory_elt:
903
904 \cs_new:Npn \amc_add_to_memory:n #1 {
905   \tl_gput_right:cn { \amc_memory_current_elt: } { #1 }
906 }
907 \cs_new_eq:NN \AMC@mem@add \amc_add_to_memory:n
908
909 \cs_new:Npn \amc_add_to_vars:n #1 {
910   \tl_gput_right:cn { \amc_memory_current_vars: } { #1 }
911 }
912 \cs_new_eq:NN \AMC@mem@addvar \amc_add_to_vars:n
913
914 \cs_new:Npn \amc_add_qidaffname:nnn #1#2#3 {
915   \amc_add_to_vars:n {\AMCid@quest=#1\setcounter{AMCquestionaff}{#2}%
916     \global\def\AMCid@name{#3}}
917 }
918 \cs_generate_variant:Nn \amc_add_qidaffname:nnn { xxx }
919 \cs_new_eq:NN \AMC@mem@qidaffname \amc_add_qidaffname:xxx
920
921 \cs_new:Npn \amc_mem_elt_cat:n #1 {
922   \amc_add_to_vars:n { \def\AMCmem@elt@cat{ #1 } }
923 }
924 \cs_generate_variant:Nn \amc_mem_elt_cat:n { x }
925 \cs_new_eq:NN \AMC@mem@category \amc_mem_elt_cat:x
926
927 \cs_new:Npn \amc_add_aid:n #1 {
928   \amc_add_to_memory:n {\AMCrep@count=#1}
929 }
930 \cs_generate_variant:Nn \amc_add_aid:n { x }
931 \cs_new_eq:NN \AMC@mem@aid \amc_add_aid:x
932
933 \cs_new:Npn \amc_if_category_is_p:n #1 {
934   \str_if_eq_p:on { \AMCmem@elt@cat } { #1 }
935 }
936 \cs_new:Npn \amc_use_memory:n #1 {

```

```

937 \int_step_inline:nnnn { 1 } { 1 } \amc_memory_elts_count {
938   \def\AMCmem@elt@cat{ plain }
939   \tl_use:c { \amc_memory_vars_i:n { ##1 } }
940   \bool_if:nTF { #1 } {
941     \tl_use:c { \amc_memory_elt_i:n { ##1 } }
942   } { }
943 }
944 }
945 \cs_new:Nn \amc_use_memory: { \amc_use_memory:n { \c_true_bool } }
946 \cs_new_eq:NN \AMC@mem@show \amc_use_memory:
947 \cs_new_eq:NN \AMC@mem@show@filter \amc_use_memory:n
948 \cs_new_eq:NN \AMC@category \amc_if_category_is_p:n
949
950 \ExplSyntaxOff
951 \newcommand\AMC@mem@add@ifneeded[1]{%
952   \AMC@if@separate@question{%
953     \AMC@mem@add{#1}%
954   }%
955 }
956 \newcommand\AMC@mem@addsingle@ifneeded[2]{%
957   \AMC@if@separate@question{%
958     \AMC@mem@next%
959     \AMC@mem@category{#2}%
960     \AMC@mem@add{#1}%
961   }%
962 }
963 \newcommand\AMC@mem@answer[1]{%
964   \addtocounter{AMC@ncase}{1}%
965   \AMC@if@separate@question{%
966     \AMC@mem@aid{\the\AMC@rep@count}%
967     \AMC@mem@add{\AMCformAnswerA{#1}}%
968   }%
969 }
970 \newcommand\AMC@mem@openQuestion{%
971   \AMC@if@separate@question{%
972     \AMC@mem@next%
973     \AMC@mem@qidaffname{\the\AMC@id@quest}{\arabic{AMC@questionaff}}{\AMC@id@name}%
974     \AMC@mem@add{\AMCformQuestionA}%
975   }%
976 }
977 \def\AMCformBegin{%
978   \AMC@zoneformulairetrue\setcounter{section}{0}%
979   \ifAMC@ensemble\ifAMC@automarks\pagestyle{AMCpageFull}\fi\fi%
980 }
981 \newcommand\AMCform{%
982   \ifAMC@ensemble\AMCformulaire@dedanstrue%
983     \AMC@mem@show%
984   \fi}
985 \newcommand\AMCformFilter[1]{%
986   \ifAMC@ensemble\AMCformulaire@dedanstrue%
987     \AMC@mem@show@filter{#1}%
988   \fi}
989 \newif\ifAMC@keepmemory

```

```

990 \newcommand\AMCformS{%
991   \ifAMC@ensemble\AMCformulaire@dedanstrue%
992   \AMCmessage{BR=0}\AMC@mem@show%
993   \global\AMC@keepmemorytrue%
994   \fi}

```

`\AMCsection` The `\AMCsection` and `\AMCsubsection` commands issue their standard counterparts (`\section` and `\subsection` with the same argument, both in the subject *and* in the separate answer sheet.

```

995 \newcommand{\AMCsectionNumbered}[1]{%
996   \section{#1}\AMC@mem@addsingle@ifneeded{\section{#1}}{section}}
997 \newcommand{\AMCsubsectionNumbered}[1]{%
998   \subsection{#1}\AMC@mem@addsingle@ifneeded{\subsection{#1}}{subsection}}
999 \newcommand{\AMCsectionStar}[1]{%
1000   \section*{#1}\AMC@mem@addsingle@ifneeded{\section*{#1}}{section}}
1001 \newcommand{\AMCsubsectionStar}[1]{%
1002   \subsection*{#1}\AMC@mem@addsingle@ifneeded{\subsection*{#1}}{subsection}}
1003 \def\AMCsection{\@ifstar\AMCsectionStar\AMCsectionNumbered}
1004 \def\AMCsubsection{\@ifstar\AMCsubsectionStar\AMCsubsectionNumbered}

```

4.11.3 Formatting answers

`choices` (*env.*) Answers have to be included in an environment `choices` (standard), `choiceshoriz` (answers on one line) or `choicescustom` (user defined) depending on the desired formatting.

`choicescustom` (*env.*) Use `\AMCBoxedAnswers` to request all answers to be included in L^AT_EX boxes; this can be useful for example when using multicolumn answers formatting.

```

tikz-single (env.)
tikz-multi (env.)
\AMCBoxedAnswers
1005 \def\AMCBoxedAnswers{\AMC@rbloctrue}
1006 \newenvironment{choices}[1][r]{%
1007   \AMCrep@count=\z@\def\une@rep{\AMCrep@itemize}%
1008   \ifAMC@rbloc\def\une@rep{\AMCrep@bloc}%
1009   \else\begin{itemize}\setlength{\itemsep}{\AMCinterIrep}\fi%
1010   \AMCrep@init{#1}}%
1011   {\AMC@fin@rep\ifAMC@rbloc\else\end{itemize}\fi}
1012 \newenvironment{choiceshoriz}[1][r]{%
1013   \AMCrep@count=\z@\def\une@rep{\AMCrep@ligne}\AMCrep@init{#1}%
1014   \par\begin{center}}%
1015   {\AMC@fin@rep\end{center}}
1016 \newenvironment{choicescustom}[1][r]{%
1017   \AMCrep@count=\z@\def\une@rep{\AMCrep@perso}\AMCrep@init{#1}%
1018   \AMCbeginAnswer\ignorespaces}%
1019   {\AMC@fin@rep\AMCendAnswer}
1020 \newenvironment{tikz-single}[1][r]{
1021   \AMCrep@count=\z@\def\une@rep{\AMCrep@tikz}\AMCrep@init{#1}%
1022   \begin{tikzpicture}}{\AMC@fin@rep\end{tikzpicture}}
1023 \newenvironment{tikz-multi}[1][r]{
1024   \AMCrep@count=\z@\def\une@rep{\AMCrep@tikzmat}\AMCrep@init{#1}%
1025   \begin{tikzpicture}[remember picture]}{\AMC@fin@rep\end{tikzpicture}}

```

`\AMCrep@bloc` For each of these styles, a corresponding `\AMCrep@xxx{\langle box \rangle}{\langle text \rangle}` is defined, which will format the answer with a box given in $\langle box \rangle$ and text $\langle text \rangle$. `\AMCrep@bloc` is also defined and used in standard formatting when the user wants to put answers inside a L^AT_EX box.

```

\AMCrep@tikz
\AMCrep@tikzmat
\AMCrep@itemize
\AMCrep@ligne
\AMCrep@perso
1026 \newcommand\AMCrep@bloc[2]{\AMC@mem@answer{#1}%
1027   \par%

```

```

1028 \ifAMC@textPos\ vbox\bgroup\AMC@tracepos{1}{atext:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}\hbox{
1029 \noindent\begin{minipage}{\linewidth}%
1030 \begin{itemize}\item{#1} #2\end{itemize}\end{minipage}%
1031 \ifAMC@textPos\AMC@tracepos{1}{atext:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}\egroup\AMC@tra
1032 \vspace{\AMCinterBrep}}
1033 \newcommand\AMCrep@tikz[5]{\AMC@mem@answer{#1}\node[#4] (lab\thecsvrow) at (#3) {#2} node[#5] (box\thecsvrow)
1034 \newcommand\AMCrep@tikzmat[5]{\AMC@mem@answer{#1}\node[#5] (box\thecsvrow) at (#3) {#1} node[#4] (lab\thecsvrow)
1035 \newcommand\AMCrep@itemize[2]{\AMC@mem@answer{#1}\item{#1} #2}
1036 \newlength\AMChorizAnswerSep
1037 \setlength\AMChorizAnswerSep{3em plus 4em}
1038 \newlength\AMChorizBoxSep
1039 \setlength\AMChorizBoxSep{1em}
1040 \newcommand\AMCrep@ligne[2]{\AMC@mem@answer{#1}%
1041 \ifAMC@textPos%
1042 \mbox{\AMC@tracebox{1}{atext:\AMCid@name:\the\AMCid@quest,\the\AMCrep@count}{#1}\hspace*\AMChorizBoxSep}%
1043 \else%
1044 \mbox{#1\hspace*\AMChorizBoxSep}{#2}%
1045 \fi\hspace*\AMChorizAnswerSep}}
1046 \newcommand\AMCrep@perso[2]{\AMC@mem@answer{#1}\AMCanswer{#1}{#2}}

```

`\AMCbeginAnswer` The custom style will use user-defined commands to format answers: `\AMCbeginAnswer` is called once before answers, `\AMCanswer{<box>}{<text>}` is called for each answer (`<box>` being the box to be ticked and `<text>` the text associated with the proposed answer), and `\AMCendAnswer` is called after all answers.

```

1047 \def\AMCbeginAnswer{}
1048 \def\AMCanswer#1#2{#1 #2}
1049 \def\AMCendAnswer{}

```

`\answer` The commands `\correctchoice` and `\wrongchoice` are used inside `choices`-like environments to give the proposed answers and specify if they are to be ticked by the students or not.

```

\wrongchoice
1050 \newcommand{\correctchoice}[2] [] {\global\advance\AMCrep@count\@ne\relax%
1051 \ifAMC@calibration\AMCmessage{REP=\the\AMCrep@count:B}\fi%
1052 \global\AMCune@bonnettrue%
1053 \AMCload@reponse{\une@rep{\ifAMC@correc\AMC@box{#1}{\AMC@checkedbox}%
1054 \else\AMC@box{#1}{\fi}{#2}}{\the\AMCrep@count}\ignorespaces}
1055 \newcommand{\wrongchoice}[2] [] {\global\advance\AMCrep@count\@ne\relax%
1056 \ifAMC@calibration\AMCmessage{REP=\the\AMCrep@count:M}\fi%
1057 \AMCload@reponse{\une@rep{\AMC@box{#1}{\fi}{#2}}{\the\AMCrep@count}%
1058 \ignorespaces}

```

4.11.4 Score zones

`\AMCscoreZone` The position of the scores on the annotated answer sheets can be defined in the L^AT_EX source file using `\AMCsetScoreZone{<options>}` (or `\AMCsetScoreZoneAnswerSheet{<options>}` for the answer sheets when the separate answer sheet option is used).

First begin with some helpers: `\AMCemptybox{<width>}{<height>}{<depth>}` draws an empty box with specified dimensions, and `\AMCmarginNote{<note>}` (code from one of [sgmoye's](http://tex.stackexchange.com) comments on tex.stackexchange.com) prints a marginal note in the left or right margin, depending on current the position (usefull in `multicols` environment).

```

1059 \newcommand{\AMCemptybox}[3] {%
1060 \sbox0{\wd0=#1\ht0=#2\dp0=#3\relax\box0}}
1061 \newlength\AMC@mn@test

```

```

1062 \newlength\AMC@mn@sep\AMC@mn@sep=4mm
1063 \newlength\AMC@mn@leftmargin
1064 \newlength\AMC@mn@rightmargin
1065 \newcommand\AMCmarginNote[1]{%
1066   \begin{tikzpicture}[remember picture,overlay]%
1067     \coordinate (here) at (0,0);%
1068     \pgfextractx{\AMC@mn@test}{\pgfpointdiff{\pgfpointorigin}%
1069       {\pgfpointanchor{current page}{center}}}%
1070     \ifodd\thepage%
1071       \AMC@mn@leftmargin=\oddsidemargin%
1072       \AMC@mn@rightmargin=\evensidemargin%
1073     \else
1074       \AMC@mn@leftmargin=\evensidemargin%
1075       \AMC@mn@rightmargin=\oddsidemargin%
1076     \fi
1077     \ifdim\AMC@mn@test < 1cm%
1078       \draw (current page.east |- here)+(-\AMC@mn@rightmargin-1in+\AMC@mn@sep,0pt) node[anchor=text,align=right]{%
1079         \AMCmarginNote{#1}};
1080     \else%
1081       \draw (current page.west |- here)+(0cm,0pt) node[anchor=text,align=right,text width=\AMC@mn@leftmargin]{%
1082         \AMCmarginNote{#1}};
1083     \fi
1084   \end{tikzpicture}%
1085 }

```

Define now different ways to place the score zone:

`none` nowhere

`question` right after the question heading

`margin` in the margin, using `marginpar` (this does not work with `multicols` environment)

`margins` in the left or right margin, depending on the current position (needs `tikz` package)

```

1084 \newcommand{\AMC@sz@box}{\AMCemptybox{\AMC@sz@width}{\AMC@sz@height}{\AMC@sz@depth}}
1085 %
1086 \newcommand{\AMC@sz@callin@question}{\AMCscoreZone{\AMC@sz@box}}
1087 %
1088 \newcommand{\AMC@sz@callout@margin}{\hspace{0pt}\marginpar{\AMCscoreZone{\AMC@sz@box}}}
1089 %
1090 \newcommand{\AMC@sz@init@margins}{\PackageWarning{automultiplechoice}{Please run twice to get proper margins}}
1091 \newcommand{\AMC@sz@callout@margins}{\hspace{0pt}\AMCmarginNote{\AMCscoreZone{\AMC@sz@box}}}

```

Let us now set up options handling.

```

1092 \newlength\AMC@sz@width
1093 \newlength\AMC@sz@height
1094 \newlength\AMC@sz@depth
1095 \def\AMC@sz@callout{}
1096 \def\AMC@sz@callin{}
1097 \define@key{AMCsz}{width}{\AMC@sz@width=#1}
1098 \define@key{AMCsz}{height}{\AMC@sz@height=#1}
1099 \define@key{AMCsz}{depth}{\AMC@sz@depth=#1}
1100 \define@key{AMCsz}{calloutside}{\def\AMC@sz@callout{#1}}
1101 \define@key{AMCsz}{callinside}{\def\AMC@sz@callin{#1}}
1102 \define@choicekey{AMCsz}{position}{none,question,margin,margins}{%
1103   \ifcsname AMC@sz@callout@#1\endcsname%

```

```

1104 \def\AMC@sz@callout{AMC@sz@callout@#1}%
1105 \else%
1106 \def\AMC@sz@callout{}%
1107 \fi%
1108 \ifcsname AMC@sz@callin@#1\endcsname%
1109 \def\AMC@sz@callin{AMC@sz@callin@#1}%
1110 \else%
1111 \def\AMC@sz@callin{}%
1112 \fi%
1113 \ifcsname AMC@sz@init@#1\endcsname%
1114 \csname AMC@sz@init@#1\endcsname%
1115 \fi%
1116 }
1117 \newcommand{\AMCsetScoreZone}[1]{\setkeys{AMCsz}{#1}}
1118 \AMCsetScoreZone{width=1.5em,height=1.5ex,depth=.5ex,position=none}

```

And do the same for \AMCsetScoreZoneAnswerSheet...

```

1119 \newcommand{\AMC@sza@box}{\AMCemptybox{\AMC@sza@width}{\AMC@sza@height}{\AMC@sza@depth}}
1120 %
1121 \newcommand{\AMC@sza@init@none}{}
1122 \newcommand{\AMC@sza@callout@none}{}
1123 \newcommand{\AMC@sza@callin@none}{}
1124 %
1125 \newcommand{\AMC@sza@init@question}{}
1126 \newcommand{\AMC@sza@callout@question}{}
1127 \newcommand{\AMC@sza@callin@question}{\AMCscoreZone{\AMC@sza@box}}
1128 %
1129 \newcommand{\AMC@sza@init@margin}{}
1130 \newcommand{\AMC@sza@callout@margin}{\hspace{Opt}\marginpar{\AMCscoreZone{\AMC@sza@box}}}
1131 \newcommand{\AMC@sza@callin@margin}{}
1132 %
1133 \newcommand{\AMC@sza@init@margins}{\PackageWarning{automultiplechoice}{Please run twice to get proper ma}}
1134 \newcommand{\AMC@sza@callout@margins}{\hspace{Opt}\AMCmarginNote{\AMCscoreZone{\AMC@sz@box}}}
1135 \newcommand{\AMC@sza@callin@margins}{}
1136 %
1137 \newlength\AMC@sza@width
1138 \newlength\AMC@sza@height
1139 \newlength\AMC@sza@depth
1140 \def\AMC@sza@callout{}
1141 \def\AMC@sza@callin{}
1142 \define@key{AMCsza}{width}{\AMC@sza@width=#1}
1143 \define@key{AMCsza}{height}{\AMC@sza@height=#1}
1144 \define@key{AMCsza}{depth}{\AMC@sza@depth=#1}
1145 \define@key{AMCsza}{calloutsideside}{\def\AMC@sza@callout{#1}}
1146 \define@key{AMCsza}{callinside}{\def\AMC@sza@callin{#1}}
1147 \define@choicekey{AMCsza}{position}{none,question,margin,margins}{%
1148 \ifcsname AMC@sza@callout@#1\endcsname%
1149 \def\AMC@sza@callout{AMC@sza@callout@#1}%
1150 \else%
1151 \def\AMC@sza@callout{}%
1152 \fi%
1153 \ifcsname AMC@sza@callin@#1\endcsname%
1154 \def\AMC@sza@callin{AMC@sza@callin@#1}%
1155 \else%

```

```

1156 \def\AMC@sza@callin{}%
1157 \fi%
1158 \ifcsname AMC@sza@init@#1\endcsname%
1159 \csname AMC@sza@init@#1\endcsname%
1160 \fi%
1161 }
1162 \newcommand{\AMCsetScoreZoneAnswerSheet}[1]{\setkeys{AMC@sza}{#1}}
1163 \AMCsetScoreZoneAnswerSheet{width=1.5em,height=1.5ex,depth=.5ex,position=none}
1164 \newcommand{\AMCnoScoreZone}{\AMCsetScoreZone{position=none}\AMCsetScoreZoneAnswerSheet{position=none}}

```

4.11.5 Formatting questions

`\AMCquestionaff` The counter `\AMCquestionaff` keeps track of the current question number. It can be redefined by the user, for example to print several questions without a number, and then print questions with a number starting at one.

`\AMC@stepQuestion` will increase this counter and `\AMC@qaff` will format the question number out.

```

1165 \newcounter{AMCquestionaff}
1166 \newcommand{\AMCnumero}[1]{\setcounter{AMCquestionaff}{#1}\addtocounter{AMCquestionaff}{-1}}
1167 \AtBeginDocument{%
1168 \ifx\@skiphyperreftrue\@undefined%
1169 \expandafter\newif\csname if@skiphyperref\endcsname%
1170 \fi%
1171 }
1172 \newcommand\AMC@stepQuestion{\ifAMCquestionNumber\@skiphyperreftrue\refstepcounter{AMCquestionaff}\@skip
1173 \newcommand\AMC@qaff{\arabic{AMCquestionaff}}

```

`\AMCbeforeQuestion` The command `\AMCbeforeQuestion` opens a new question. The command `\AMCbeginQuestion{<n>}{<sign>}` will format the question header, where `<n>` is the question number and `<sign>` being `\multiSymbole` in case of a multiple question, and empty in case of a simple one. `\AMCbeforeQuestion`, `\AMCbeginQuestion` and `\multiSymbole` can be user-redefined.

```

1174 \def\AMCbeforeQuestion{\ifAMC@qbloc\else\par\noindent\fi}
1175 \def\AMCbeginQuestion#1#2{\noindent\AMC@loc@q{#1}{#2}%
1176 \ifx\@empty\AMC@sz@callin\@empty\hspace*{1em}\fi%
1177 }
1178 \def\multiSymbole{${\clubsuit}$}

```

`question (env.)` Environment `{question}{<key>}` encloses a simple question (with one and only one correct choice) with associated unique key `<key>` and the proposed answers.

`variable-single (env.)` Environment `{questionmult}{<key>}` is the same for multiple questions (with none, one or several correct choices).

`questionouverte (env.)` Environment `{questionmultx}{<key>}` is the same as `questionmult`, but with no use of `\ouverte@vs` `\multiSymbole`.

Environment `{questionouverte}[<width>]` is used for open questions (that won't be marked automatically!), with width given as an optional argument (defaults to 3 cm).

The command `\AMCexternalQuestion{<id>}{<maxscore>}` allows to declare a question that will be scored outside AMC, with a maximal score `<maxscore>`. When you use this command, you can manage the question number and question text freely (AMC won't handle this).

```

1179 \ifx\question\undefined\else\let\question\undefined\fi
1180 \def\AMCnobloc{\AMC@qblocfalse}
1181 \def\AMCbloc{\AMC@qbloctrue}

```

```

1182 \newcommand\AMCstartWithQuestion[1]{%
1183   \global\def\AMCid@name{#1}\AMC@affecte{#1}{\AMCid@quest}%
1184   \ifAMC@calibration%
1185     \AMCmessage{Q=\the\AMCid@quest}%
1186     \immediate\write\AMC@XYFILE{\string\question{\the\AMCid@quest}{\AMCid@name}}%
1187   \fi%
1188 }
1189 \newcommand\AMCexternalQuestion[2]{%
1190   \AMCstartWithQuestion{#1}%
1191   \ifAMC@calibration%
1192     \AMCmessage{B=MAX=#2}%
1193     \AMCmessage{MULT}%
1194     \AMCmessage{FQ}%
1195   \fi%
1196 }
1197 \newenvironment{question}[2][ ]{%
1198   \def\AMCcurrentenv{question}%
1199   \AMC@stepQuestion%
1200   \AMCstartWithQuestion{#2}%
1201   \AMCbeforeQuestion%
1202   \ifx\@empty\AMC@sz@callout\@empty\else%
1203     \csname\AMC@sz@callout\endcsname%
1204   \fi%
1205   \AMCtype@multifalse\ifAMC@qbloc\ifAMC@textPos\vbox\bgroup\AMC@tracepos{1}{qtext:#2:\the\AMCid@quest,0}%
1206   \ifAMC@affichekeys\index{\texttt{#2}}\ifAMC@keyline[\texttt{#2}]\newline\fi\fi%
1207   \AMCbeginQuestion{\ifAMC@affichekeys\ifAMC@ensemble\AMC@qaff\ \fi\ifAMC@keyline\else[\texttt{#2}]\fi}%
1208   \ifx\@empty\AMC@sz@callin\@empty\else%
1209     \csname\AMC@sz@callin\endcsname%
1210   \fi%
1211   \AMCformulaire@dedansfalse\setcounter{AMC@ncase}{0}%
1212   \AMC@mem@openQuestion}%
1213 {\ifAMC@qbloc\end{minipage}\ifAMC@textPos\AMC@tracepos{1}{qtext:\AMCid@name:\the\AMCid@quest,0}\egroup\AMC@end}%
1214 \newenvironment{questionmult}[1]{%
1215   \AMC@bonnefalse\begin{question}[{\multiSymbole}]{#1}%
1216   \AMCtype@multitrue\ifAMC@calibration%
1217     \AMCmessage{MULT}\fi%
1218 }{\end{question}}
1219 \newenvironment{variable-single}[2]
1220 {\def\AMCbeginQuestion##1##2{}
1221 \begin{questionmult}{#1}\scoring{v=#2}
1222 \begin{tikz-single}[o]}
1223 {\end{tikz-single}
1224 \end{questionmult}}
1225 \newenvironment{variable-multi}[4]
1226 {\def\AMCbeginQuestion##1##2{}
1227 \begin{questionmult}{#1}\scoring{v=#4}
1228 \begin{tikz-multi}[o]
1229 \node[#3] (var) at (0,0) {#2};}
1230 {\end{tikz-multi}
1231 \end{questionmult}}
1232 \newenvironment{questionmultx}[1]{%
1233   \begin{group}\def\multiSymbole{}\begin{questionmult}{#1}%
1234   {\end{questionmult}\end{group}}

```



```

1235 \newdimen\ouverte@vs
1236 \newenvironment{questionouverte}[1][3cm]{%
1237   \AMC@stepQuestion%
1238   \AMCtype@multifalse\ouverte@vs=#1%
1239   \ifAMC@qbloc\noindent\begin{minipage}{\linewidth}\fi%
1240   \AMCbeginQuestion{\AMC@qaff}{}}%
1241 {\vspace*{\ouverte@vs}\ifAMC@qbloc\end{minipage}\vspace{3ex}\fi}

```

4.11.6 Explanations

`\explain` The command `\explain{<text>}` is used inside question-like environments to give the explanation for the answers of a question. The command `\explaincontext{<text>}` inserts its argument only in the corrected paper.

```

1242 \newcommand{\explain}[1]{%
1243   \ifAMC@correthead%
1244     \AMCif@env{question}{\par\noindent{\AMC@loc@explain #1}}{\AMC@error@explain}\vspace{1ex}%
1245   \else%
1246     \AMCif@env{question}{}{\AMC@error@explain}%
1247   \fi%
1248 }
1249 \newcommand{\explaincontext}[1]{%
1250   \ifAMC@correc%
1251     #1%
1252   \fi%
1253 }

```

4.12 Scoring

`\scoring` Scoring strategies are simply transmitted to the `.amc` file for later analysis.

`\scoringDefaultS` `\scoring{<score>}` details the scoring strategy for current question or current answer,
`\scoringDefaultM` `\scoringDefaultS{<score>}` and `\scoringDefaultM{<score>}` gives default scoring strategy for
`QuestionIndicative` simple and multiple questions, and `\QuestionIndicative` tells that the current question is not
 no be taken into account in the global mark.

```

1254 \def\scoring#1{\ifAMC@calibration\AMCmessage{B=#1}\fi\ignorespaces}
1255 \def\scoringDefaultS#1{\ifAMC@calibration\AMCmessage{BDS=#1}\fi}
1256 \def\scoringDefaultM#1{\ifAMC@calibration\AMCmessage{BDM=#1}\fi}
1257 \def\QuestionIndicative{\ifAMC@calibration\AMCmessage{INDIC}\fi}

```

4.13 Numerical data

4.13.1 Codes

`\AMCcodeGrid` Students can code some numerical information (such as student number) through special questions, which can be formatted easily with the command `\AMCcodeGrid[⟨opts⟩]{⟨key⟩}{⟨descr⟩}`, where `⟨key⟩` is a key prefix and `⟨descr⟩` is a coma-separated list of character pools to offer. The characters entered by the student will be available through the questions `⟨key⟩[1], …, ⟨key⟩[⟨length(descr)⟩]`.

As an example,

`\AMCcodeGrid{code}{ABCD,012345,012345,012345,012345}` produces the opposite boxes (two results are show here: without or with `separateanswersheet` option), and trace positions of all the boxes in the `.xy` file with the `code` identifier: the first digit is represented by question with key `code[6]`, the second by question with key `code[5]`, and so on.

Positions of the boxes are logged in the `.xy` file, as shown in section 5.3 for the first set of boxes (without `separateanswersheet`, with digits outside boxes).

	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>
	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>
<input type="text"/>	A	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2
<input type="text"/>	B	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3
<input type="text"/>	C	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4
<input type="text"/>	D	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5

	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>	0	<input type="text"/>
	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>	1	<input type="text"/>
<input type="text"/>	A	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2	<input type="text"/>	2
<input type="text"/>	B	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3	<input type="text"/>	3
<input type="text"/>	C	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4	<input type="text"/>	4
<input type="text"/>	D	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5	<input type="text"/>	5

The “horizontal” version can also be considered using option `h`, especially with a small number of digits. See opposite for the result of

`\AMCcodeGrid[h]{code}{ABCDEF,0123456789,0123456789}`.

The `\AMCcodeGridInt[⟨opts⟩]{⟨key⟩}{⟨n⟩}` is a shortcut for calling `\AMCcodeGrid` with `⟨n⟩` digits from 0 to 9. This allows to create grids for `⟨n⟩`-digits integers easily.

These two commands supports the following options (given as a comma-separated list optional argument `⟨opts⟩`):

- `vertical=true` or `false` to indicate the direction to be used (default is `true`);
- `h` is a shortcut for `vertical=false`;
- `v` is a shortcut for `vertical=true`;
- `top` to request top-aligned columns in vertical direction.
- `multi` for codes that are repeated on each page.

```

1258 \newcount\AMC@chiffres
1259 \newdimen\AMCcodeHspace\AMCcodeHspace=.5em
1260 \newdimen\AMCcodeVspace\AMCcodeVspace=.5em
1261 \newcommand\AMCcodeID@squarebrackets[2]{#1[#2]}
1262 \newcommand\AMCcodeID@dot[2]{#1.#2}
1263 \newcommand\AMCcodeID@@[1]{%
1264   \expandafter\def\expandafter\AMCcodeID\expandafter{\csname AMCcodeID@#1\endcsname}%
1265   \def\AMCcodeID@mode{#1}%
1266 }
```

```

1267 \AMCcodeID@@{squarebrackets}
1268 \ExplSyntaxOn
1269
1270 \clist_new:N \amc_code_descr_clist
1271 \seq_new:N \amc_code_digits_seq
1272 \int_new:N \amc_code_digit_n_int
1273 \bool_new:N \amc_code_vertical_bool
1274 \bool_new:N \amc_code_top_bool
1275 \bool_new:N \amc_code_multi_bool
1276 \clist_new:N \amc__multi_clist
1277
1278 \cs_new:Npn \amc_code_init:N #1 {
1279   \def\AMCbeginQuestion##1##2{}
1280   \def\AMCbeforeQuestion{}
1281   \AMCnoScoreZone
1282   \AMCquestionNumberfalse
1283   \setlength{\parindent}{0pt}
1284   \AMCnobloc
1285   \int_set:Nn \amc_code_digit_n_int { \clist_count:N #1 }
1286 }
1287
1288 \cs_new:Nn \amc_code_digit_init: {
1289   \QuestionIndicative
1290   \global\AMCrep@count=\z@
1291 }
1292
1293 \cs_new:Npn \amc_code_digit:n #1 {
1294   \global\advance\AMCrep@count\@ne\relax
1295   \ifAMC@calibration\AMCmessage{ REP = \the\AMCrep@count : M }\fi
1296   \hbox{\AMC@keyBox@{#1}{1}{case : \AMCid@name : \the\AMCid@quest , \the\AMCrep@count}}
1297   \bool_if:NTF \amc_code_vertical_bool {
1298     \vspace{\AMCcodeVspace}
1299   }{
1300     \hspace{\AMCcodeHspace}
1301   }
1302 }
1303
1304 \keys_define:nn { amccode } {
1305   vertical .bool_set:N = \amc_code_vertical_bool,
1306   vertical .initial:n = { true },
1307   vertical .default:n = { true },
1308   v .code:n = { \bool_set_true:N \amc_code_vertical_bool },
1309   h .code:n = { \bool_set_false:N \amc_code_vertical_bool },
1310   top .bool_set:N = \amc_code_top_bool,
1311   top .initial:n = { false },
1312   top .default:n = { true },
1313   multi .bool_set:N = \amc_code_multi_bool,
1314   multi .initial:n = { false },
1315   multi .default:n = { true }
1316 }
1317
1318 \cs_new_nopar:Nn \amc_multi_report: {
1319   \ifAMC@calibration

```

```

1320 \immediate\write\AMC@XYFILE{\string\with{multi=\clist_use:Nn\amc__multi_clist{,}}}}
1321 \fi
1322 }
1323 \cs_new_eq:NN \AMC@multi@report \amc_multi_report:
1324 \int_new:N \amc_multi_count_int
1325 \cs_new_nopar:Nn \amc_multi_clear: {
1326   \int_gzero:N \amc_multi_count_int
1327 }
1328 \cs_new_eq:NN \AMC@multiclear \amc_multi_clear:
1329
1330 \cs_new:Npn \amc_code_generate:nNn #1#2#3 {
1331   { \keys_set:nn { amccode } { #3 }
1332     \bool_if:NTF \amc_code_multi_bool {
1333       \clist_gset:Nn \amc__multi_clist { #1 }
1334     } {}
1335     \bool_if:NTF \amc_code_multi_bool { \int_gincr:N \amc_multi_count_int } {}
1336     \amc_code_init:N #2
1337     \clist_map_inline:Nn #2 { % iterates over 'digits'
1338       \begin{question}{
1339         \AMCcodeID{ #1 \bool_if:NTF
1340           \amc_code_multi_bool
1341           { * \int_use:N \amc_multi_count_int } {} }
1342         { \int_use:N \amc_code_digit_n_int }
1343       }
1344       \amc_code_digit_init:
1345       \seq_set_split:Nnn \amc_code_digits_seq {} { ##1 }
1346       \bool_if:NTF \amc_code_vertical_bool {
1347         \hspace{0pt}
1348         \bool_if:NTF \amc_code_top_bool { \vtop } { \vbox }
1349         \bgroup
1350       }{
1351         \hbox\bgroup
1352       }
1353       \seq_map_inline:Nn \amc_code_digits_seq {
1354         % iterates over available characters for 'digit'
1355         \amc_code_digit:n { ####1 }
1356       }
1357       \bool_if:NTF \amc_code_vertical_bool {
1358         \vspace{-\AMCcodeVspace}\egroup
1359         \hspace{\AMCcodeHspace}
1360       }{
1361         \egroup\vspace{\AMCcodeVspace}
1362         \par
1363       }
1364       \end{question}
1365       \int_decr:N \amc_code_digit_n_int
1366     }
1367   }
1368 }
1369
1370 \cs_new:Npn \amc_code_generate:nnn #1#2#3 {
1371   \clist_set:Nn \amc_code_descr_clist { #2 }
1372   \amc_code_generate:nNn { #1 } \amc_code_descr_clist { #3 }

```

```

1373 }
1374 \cs_generate_variant:Nn \amc_code_generate:nnn { xxx }
1375 \newcommand{\AMCcodeGrid}[3][]{
1376   \amc_code_generate:xxx { #2 } { #3 } { #1 }
1377 }
1378
1379 \cs_new:Npn \amc_code_generate_integer:nnn #1#2#3 {
1380   \clist_clear:N \amc_code_descr_clist
1381   \prg_replicate:nn { #2 } { \clist_put_right:Nn \amc_code_descr_clist { 0123456789 } }
1382   \amc_code_generate:nNn { #1 } \amc_code_descr_clist { #3 }
1383 }
1384 \cs_generate_variant:Nn \amc_code_generate_integer:nnn { xxx }
1385 \newcommand{\AMCcodeGridInt}[3][]{
1386   \amc_code_generate_integer:xxx { #2 } { #3 } { #1 }
1387 }
1388
1389 \cs_new:Npn \amc_code_generate_integer_v:nn #1#2 {
1390   \amc_code_generate_integer:nnn { #1 } { #2 } { v }
1391 }
1392 \cs_new:Npn \amc_code_generate_integer_h:nn #1#2 {
1393   \amc_code_generate_integer:nnn { #1 } { #2 } { h }
1394 }
1395 \cs_generate_variant:Nn \amc_code_generate_integer_v:nn { xx }
1396 \cs_generate_variant:Nn \amc_code_generate_integer_h:nn { xx }
1397 \cs_new_eq:NN \AMCcode \amc_code_generate_integer_v:xx
1398 \cs_new_eq:NN \AMCcodeH \amc_code_generate_integer_h:xx
1399
1400 \ExplSyntaxOff

```

4.13.2 Numerical questions

`\AMCnumericChoices` The command `\AMCnumericChoices{<correct>}{<options>}` can be used as a replacement for the `choices` environment when the questions asks for a numeric value to code on the answer sheet.

As an example,

```

\begin{question}{product}
  What is the value of  $7 \times 5$ ?
  \AMCnumericChoices{35}{digits=2,sign=false}
\end{question}

```

produces (in correction mode):

Question 11 What is the value of 7×5 ?																				
<table border="1" style="margin: auto; border-collapse: collapse;"> <tr> <td><input type="checkbox"/>0</td><td><input type="checkbox"/>1</td><td><input type="checkbox"/>2</td><td><input checked="" type="checkbox"/>3</td><td><input type="checkbox"/>4</td><td><input type="checkbox"/>5</td><td><input type="checkbox"/>6</td><td><input type="checkbox"/>7</td><td><input type="checkbox"/>8</td><td><input type="checkbox"/>9</td> </tr> <tr> <td><input type="checkbox"/>0</td><td><input type="checkbox"/>1</td><td><input type="checkbox"/>2</td><td><input type="checkbox"/>3</td><td><input type="checkbox"/>4</td><td><input checked="" type="checkbox"/>5</td><td><input type="checkbox"/>6</td><td><input type="checkbox"/>7</td><td><input type="checkbox"/>8</td><td><input type="checkbox"/>9</td> </tr> </table>	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input checked="" type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9	<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input checked="" type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9
<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input checked="" type="checkbox"/> 3	<input type="checkbox"/> 4	<input type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9											
<input type="checkbox"/> 0	<input type="checkbox"/> 1	<input type="checkbox"/> 2	<input type="checkbox"/> 3	<input type="checkbox"/> 4	<input checked="" type="checkbox"/> 5	<input type="checkbox"/> 6	<input type="checkbox"/> 7	<input type="checkbox"/> 8	<input type="checkbox"/> 9											

and these boxes are only shown on the separate answer sheet if the `separateanswersheet` option is used.

This command uses the `\AMCformatChoices{<showcommand>}{<hidecommand>}{<arg1>}{<arg2>}` command, that calls either `<hidecommand>{<arg1>}{<arg2>}` if the `separateanswersheet` op-

tion is used and if we are currently in the question part (not in the answer sheet), or $\langle showcommand \rangle \{ \langle arg1 \rangle \} \{ \langle arg2 \rangle \}$ when all the boxes are to be produced.

```

1401 \newcommand\AMCformatChoices[4]{%
1402   \global\AMCrep@count=\z@%
1403   \AMC@if@separate@question{%
1404     \AMC@mem@add{\global\AMCrep@count=\z@%
1405       #1{#3}{#4}}%
1406   }%
1407   \ifAMC@ensemble%
1408     #2{#3}{#4}%
1409     \AMCmessage{QPART}%
1410   \else%
1411     #1{#3}{#4}%
1412   \fi%
1413 }
```

Some computation commands are now defined. The command $\backslash amc_fp_decompose:NNn\{\langle fp\ var \rangle\}\{\langle int\ var \rangle\}\{\langle x \rangle\}$ sets $\langle fp\ var \rangle$ to be the *mantissa* and $\langle int\ var \rangle$ the *exponent* of the floating point number $\langle x \rangle$. For example, $\backslash amc_fp_decompose:NNn\mant_fp\expo_int\{123.456\}$ give the value 1.23456 to $\backslash mant_fp$ and 2 to $\backslash expo_int$ (because $123.456 = 1.23456 \times 10^2$).

The command $\backslash amc_fp_to_digits:Nnnn\{\langle clist \rangle\}\{\langle x \rangle\}\{\langle n\ digits \rangle\}\{\langle base \rangle\}$ rounds the floating point number $\langle x \rangle$ and populates the comma separated list $\langle clist \rangle$ with its $\langle n\ digits \rangle$ digits in base $\langle base \rangle$. An error is issued if $\langle x \rangle$ would have required more digits.

```

1414 \ExplSyntaxOn
1415
1416 \cs_generate_variant:Nn \tl_replace_once:Nnn { Nxn }
1417
1418 \tl_new:N \amc_ee_tl
1419 \seq_new:N \amc_ee_seq
```

Note that with some versions of 13fp-convert (prior to 2017-09-18), $\backslash fp_to_scientific$ leads to a ‘e’ with catcode 12 (*other*). We convert it to catcode *letter* before splitting.

```

1420 \group_begin:
1421 \char_set_catcode_other:N E
1422 \tex_lowercase:D
1423 {
1424   \cs_new:Npn \amc_read_scientific:NNn #1 #2 #3 {
1425     \tl_set:Nn \amc_ee_tl { #3 }
1426     \tl_replace_once:Nxn \amc_ee_tl { E } { e }
1427     \seq_set_split:NnV \amc_ee_seq e \amc_ee_tl
1428     \fp_set:Nn #1 { \seq_item:Nn \amc_ee_seq 1 }
1429     \int_set:Nn #2 { \seq_item:Nn \amc_ee_seq 2 }
1430   }
1431 }
1432 \group_end:
1433
1434 \cs_generate_variant:Nn \amc_read_scientific:NNn { NNf, NNx }
1435
1436 \fp_new:N \amc_fulls_fp
1437 \cs_new:Npn \amc_fp_decompose:NNn #1 #2 #3 {
1438   \fp_set:Nn \amc_fulls_fp { #3 }
```

Note that with some versions of 13fp-convert, the exponent part is omitted for some values, so that we add e 0.

```

1439 \amc_read_scientific:NNx #1 #2
1440 { \fp_to_scientific:N \amc_fulls_fp e 0 }
1441 }
1442 \cs_generate_variant:Nn \amc_fp_decompose:NNn { NNx }
1443
1444 \fp_new:N \amc_num_mantissa_fp
1445 \int_new:N \amc_num_exponent_int
1446 \cs_new:Npn \amc_fp_n_significant_digits:Nnn #1 #2 #3 {
1447   \amc_fp_decompose:NNn \amc_num_mantissa_fp \amc_num_exponent_int
1448   { #2 }
1449   \fp_set:Nn #1
1450   { round(\amc_num_mantissa_fp * 10^((#3)-1)) }
1451   \fp_compare:nTF { abs(#1) >= 10^(#3) }
1452   {
1453     \fp_set:Nn #1 { #1 / 10 }
1454   } { }
1455 }
1456
1457 \fp_new:N \amc_num_nsig_fp
1458 \cs_new:Npn \amc_fp_show_n_significant_digits:nn #1 #2 {
1459   \amc_fp_n_significant_digits:Nnn \amc_num_nsig_fp { #1 } { #2 }
1460 }
1461 \cs_new_eq:NN \AMCsignificantDigits \amc_fp_show_n_significant_digits:nn
1462
1463 \cs_new:Npn \amc_fp_show_significant_digits: {
1464   \fp_use:N \amc_num_nsig_fp
1465 }
1466 \cs_new_eq:NN \AMCshowSignificantDigits \amc_fp_show_significant_digits:
1467
1468 \cs_new:Npn \amc_fp_n_digits:Nnn #1 #2 #3 {
1469   \fp_set:Nn #1
1470   { round((#2) * \amc_num_base_int^(#3)) }
1471 }
1472
1473 \int_new:N \amc_todigits_int
1474 \cs_new:Npn \amc_fp_to_digits:Nnnn #1 #2 #3 #4 {
1475   \clist_clear:N #1
1476   \int_set:Nn \amc_todigits_int { \fp_eval:n { abs(round(#2)) } }
1477   \prg_replicate:nn { #3 } {
1478     \clist_put_left:Nx #1 { \int_mod:nn \amc_todigits_int { #4 } }
1479     \int_set:Nn \amc_todigits_int
1480     { \int_div_truncate:nn \amc_todigits_int { #4 } }
1481   }
1482   \int_compare:nNnTF \amc_todigits_int = 0 { } {
1483     \message{^^J!~Error:~number~too~large,
1484       ~some~digits~will~be~discarded^^J}
1485   }
1486 }
1487
1488 \cs_new:Npn \amc_invalid_digits:Nn #1 #2 {
1489   \clist_clear:N #1
1490   \prg_replicate:nn { #2 } { \clist_put_left:Nx #1 { -1 } }
1491 }

```

```

1492
1493 \cs_new:Npn \amc_get_fp_sign:Nn #1 #2 {
1494   \fp_compare:nNnTF #2 < 0 {
1495     \int_set:Nn #1 { -1 }
1496   }{
1497     \fp_compare:nNnTF #2 > 0 {
1498       \int_set:Nn #1 { 1 }
1499     }{
1500       \int_set:Nn #1 { 0 }
1501     }
1502   }
1503 }
1504
1505 \cs_new:Npn \amc_get_int_sign:Nn #1 #2 {
1506   \int_compare:nNnTF #2 < 0 {
1507     \int_set:Nn #1 { -1 }
1508   }{
1509     \int_compare:nNnTF #2 > 0 {
1510       \int_set:Nn #1 { 1 }
1511     }{
1512       \int_set:Nn #1 { 0 }
1513     }
1514   }
1515 }
1516
1517 \ExplSyntaxOff

The command \AMCnumericShow{<value>}{<opts>} is called to draw all necessary boxes
to code a numerical value <value> with options given as a comma separated list <opts>.
\AMCnumericOpts{<opts>} can be used to set some default values for these options.

Begin with the available options:

1518 \def\AMCnntextGoto{}
1519 \def\AMCnntextVHead#1{\emph{b#1}}
1520 \newdimen\AMCnumeric@Hspace\AMCnumeric@Hspace=.5em
1521 \newdimen\AMCnumeric@Vspace\AMCnumeric@Vspace=1ex
1522 \ExplSyntaxOn
1523
1524 \keys_define:nn { amcnumeric } {
1525   Tsign .code:n = {\def\AMCnntextSign{#1}},
1526   Tsign .initial:n = {},
1527   Tpoint .code:n = {\def\AMCdecimalPoint{#1}},
1528   Tpoint .initial:n = { \raisebox{1ex}{\bf .} },
1529   Texponent .code:n = {\def\AMCexponent{#1}},
1530   Texponent .initial:n = { $\times 10^{\textasciicircum} $ },
1531   vspace .code:n = {\AMCnumeric@Vspace=#1},
1532   hspace .code:n = {\AMCnumeric@Hspace=#1},
1533   bordercol .code:n = {\def\AMCncol@Border{#1}},
1534   bordercol .initial:n = { lightgray },
1535   borderwidth .code:n = {\def\AMCncol@BorderWidth{#1}},
1536   borderwidth .initial:n = { 1mm },
1537   backgroundcol .code:n = {\def\AMCncol@Background{#1}},
1538   backgroundcol .initial:n = { white },
1539   digits .int_set:N = \amc_num_ndigits_int,
1540   digits .initial:n = { 3 },

```



```

1541 decimals .int_set:N = \amc_num_decd_int,
1542 decimals .initial:n = { 0 },
1543 exponent .int_set:N = \amc_num_expo_int,
1544 exponent .initial:n = { 0 },
1545 base .int_set:N = \amc_num_base_int,
1546 base .initial:n = { 10 },
1547 sign .bool_set:N = \amc_num_sign_bool,
1548 sign .initial:n = { true },
1549 sign .default:n = { true },
1550 exposign .bool_set:N = \amc_num_exposign_bool,
1551 exposign .initial:n = { true },
1552 exposign .default:n = { true },
1553 strict .bool_set:N = \amc_num_strict_bool,
1554 strict .initial:n = { false },
1555 strict .default:n = { true },
1556 scoring .bool_set:N = \amc_num_scoring_bool,
1557 scoring .initial:n = { true },
1558 scoring .default:n = { true },
1559 ignoreblank .bool_set:N = \amc_num_ignoreblank_bool,
1560 ignoreblank .initial:n = { false },
1561 ignoreblank .default:n = { true },
1562 vertical .bool_set:N = \amc_num_vertical_bool,
1563 vertical .initial:n = { false },
1564 vertical .default:n = { true },
1565 expovertical .bool_set:N = \amc_num_expovertical_bool,
1566 expovertical .initial:n = { false },
1567 expovertical .default:n = { true },
1568 reverse .bool_set:N = \amc_num_reverse_bool,
1569 reverse .initial:n = { false },
1570 reverse .default:n = { true },
1571 vhead .bool_set:N = \amc_num_vhead_bool,
1572 vhead .initial:n = { false },
1573 vhead .default:n = { true },
1574 Tvhead .code:n = {\clist_set:Nx \amc_tvhead_clist {\clist_reverse:n {#1}}},
1575 Tvhead .initial:n = {}, % \c_empty_clist does not work with \clist_reverse:n
1576 vheadunitindex .int_set:N = \amc_vheadunitindex_int,
1577 vheadunitindex .initial:n = 0,
1578 nozero .bool_set:N = \amc_num_nozero_bool,
1579 nozero .initial:n = { false },
1580 nozero .default:n = { true },
1581 significant .bool_set:N = \amc_num_significant_bool,
1582 significant .initial:n = { false },
1583 significant .default:n = { true },
1584 scoreexact .code:n = {\def\AMC@numeric@scoreexact{#1}},
1585 scoreexact .initial:n = { 2 },
1586 scoreapprox .code:n = {\def\AMC@numeric@scoreapprox{#1}},
1587 scoreapprox .initial:n = { 1 },
1588 scorewrong .code:n = {\def\AMC@numeric@scorewrong{#1}},
1589 scorewrong .initial:n = { 0 },
1590 exact .int_set:N = \amc_num_exact_int,
1591 exact .initial:n = { 0 },
1592 approx .int_set:N = \amc_num_approx_int,
1593 approx .initial:n = { 0 },

```

```

1594 keepas .code:n = {\def\AMC@numeric@keepas{#1}},
1595 keepas .initial:n = {},
1596 alsocorrect .code:n = {\def\AMC@numeric@alsocorrect{#1}},
1597 alsocorrect .initial:n = {}
1598 }
1599
1600 \cs_new:Npn \amc_num_setopts #1 {
1601   \keys_set:nn { amcnumeric } { #1 }
1602 }
1603
1604 \cs_new_nopar:Nn \amc_num_check_score_opts: {
1605   \bool_if:NTF \amc_num_ignoreblank_bool {
1606     \int_compare:nNnTF \amc_num_base_int = { 10 } { } {
1607       \message{^^J!~Error:~ignoreblank~can~only~be~used~with~number~base~10^^J}
1608     }
1609   } {}
1610 }
1611
1612 \cs_new_eq:NN \AMCnumericOpts \amc_num_setopts
1613

```

The command `\amc_num_char:nn{<i>}<j>}` draw a box with content *<i>* (only if needed), where *<j>* is `\AMC@checkbox` if the corresponding choice is correct and empty if not.

```

1614 \cs_new:Npn \amc_num_char:nn #1 #2 {
1615   \global\advance\AMCrep@count\@ne\relax
1616   \AMCmessage{REP= \the\AMCrep@count :
1617     \ifx#2\AMC@checkbox B\else M\fi }
1618   \ifAMC@correc
1619     \protect\AMC@keyBox@{#1}{#2}{1}{case : \AMCid@name :
1620       \the\AMCid@quest , \the\AMCrep@count}
1621   \else
1622     \protect\AMC@keyBox@{#1}{}{1}{case : \AMCid@name :
1623       \the\AMCid@quest , \the\AMCrep@count}
1624   \fi
1625 }

```

The command `\amc_num_digit_box:nn{<i>}<j>}` draws a box for current digit value *<i>*, where *<j>* is the correct value for the current digit. If *<i>* is greater than 9, it is converted to a character from the English alphabet (A for 10, B for 11...)

```

1626 \int_new:N \amc_num_digit_value_int
1627 \tl_new:N \amc_num_digit_value_tl
1628 \cs_new:Npn \amc_num_digit_box:nn #1 #2 {
1629   \int_set:Nn \amc_num_digit_value_int { #1 }
1630   \tl_set:Nn \amc_num_digit_value_tl {
1631     \int_compare:nNnTF { \amc_num_digit_value_int } < { 10 }
1632     { \int_to_arabic:n { \amc_num_digit_value_int } }
1633     { \int_to_Alph:n { \amc_num_digit_value_int - 9 } }
1634   }
1635   \int_compare:nNnTF { #1 } = { #2 } {
1636     \amc_num_char:nn{ \tl_use:N \amc_num_digit_value_tl }
1637     {\AMC@checkbox}
1638   } {
1639     \amc_num_char:nn{ \tl_use:N \amc_num_digit_value_tl }

```

```

1640         {}
1641     }
1642 }

```

The command `\amc_num_sign_boxes:Nn{<sign>}{<prefix>}` draws two boxes for the students to code the sign (with a right value given by the boolean `<negative>`).

```

1643 \cs_new:Npn \amc_num_sign_boxes:Nn #1 #2 {
1644   \int_case:nn { #1 } {
1645     { -1 } {
1646       \hbox{\amc_num_char:nn{+$}{}}
1647       \vspace{\AMCnumeric@Vspace}
1648       \AMCmessage{B=set. sign #2 =1}
1649       \hbox{\amc_num_char:nn{$-}{\AMC@checkbox}}
1650       \AMCmessage{B=set. sign #2 =-1}
1651     }
1652     { 1 } {
1653       \hbox{\amc_num_char:nn{+$}{\AMC@checkbox}}
1654       \vspace{\AMCnumeric@Vspace}
1655       \AMCmessage{B=set. sign #2 =1}
1656       \hbox{\amc_num_char:nn{$-}{}}
1657       \AMCmessage{B=set. sign #2 =-1}
1658     }
1659     { 0 } {
1660       \hbox{\amc_num_char:nn{+$}{}}
1661       \vspace{\AMCnumeric@Vspace}
1662       \AMCmessage{B=set. sign #2 =1}
1663       \hbox{\amc_num_char:nn{$-}{}}
1664       \AMCmessage{B=set. sign #2 =-1}
1665     }
1666   }
1667 }

```

The command `\amc_num_digit_boxes_h:nnn{<varname>}{<correct>}{<maxdigit>}` draws a serie of boxes for all possible values of a digit (from 0 to `<maxdigit>`), where the correct value is `<correct>`, transmitting scoring data to AMC so that the variable `<varname>` will be set to the value chosen by the student.

```

1668 \cs_new:Npn \amc_num_digit_boxes_h:nnn #1 #2 #3 {
1669   \int_step_inline:nnnn
1670   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1671   { 1 } { #3 - 1 } {
1672     \amc_num_digit_box:nn { ##1 }{ #2 }
1673     \AMCmessage{B= set. #1 = ##1}
1674     \hspace{\AMCnumeric@Hspace}
1675   }
1676   \hspace{-\AMCnumeric@Hspace}
1677 }
1678
1679 \cs_new:Npn \amc_num_digit_boxes_v:nnn #1 #2 #3 {
1680   \int_step_inline:nnnn
1681   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1682   { 1 } { #3 - 1 } {
1683     \vbox{\hbox{
1684       \amc_num_digit_box:nn { ##1 }{ #2 }
1685     }}

```

```

1686 \AMCmessage{B= set. #1 = ##1}
1687 \int_compare:nNnTF { ##1 } < { #3 - 1 } {
1688   \vspace{\AMCnumeric@Vspace}
1689 } {}
1690 }
1691 }
1692
1693 \int_new:N \amc_num_first_digit_int
1694 \cs_new:Npn \amc_num_digit_boxes_vr:nnn #1 #2 #3 {
1695   \int_set:Nn \amc_num_first_digit_int
1696   { \bool_if:NTF \amc_num_nozero_bool { 1 } { 0 } }
1697   \int_step_inline:nnnn { #3 - 1 } { -1 }
1698   \amc_num_first_digit_int {
1699     \vbox{\hbox{
1700       \amc_num_digit_box:nn { ##1 } { #2 }
1701     }}
1702     \AMCmessage{B= set. #1 = ##1}
1703     \int_compare:nNnTF { ##1 } > \amc_num_first_digit_int {
1704       \vspace{\AMCnumeric@Vspace}
1705     } {}
1706   }
1707 }

```

The command `\amc_num_integer_boxes_v:Nnn{<correct digits>}{<prefix>}{<decimals>}` draws boxes for integer entry, without the sign.

```

1708 \cs_new:Npn \amc_num_integer_boxes_v:Nnn #1 #2 #3 {
begin a loop over all digits,
1709   \int_set_eq:NN \amc_num_digit_int { \clist_count:N #1 }
1710   \clist_map_inline:Nn #1 {
place the decimal point if necessary,
1711     \int_compare:nNnTF \amc_num_digit_int = { #3 } {
1712       \hbox{\AMCdecimalPoint }\hspace{\AMCnumeric@Hspace}
1713     } {}
draw the box for this digit,
1714     \hbox{\vbox{
1715       \bool_if:NTF \amc_num_vhead_bool {
1716         \vbox{\hbox to \AMC@boxedwidth{\hfill\AMCncontextVHead{ \int_eval:n
1717           { \amc_num_digit_int - 1 } }\hfill}}
1718         \vspace{\AMCnumeric@Vspace}
1719       } {}
1720       \bool_if:NTF \amc_num_reverse_bool {
1721         \amc_num_digit_boxes_vr:nnn { #2
1722           \int_to_Alph:n \amc_num_digit_int }
1723         { ##1 } { \amc_num_base_int }
1724       } {
1725         \amc_num_digit_boxes_v:nnn { #2
1726           \int_to_Alph:n \amc_num_digit_int }
1727         { ##1 } { \amc_num_base_int }
1728       }
1729     }}

```

and end the loop over digits, adding space if this is not the last one.

```

1730 \int_compare:nNnTF \amc_num_digit_int > 1 {
1731   \hspace{\AMCnumeric@Hspace}
1732 } { }
1733 \int_decr:N \amc_num_digit_int
1734 }
1735 }
1736

```

The command `\amc_num_integer_boxes_h:Nnn{<correct digits>}{<prefix>}{<decimals>}` does the same, in horizontal mode.

```

1737
1738 \cs_new:Npn \amc_num_integer_boxes_h:Nnn #1 #2 #3 {
1739   \vbox{
1740     \int_set_eq:NN \amc_num_digit_int { \clist_count:N #1 }
1741     \clist_map_inline:Nn #1 {
1742       \int_compare:nNnTF
1743       \amc_num_digit_int = { #3 } {
1744         \hbox{ \AMCdecimalPoint }
1745       } { }
1746       \hbox{
1747         \amc_num_digit_boxes_h:nnn { #2
1748           \int_to_Alph:n \amc_num_digit_int }
1749         { ##1 } \amc_num_base_int
1750       }
1751       \int_compare:nNnTF \amc_num_digit_int > 1 {
1752         \vspace{\AMCnumeric@Vspace}
1753       } { }
1754       \int_decr:N \amc_num_digit_int
1755     }
1756   }
1757

```

Finally, `\amc_num_integer_boxes:NnnNN{<correct digits>}{<prefix>}{<decimals>}{<sign bool>}{<sign>}` draws boxes for integer entry, including the sign if `<sign bool>` is true. When using the `strict` option, check the `+` box for a null value.

```

1758
1759 \cs_new:Npn \amc_num_integer_boxes:NnnNN #1 #2 #3 #4 #5 {
1760   \hbox{
1761     \bool_if:NTF { #4 } {
1762       \vbox{
1763         \ifx\AMCnTextSign\@empty\@empty\else
1764           \hbox{\AMCnTextSign}\vspace{\AMCnumeric@Vspace}\fi
1765         \bool_if:NTF \amc_num_strict_bool {
1766           \int_compare:nNnTF { #5 } = 0 {
1767             \amc_num_sign_boxes:Nn { 1 } { #2 }
1768           }{
1769             \amc_num_sign_boxes:Nn { #5 } { #2 }
1770           }
1771         }{
1772           \amc_num_sign_boxes:Nn { #5 } { #2 }
1773         }
1774       }
1775       \hspace{.5em}
1776       \vrule

```

```

1777     \hspace{.5em}
1778   } { }
1779   \hbox{
1780     \bool_if:NTF \amc_num_vertical_bool
1781     \amc_num_integer_boxes_v:Nnn \amc_num_integer_boxes_h:Nnn
1782     #1 { #2 } { #3 }
1783   }
1784 }
1785 }
1786

```

The command `\amc_num_build_integer_scoring:Nnnnn{<tl var>}{<sign bool>}{<prefix>}{<n>}{<decimals>}` builds a scoring to compute an integer from a serie of $\langle n \rangle$ -digits boxes (from which $\langle decimals \rangle$ are for decimals), with name prefix $\langle prefix \rangle$, using a sign variable if $\langle sign bool \rangle$ is true.

```

1787
1788 \cs_new:Npn \amc_num_build_integer_scoring:Nnnnn #1 #2 #3 #4 #5 {
1789   \amc_num_check_score_opts:
1790   \tl_clear:N #1
1791   \int_set_eq:NN \amc_num_digit_int { #4 }
1792   \int_while_do:nNnn \amc_num_digit_int > 0 {
1793     \bool_if:NTF \amc_num_strict_bool {
1794       \AMCmessage{B=requires. #3
1795         \int_to_Alph:n \amc_num_digit_int = 1}
1796     } {
1797       \AMCmessage{B=default. #3
1798         \int_to_Alph:n \amc_num_digit_int =
1799         \bool_if:NTF \amc_num_ignoreblank_bool { } { 0 }
1800       }
1801     }
1802     \int_compare:nNnTF \amc_num_digit_int = #4 { } {
1803       \bool_if:NTF \amc_num_ignoreblank_bool {
1804         \tl_put_right:Nx #1 { ~.~ }
1805         \int_compare:nNnTF \amc_num_digit_int = #5 {
1806           \tl_put_right:Nx #1 { "." ~.~ }
1807         } { }
1808       } {
1809         \tl_put_left:Nn #1 { ( }
1810         \tl_put_right:Nx #1 { ) *
1811         \int_use:N \amc_num_base_int + }
1812       }
1813     }
1814     \tl_put_right:Nx #1
1815     { #3 \int_to_Alph:n \amc_num_digit_int }
1816     \int_decr:N \amc_num_digit_int
1817   }
1818   \bool_if:NTF \amc_num_ignoreblank_bool {
1819     \tl_put_left:Nn #1 { ( 0 + ( }
1820     \tl_put_right:Nn #1 { ) ) }
1821     \int_compare:nNnTF \amc_num_decd_int > 0 {
1822       \tl_put_right:Nx #1 { * ( \int_use:N \amc_num_base_int ** \int_eval:n { #5 } ) }
1823     } { }
1824   } {
1825     \tl_put_left:Nn #1 { ( }
1826     \tl_put_right:Nn #1 { ) }

```

```

1827 }
1828 \bool_if:NTF { #2 } {
1829   \bool_if:NTF \amc_num_strict_bool {
1830     \AMCmessage{B=requires. sign #3 =1}
1831   } {
1832     \AMCmessage{B=default. sign #3 =1}
1833   }
1834   \tl_put_right:Nx #1 { * ( sign #3 ) }
1835 } { }
1836 }
1837

```

Then the command `\AMCnumericShow{<x>}{<options>}` itself:

```

1838
1839 \fp_new:N \amc_num_result_fp
1840 \fp_new:N \amc_num_correct_fp
1841 \clist_new:N \amc_num_digits_clist
1842 \clist_new:N \amc_num_expo_digits_clist
1843 \int_new:N \amc_num_digit_int
1844 \int_new:N \amc_num_sign_int
1845 \int_new:N \amc_num_expo_sign_int
1846 \tl_new:N \amc_num_compute_tl
1847 \tl_new:N \amc_num_expo_tl
1848 \int_new:N \amc_num_correct_expo_int
1849
1850 \cs_new:Npn \amc_numeric_show:nn #1 #2 {

```

We have to tell AMC that the scoring we will give concerns this question:

```

1851 \ifAMC@ensemble\ifAMCformulaire@dedans
1852   \AMCmessage{Q=\the\AMCid@quest}
1853 \fi\fi

```

Then we parse the options from `<opts>`:

```

1854 {\keys_set:nn { amcnumeric } { #2 }

```

if Tvhead is set, we adapt the `AMCncontextVHead` macro

```

1855 \int_compare:nTF {\amc_vheadunitindex_int = 0}
1856 {\int_set:Nn \amc_vheadunitindex_int {\amc_num_decd_int + 1}}
1857 {}
1858
1859 \clist_if_empty:NTF \amc_tvhead_clist
1860 {}
1861 {
1862   \def\AMCncontextVHead##1{
1863     \int_set:Nn \l_tmpa_int
1864     {\int_max:nn
1865      {(##1) - \amc_num_decd_int + \amc_vheadunitindex_int}
1866      {0}}
1867     \emph{\clist_item:Nn \amc_tvhead_clist {\l_tmpa_int}}}}
1868
1869   \bool_if:nTF { \bool_if_p:N\amc_num_significant_bool
1870     && \int_compare_p:n { \amc_num_base_int != 10 } } {
1871     \message{^^J!~AMCnumeric~Error:~significant=true~can't~be~used~with~base!=10.^^J}
1872   } {}
1873   \bool_if:nTF { \int_compare_p:n { \amc_num_expo_int != 0 }

```

```

1874     && \int_compare_p:n { \amc_num_base_int != 10 } } {
1875     \message{^^J!~AMCnumeric~Error:~scientific~notation~can't~be~used~with~base!=10.^^J}
1876 } {}

```

Convert the floating point correct value to integer, taking into account the parameters significant, exponent and decimals:

```

1877 \ifx\@empty#1\@empty
1878   \fp_set:Nn \amc_num_correct_fp { 0 }
1879   \fp_set:Nn \amc_num_mantissa_fp { 0 }
1880   \int_set:Nn \amc_num_correct_expo_int { 0 }
1881 \else
1882 \bool_if:NTF \amc_num_significant_bool {
1883   \amc_fp_n_significant_digits:Nnn \amc_num_correct_fp { #1 } \amc_num_ndigits_int
1884 } {
1885   \int_compare:nNnTF \amc_num_expo_int > 0 {
1886     \amc_fp_decompose:NnN \amc_num_mantissa_fp \amc_num_correct_expo_int { #1 }
1887     \int_compare:nNnTF { \amc_num_ndigits_int - \amc_num_decd_int } > 1 {
1888       \fp_set:Nn \amc_num_mantissa_fp {
1889         \amc_num_mantissa_fp * \amc_num_base_int^( \amc_num_ndigits_int - \amc_num_decd_int - 1 )
1890       }
1891       \int_set:Nn \amc_num_correct_expo_int {
1892         \amc_num_correct_expo_int - ( \amc_num_ndigits_int - \amc_num_decd_int - 1 )
1893       }
1894     } {}
1895     \amc_fp_n_digits:Nnn \amc_num_correct_fp \amc_num_mantissa_fp \amc_num_decd_int
1896   } {
1897     \amc_fp_n_digits:Nnn \amc_num_correct_fp { #1 } \amc_num_decd_int
1898   }
1899 }
1900 \fi

```

Now extracts the required digits:

```

1901 \ifx\@empty#1\@empty
1902   \amc_invalid_digits:Nn \amc_num_digits_clist \amc_num_ndigits_int
1903   \amc_invalid_digits:Nn \amc_num_expo_digits_clist \amc_num_expo_int
1904   \int_set:Nn \amc_num_sign_int { 0 }
1905   \int_set:Nn \amc_num_expo_sign_int { 0 }
1906 \else
1907   \amc_fp_to_digits:Nnnn \amc_num_digits_clist \amc_num_correct_fp
1908   \amc_num_ndigits_int \amc_num_base_int
1909   \amc_get_fp_sign:Nn \amc_num_sign_int \amc_num_correct_fp
1910   \int_compare:nNnTF \amc_num_expo_int > 0 {
1911     \amc_fp_to_digits:Nnnn \amc_num_expo_digits_clist \amc_num_correct_expo_int
1912     \amc_num_expo_int \amc_num_base_int
1913     \amc_get_int_sign:Nn \amc_num_expo_sign_int \amc_num_correct_expo_int
1914   } {}
1915 \fi

```

The question scoring is given to AMC (if requested by the `scoring=true` option). Note that the variable `intV` refers to the correct value, and `intX` to the value entered by the student.

```

1916 \fp_set:Nn \amc_num_result_fp { #1 }
1917 \AMCmessage{B=numval=\fp_to_scientific:N \amc_num_result_fp ,
1918   numex=\int_use:N \amc_num_exact_int,
1919   numapp=\int_use:N \amc_num_approx_int,
1920   numsex=\AMC@numeric@scoreexact,

```



```

1921     num sapp=\AMC@numeric@scoreapprox
1922 }
1923 \bool_if:NTF \amc_num_scoring_bool {
1924   \AMCmessage{B=haut=mz=d=undef,p=undef,
1925     formula=(Vdifference <= \int_use:N \amc_num_exact_int ?
1926     \AMC@numeric@scoreexact :
1927     \int_compare:nNnTF \amc_num_approx_int = 0 {
1928       \AMC@numeric@scorewrong
1929     } {
1930       (Vdifference <= \int_use:N \amc_num_approx_int ?
1931       \AMC@numeric@scoreapprox : \AMC@numeric@scorewrong)
1932     }
1933   )}
1934 } {}
1935 \amc_num_build_integer_scoring:Nnnnn
1936   \amc_num_compute_tl \amc_num_sign_bool { digit } \amc_num_ndigits_int
1937   \amc_num_decd_int
1938   \int_compare:nNnTF \amc_num_expo_int > 0 {
1939     \amc_num_build_integer_scoring:Nnnnn
1940     \amc_num_expo_tl \amc_num_exposign_bool { expo } \amc_num_expo_int { 0 }
1941     \AMCmessage{B= set. intE = \amc_num_expo_tl}
1942   } {}
1943   \AMCmessage{B= set.intV = \fp_to_int:N \amc_num_correct_fp ,
1944     set.intXX = \amc_num_compute_tl }
1945   \int_compare:nNnTF \amc_num_expo_int > 0 {
1946     \AMCmessage{B= set.intX = intXX * \int_use:N \amc_num_base_int ** ( intE - (\int_use:N \amc_num_correc
1947   ){
1948     \AMCmessage{B= set.intX = intXX}
1949   }
1950   \int_compare:nNnTF \amc_num_expo_int > 0 {
1951     \AMCmessage{B= set.valueX = intXX * \int_use:N \amc_num_base_int ** (intE - \int_use:N \amc_num_decd
1952   ){
1953     \AMCmessage{B= set.valueX = intXX * \int_use:N \amc_num_base_int ** (- \int_use:N \amc_num_decd_int))}
1954   }
1955   \ifx\@empty\AMC@numeric@keepas\@empty\else
1956     \AMCmessage{B= setglobal.\AMC@numeric@keepas = valueX}
1957   \fi
1958   \ifx\@empty#1\@empty
1959     \bool_if:NTF \amc_num_significant_bool {
1960       \AMCmessage{B=set.Vdifference=0}
1961     }{
1962       \ifx\@empty\AMC@numeric@alsocorrect\@empty
1963         \AMCmessage{B=set.Vdifference=0}
1964       \else
1965         \AMCmessage{B="set.Vdifference =
1966           amcvdifference( \AMC@numeric@alsocorrect, valueX, \int_use:N \amc_num_decd_int, \int_use:N \amc_r
1967           "}
1968       \fi
1969     }
1970   \else
1971     \bool_if:NTF \amc_num_significant_bool {
1972       \AMCmessage{B=set.Vdifference="min( abs((intV)-(intX)) ,
1973         abs(\int_use:N \amc_num_base_int * (intV) - (intX)) ,

```

```

1974      abs((intV) - \int_use:N\amc_num_base_int * (intX)) )"}
1975  } {
1976    \ifx\@empty\AMC@numeric@alsocorrect\@empty
1977    \AMCmessage{B=set.Vdifference=abs((intV)-(intX))}
1978    \else
1979    \AMCmessage{B="set.Vdifference =
1980      min( amcvdifference( \AMC@numeric@alsocorrect, valueX, \int_use:N\amc_num_decd_int, \int_use:N\am
1981      abs((intV)-(intX)) )"}
1982    \fi
1983  }
1984  \fi

```

Begin now with the frame around all the boxes:

```

1985  \ifAMC@extractOnly\else
1986  \vspace{1.5ex}\par{
1987    \fboxrule=\AMCncol@BorderWidth
1988    \fcolorbox{\AMCncol@Border}{\AMCncol@Background}{
1989      \bool_if:NTF \amc_num_expovertical_bool {
1990        \hbox{\vbox{
1991          \vbox{\amc_num_integer_boxes:NnnNN
1992            \amc_num_digits_clist { digit } \amc_num_decd_int \amc_num_sign_bool
1993            \amc_num_sign_int}
1994          \int_compare:nNnTF \amc_num_expo_int > 0 {
1995            \vspace{\AMCnumeric@Vspace}
1996            \vbox{\hbox{\AMCexponent}}
1997            \vspace{\AMCnumeric@Vspace}
1998            \vbox{\amc_num_integer_boxes:NnnNN
1999              \amc_num_expo_digits_clist { expo } { 0 } \amc_num_exposign_bool
2000              \amc_num_expo_sign_int}
2001            } {}
2002          }}
2003        } {
2004          \amc_num_integer_boxes:NnnNN
2005          \amc_num_digits_clist { digit } \amc_num_decd_int \amc_num_sign_bool
2006          \amc_num_sign_int
2007          \int_compare:nNnTF \amc_num_expo_int > 0 {
2008            \hspace{\AMCnumeric@Hspace}\AMCexponent\hspace{\AMCnumeric@Hspace}
2009            \amc_num_integer_boxes:NnnNN
2010            \amc_num_expo_digits_clist { expo } { 0 } \amc_num_exposign_bool
2011            \amc_num_expo_sign_int
2012          } {}
2013        }
2014      }
2015    }
2016  \fi

```

And tell AMC that we finished with this question:

```

2017  \ifAMC@ensemble\else\vspace{\AMCpostNquest}\par\fi
2018  \ifAMC@ensemble\ifAMCformulaire@dedans
2019    \AMCmessage{FQ}
2020  \fi\fi
2021 }
2022 }
2023

```

```

2024 \cs_new_eq:NN \AMCnumericShow \amc_numeric_show:nn
2025

```

`\AMCnumericHide` is called when the boxes are not to be drawn (in the question sheets for separate answer sheet layout), and `\AMCnumericChoices{⟨value⟩}{⟨options⟩}` is the function to be used in the LaTeX source code of the exam.

```

2026 \cs_new:Npn \amc_numeric_hide:nn #1 #2 {
2027   \keys_set:nn { amcnumeric } { #2 }
2028   \AMCncontextGoto
2029   \ifAMC@qbloc\else\vspace{1.5ex}\par\fi
2030 }
2031
2032 \cs_new_eq:NN \AMCnumericHide \amc_numeric_hide:nn
2033
2034 \ExplSyntaxOff
2035 \def\AMCnumericChoicesPlain{%
2036   \AMC@if@separate@question{\AMC@mem@category{numeric}}{%
2037     \AMCformatChoices{\AMCnumericShow}{\AMCnumericHide}%
2038   }

```

The `{⟨value⟩}` argument is often given as a macro, that is to be expanded before calling `\AMCnumericChoicesPlain`, so that its value will be the same in the separate answer sheet...

```

2039 \ExplSyntaxOn
2040
2041 \cs_new:Npn \amc_numeric_choices:nn #1#2 {
2042   \AMCnumericChoicesPlain{#1}{#2}
2043 }
2044 \cs_generate_variant:Nn \amc_numeric_choices:nn { xn }
2045 \cs_new_eq:NN \AMCnumericChoices \amc_numeric_choices:xn
2046
2047 \ExplSyntaxOff

```

4.13.3 Intervals

`\AMCIntervals` The command `\AMCIntervals{⟨x⟩}{⟨x0⟩}{⟨x1⟩}{⟨delta⟩}` can be used to present answers as intervals $[x_i, x_i + \delta[$ covering $[\langle x0 \rangle, \langle x1 \rangle]$, such that the only interval containing $\langle x \rangle$ is declared as `\correctchoice`, and the other as `\wrongchoice`.

For this command to work, one has to load package `fp`.

As an example,

```

\begin{question}{quarter}
  In which interval falls  $1/4$ ?
  \begin{multicols}{5}
    \begin{choices}[o]
      \AMCIntervals{0.25}{0}{1}{0.1}
    \end{choices}
  \end{multicols}
\end{question}

```

produces (in correction mode):

Question 12 In which interval falls $1/4$?

<input type="checkbox"/> [0, 0.1[<input checked="" type="checkbox"/> [0.2, 0.3[<input type="checkbox"/> [0.4, 0.5[<input type="checkbox"/> [0.6, 0.7[<input type="checkbox"/> [0.8, 0.9[
<input type="checkbox"/> [0.1, 0.2[<input type="checkbox"/> [0.3, 0.4[<input type="checkbox"/> [0.5, 0.6[<input type="checkbox"/> [0.7, 0.8[<input type="checkbox"/> [0.9, 1[

Note that the interval formatting can be changed redefining the `\AMCintervalFormat` command, which is originally defined as

```
2048 \def\AMCintervalFormat#1#2{[#1,\,#2]}
```

to follow local conventions (writting $[a, b]$ instead of $[a, b[$ is for example a common usage).

```
2049 \ExplSyntaxOn
```

```
2050
```

```
2051 \fp_new:N \amc_interv_a
```

```
2052 \fp_new:N \amc_interv_b
```

```
2053 \cs_new:Npn \amc_intervals:nnnn #1 #2 #3 #4 {
```

```
2054   \fp_set:Nn \amc_interv_a { #2 }
```

```
2055   \fp_do_while:nn { \amc_interv_a < #3 } {
```

```
2056     \fp_set:Nn \amc_interv_b { \amc_interv_a + #4 }
```

```
2057     \fp_compare:nTF { \amc_interv_a <= #1 < \amc_interv_b }
```

```
2058       \correctchoice \wrongchoice
```

```
2059       {\AMCintervalFormat{\fp_use:N \amc_interv_a}{\fp_use:N \amc_interv_b}}
```

```
2060       \fp_set:Nn \amc_interv_a \amc_interv_b
```

```
2061   }
```

```
2062 }
```

```
2063 \cs_new_eq:NN \AMCIntervals \amc_intervals:nnnn
```

```
2064
```

```
2065 \ExplSyntaxOff
```

4.14 Open questions

`\AMCOpen` The command `\AMCOpen{<options>}{<choices>}` can be used as a replacement for the `choices` environment when asking the student to write some answer by hand. The teacher will correct and mark this answer either on the paper before scanning, or with manual data capture, thanks to the scoring boxes.

As an example,

```
\begin{question}{Linux}
```

```
  What is the first name of the person who started working on the Linux kernel?
```

```
  \AMCOpen{}{\wrongchoice[w]{w}\scoring{0}\correctchoice[c]{c}\scoring{2}}
```

```
\end{question}
```

shows:

Question 13 What is the first name of the person who started working on the Linux kernel?

☐ w ☐ c

.....

The teacher will have to tick the ‘w’ box for wrong answers, and the ‘c’ box for correct answers.

Begin with the options definitions:

```

2066 \def\AMCotextGoto{}
2067 \def\AMCotextReserved{}
2068 \def\AMCocol@Background{lightgray}
2069 \def\AMCocol@BoxFrameRule{white}
2070 \def\AMCocol@FrameRule{black}
2071 \def\AMCocol@Foreground{}
2072 \def\AMCopen@answer{}
2073 \def\AMCopen@question{}
2074 \def\AMCopen@lineuptext{}
2075 \define@key{AMCOpen}{backgroundcol}{\def\AMCocol@Background{#1}}
2076 \define@key{AMCOpen}{foregroundcol}{\def\AMCocol@Foreground{#1}}
2077 \define@key{AMCOpen}{Treserved}{\def\AMCotextReserved{#1}}
2078 \define@key{AMCOpen}{question}{\AMCid@name}{\def\AMCopen@question{#1}}
2079 \define@key{AMCOpen}{answer}{\def\AMCopen@answer{#1}}
2080 \define@key{AMCOpen}{contentcommand}{AMCopen@lines}{\def\AMCopen@contentcommand{#1}}
2081 \newdimen\AMCopen@Hspace\AMCopen@Hspace=.5em
2082 \define@key{AMCOpen}{hspace}{\AMCopen@Hspace=#1}
2083 \def\AMCopen@Width{.95\linewidth}
2084 \define@key{AMCOpen}{width}{\def\AMCopen@Width{#1}}
2085 \newdimen\AMCopen@LineHeight\AMCopen@LineHeight=1cm
2086 \define@key{AMCOpen}{lineheight}{\AMCopen@LineHeight=#1}
2087 \newcount\AMCopen@Lines\AMCopen@Lines=1
2088 \define@key{AMCOpen}{lines}{\AMCopen@Lines=#1}
2089 \newdimen\AMCopen@boxmargin\AMCopen@boxmargin=3pt
2090 \define@key{AMCOpen}{boxmargin}{\AMCopen@boxmargin=#1}
2091 \newdimen\AMCopen@boxframerule\AMCopen@boxframerule=1pt
2092 \define@key{AMCOpen}{boxframerule}{\AMCopen@boxframerule=#1}
2093 \define@key{AMCOpen}{boxframerulecol}{\def\AMCocol@BoxFrameRule{#1}}
2094 \define@key{AMCOpen}{framerulecol}{\def\AMCocol@FrameRule{#1}}
2095 \newdimen\AMCopen@framerule\AMCopen@framerule=1pt
2096 \define@key{AMCOpen}{framerule}{\AMCopen@framerule=#1}
2097 \define@key{AMCOpen}{lineuptext}{\def\AMCopen@lineuptext{#1}}
2098 \define@boolkey{AMCOpen}{dots}[true]{}
2099 \define@boolkey{AMCOpen}{scan}[true]{}
2100 \define@boolkey{AMCOpen}{retick}[true]{}
2101 \define@boolkey{AMCOpen}{annotate}[false]{}
2102 \define@boolkey{AMCOpen}{lineup}[false]{}
2103 \setkeys{AMCOpen}{dots,scan,retick,annotate,lineup,contentcommand}
2104 \newcommand\AMCopenOpts[1]{\setkeys{AMCOpen}{#1}}

```

The command \AMCOpen is similar to \AMCnumericChoices, calling either \AMCopenShow or \AMCopenHide.

```

2105 \newcommand\AMCopen@lines{%
2106   \begin{minipage}{\AMCopen@Width}%
2107     \loop\vspace{\AMCopen@LineHeight}
2108     \hspace*{.5em}\ifAMC@correc\smash{\AMCopen@answer}\def\AMCopen@answer{}\fi%
2109     \ifKV@AMCopen@dots%
2110       \dotfill\hspace*{.5em}
2111       \fi
2112     \ifnum\AMCopen@Lines>\@ne\par\advance\AMCopen@Lines\m@ne\repeat%
2113   \end{minipage}
2114 }
2115 \newcommand\AMCopenShow[2]{
2116   \ifAMC@ensemble\ifAMC@formulaire@dedans%

```

```

2117 \AMCmessage{Q=\the\AMCid@quest}%
2118 \fi\fi%
2119 {\setkeys{AMCOpen}{#1}%
2120 \ifKV@AMCOpen@lineup%
2121 \ifAMC@ensemble\else%
2122 \ifx\@empty\AMCopen@lineuptext\@empty\fi%
2123 \fi%
2124 \ifAMC@correc\smash{\AMCopen@answer}\fi%
2125 \ifx\@empty\AMCopen@lineuptext\@empty%
2126 \dotfill%
2127 \else%
2128 \AMCopen@lineuptext\hfill%
2129 \fi%
2130 \else%
2131 \hspace*{.5em}\linebreak[1]\hspace*{\fill}%
2132 \fi%
2133 {\AMCnoCompleteMulti%
2134 \def\AMCbeginAnswer{}\def\AMCendAnswer{}%
2135 \def\AMCanswer##1##2{\ifAMC@ensemble ##1\else%
2136 \ifAMC@inside@box ##1\else\AMCboxOutsideLetter{##1}{##2}}\fi\fi%
2137 \hspace{\AMCopen@Hspace}}%
2138 \fboxsep=\AMCopen@boxmargin%
2139 \fboxrule=\AMCopen@boxframerule%
2140 \fcolorbox{\AMCocol@BoxFrameRule}{\AMCocol@Background}{%
2141 \ifAMC@ensemble\AMCopen@question%
2142 \ifx\@empty\AMCopen@question\@empty\else\hspace{\AMCopen@Hspace}\fi%
2143 \fi%
2144 \begin{choicescustom}[o]%
2145 \ifx\AMCocol@Foreground\@empty\@empty\else%
2146 \def\AMC@boxcolor{\AMCocol@Foreground}%
2147 \fi%
2148 #2%
2149 \ifKV@AMCOpen@scan\else\AMCdontScan\fi%
2150 \ifKV@AMCOpen@retick\AMCreTick\fi%
2151 \ifKV@AMCOpen@annotate\else\AMCdontAnnotate\fi%
2152 \end{choicescustom}%
2153 \ifx\@empty\AMCotextReserved\@empty%
2154 \hspace{-\AMCopen@Hspace}%
2155 \else%
2156 \ifx\AMCocol@Foreground\@empty\@empty%
2157 \AMCotextReserved%
2158 \else%
2159 \textcolor{\AMCocol@Foreground}{\AMCotextReserved}%
2160 \fi%
2161 \fi%
2162 }}%
2163 \ifKV@AMCOpen@lineup\else%
2164 \par\nobreak\noindent%
2165 \hspace*{\fill}{%
2166 \fboxrule=\AMCopen@framerule%
2167 \fcolorbox{\AMCocol@FrameRule}{white}{%
2168 \csname\AMCopen@contentcommand\endcsname
2169 }%

```

```

2170     \vspace{\AMCpostQuest}\par%
2171     \fi%
2172 }%
2173 \ifAMC@ensemble\ifAMCformulaire@dedans%
2174 \AMCmessage{FQ}%
2175 \fi\fi%
2176 }
2177 \newcommand\AMCOpenHide[2]{%
2178 \AMCotextGoto%
2179 \ifAMC@qbloc\else\vspace{1.5ex}\par\fi%
2180 }
2181 \def\AMCOpen{%
2182 \AMC@if@separate@question{\AMC@mem@category{open}}%
2183 \AMCformatChoices{\AMCOpenShow}{\AMCOpenHide}%
2184 }

```

4.15 Boxes with letters only

`\AMCBoxOnly` Sometimes the letters printed in the boxes (or just after them) are enough to describe the answers. In such cases, printing the boxes both on the question and on the answer sheet is not necessary. The `\AMCBoxOnly{<options>}{<choices>}` can be used as a replacement for the `choices` environment:

```

\begin{question}{arm}
  Which letter shows the \textit{arm} on the diagram?
  \AMCBoxOnly{ordered=true}{\wrongchoice[A]{}\correctchoice[B]{}%
    \wrongchoice[C]{}\wrongchoice[D]{}%
\end{question}

2185 \def\AMCbotextGoto{}
2186 \def\AMCbo@help{}
2187 \define@key{AMCBoxOnly}{help}{\def\AMCbo@help{#1}}
2188 \define@boolkey{AMCBoxOnly}{ordered}[false]{}
2189 \setkeys{AMCBoxOnly}{ordered}
2190 \newcommand\AMCboOpts[1]{\setkeys{AMCBoxOnly}{#1}}
2191 \newcommand\AMCboShow[2]{%
2192 \ifAMC@ensemble\ifAMCformulaire@dedans%
2193 \AMCmessage{Q=\the\AMCid@quest}%
2194 \fi\fi%
2195 {\setkeys{AMCBoxOnly}{#1}%
2196 \def\AMCbeginAnswer{}\def\AMCendAnswer{}%
2197 \def\AMCanswer##1##2{\hspace{\AMCformHSpace} \ifAMC@ensemble ##1\else%
2198 \ifAMC@inside@box ##1\else\AMCboxOutsideLetter{##1}{##2}\fi\fi%
2199 }%
2200 \ifAMC@ensemble\AMCbo@help\fi%
2201 \ifKV@AMCBoxOnly@ordered%
2202 \begin{choicescustom}[o]%
2203 \else%
2204 \begin{choicescustom}%
2205 \fi%
2206 #2
2207 \end{choicescustom}%
2208 }%

```

```

2209 \ifAMC@ensemble\ifAMCformulaire@dedans%
2210 \AMCmessage{FQ}%
2211 \fi\fi%
2212 }
2213 \newcommand\AMCboHide[2]{
2214 \AMCbotextGoto%
2215 \ifAMC@qbloc\else\vspace{1.5ex}\par\fi%
2216 }
2217 \def\AMCBoxOnly{%
2218 \AMC@if@separate@question{\AMC@mem@category{box}}}%
2219 \AMCformatChoices{\AMCboShow}{\AMCboHide}%
2220 }

```

4.16 Page formatting

4.16.1 Watermark

`\AMCw@termark` These commands are used to print a grey “DRAFT” under each page, so as to prevent from
`\AMCw@terprint` printing old versions of the subject.

```

2221 \DeclareFontShape{OT1}{cmr}{b}{n}{<35->cmr17}{-}
2222 \def\AMC@watertext{\AMC@loc@draft}
2223 \newcommand\AMCw@termark{%
2224 \setlength{\@tempdimb}{.5\paperwidth}%
2225 \setlength{\@tempdimc}{-.5\paperheight}%
2226 \put(\strip@pt\@tempdimb,\strip@pt\@tempdimc){%
2227 \makebox(0,0){\rotatebox{45}{\AMC@LR{%
2228 \textcolor{gray}{0.8}{
2229 \fontencoding{OT1}\fontfamily{cmr}
2230 \fontseries{b}\fontshape{n}
2231 \fontsize{90pt}{120pt}
2232 \selectfont
2233 \AMC@watertext}}}}}
2234 \newcommand\AMCw@terprint[1]{%
2235 \setbox\@tempboxa\vbox to \z@{%
2236 \vbox{%
2237 \hbox to \z@{%
2238 #1\hss}}\vss}
2239 \dp\@tempboxa\z@
2240 \box\@tempboxa}

```

4.16.2 Signs for scan analysis

The following code sets up all the signs to be printed on the pages so as to be able to recognize the position of the boxes on the scans. Four circles ● are printed on the corners (see `\m@rqueCalage`), and binary boxes show the student sheet number (see `\AMCIDBoxesA`), the page (see `\AMCIDBoxesB`) and a checking number (see `\AMCIDBoxesC`).

`\AMC@intituleHead` is the title to be printed at the beginning (used for corrected sheet, and empty on subject). `\AMC@note` is printed at the bottom of each page. You can change its value using `\AMCsetFoot{<foot>}`.

```

2241 \def\AMCccercle#1#2{%
2242 {\setlength{\unitlength}{1mm}%
2243 \begin{picture}(\#1,\#1)(-\#2,-\#2)\thinlines\circle*{\#1}\end{picture}}}

```



```

2244 \def\m@rqueCalage{\AMC@circle{3.6}{1.8}}
2245 \def\m@rque#1{\AMC@tracebox{1}{#1}{\m@rqueCalage}}
2246 \def\he@dtaille#1{% \par cancels the \leavevmode
2247   % introduced by https://github.com/pietvo/fancyhdr/commit/6b1ad10eeb5bc3d804f3cd2cf193e6440d0229e6
2248   \par\vbox to 1cm{#1}}
2249 \def\he@dbas#1{\he@dtaille{\vspace*{\fill}#1}}
2250 \def\he@dhaut#1{\he@dtaille{#1\vspace*{\fill}}}}
2251 \def\AMC@intituleHead{\AMC@loc@corrected}
2252 \def\AMC@note{}
2253 \def\AMCsetFoot#1{\def\AMC@note{#1}}
2254 \newcommand\AMCStudentNumber{\the\AMCid@etud}
2255 \newcommand\AMCIDBoxesA{\AMC@binaryCode{id=1,ndigits=\AMC@NCBetud}{\the\AMCid@etud}}
2256 \newcommand\AMCIDBoxesB{\AMC@binaryCode{id=2,ndigits=\AMC@NCBpage}{\thepage}}
2257 \newcommand\AMCIDBoxesC{\AMC@binaryCode{id=3,ndigits=\AMC@NCBcheck}{\the\AMCid@check}}
2258 \newcommand\AMCIDBoxesABC{%
2259   \hbox{\vbox{\noindent\AMCIDBoxesA\
2260     \noindent\AMCIDBoxesB\AMCIDBoxesC}}}%
2261 }
2262 \AtBeginPage{\ifAMC@pagelayout\global\advance\AMCid@check\m@ne%
2263   \ifnum\AMCid@check<1\global\AMCid@check=\AMCid@checkmax\fi%
2264   \AMC@pagepos%
2265   \ifAMC@watermark\ifAMC@correthead\else\AMCw@terprint{\AMCw@termark}%
2266   \fi\fi\fi}
2267 \fancypagestyle{AMCpageHeadOnly}{%
2268   \fancyhf{} \fancyhead[C]{\textsc{\AMC@intituleHead}}%
2269   \renewcommand{\headrulewidth}{0pt}%
2270   \renewcommand{\footrulewidth}{0pt}%
2271 }
2272 \fancypagestyle{AMCpageFull}{%
2273   \fancyhf{}%
2274   \fancyhead[L]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHG}}}}%
2275   \fancyhead[R]{\AMC@LR{\he@dbas{\leavevmode\m@rque{positionHD}}}}%
2276   \fancyfoot[L]{\AMC@LR{\leavevmode\m@rque{positionBG}}}%
2277   \fancyfoot[R]{\AMC@LR{\leavevmode\m@rque{positionBD}}}%
2278   \fancyhead[C]{\AMC@LR{\he@dhaut{%
2279     \begin{minipage}[b]{\AMC@CBtaille}\AMCboxColor{black}%
2280       \ifAMCids@top\vbox to \AMCids@height{\texttt{+\the\AMCid@etud/\thepage/\the\AMCid@check+}}\fi%
2281       \AMCIDBoxesABC
2282     \end{minipage}%
2283     \ifAMCids@side\hbox to \AMCids@width{\hspace*{\fill}%
2284       \texttt{+\the\AMCid@etud/\thepage/\the\AMCid@check+}}\fi%
2285     }}}%
2286   \fancyhfoffset[EOLR]{5mm}%
2287   \fancyfoot[C]{\AMC@note}%
2288   \renewcommand{\headrulewidth}{0pt}%
2289   \renewcommand{\footrulewidth}{0pt}%
2290 }
2291 \newcommand\AMCsubjectPageTag{%
2292   \fbox{\texttt{\the\AMCid@etud:\thepage}}%
2293 }
2294 \fancypagestyle{AMCpageNoMarks}{%
2295   \fancyhf{}%
2296   \fancyhead[R]{\AMCsubjectPageTag}%

```

```

2297 \fancyfoot[C]{\AMC@note}%
2298 \renewcommand{\headrulewidth}{0pt}%
2299 \renewcommand{\footrulewidth}{0pt}%
2300 }
2301 \fancypagestyle{AMCpageEmpty}{%
2302 \fancyhf{}%
2303 \renewcommand{\headrulewidth}{0pt}%
2304 \renewcommand{\footrulewidth}{0pt}%
2305 }
2306 \AtBeginDocument{%
2307 \ifAMC@pagelayout%
2308 \ifAMC@correthead
2309 \pagestyle{AMCpageHeadOnly}
2310 \else
2311 \pagestyle{AMCpageFull}
2312 \fi
2313 \fi
2314 }

```

4.17 Defining a single exam copy content

`\onecopy` The command `\onecopy[$\langle n \rangle$]{ $\langle code \rangle$ }` generates $\langle n \rangle$ copies of the subject that is described in $\langle code \rangle$. The L^AT_EX code $\langle code \rangle$ that generates a single copy can be a little long, so that the environment `examcopy` is often preferred.

```

2315 \newcommand{\onecopy}[2]{%
2316 \ifx\AMCNombreCopies\undefined\AMCnum@copies=#1%
2317 \else\AMCnum@copies=\AMCNombreCopies\fi%
2318 \AMCmessage{TOTAL=\the\AMCnum@copies}%
2319 \message{^^JAMC: copies: total=\the\AMCnum@copies^^J}%
2320 \AMCid@etud=\AMCid@etudstart%
2321 \ifnum\AMCid@etud=0\AMCid@etud=\AMC@premierecopie\fi%
2322 \AMCid@etudfin=\AMCnum@copies%
2323 \advance\AMCid@etudfin\AMCid@etud\relax%
2324 \ifAMC@correthead\AMCid@etudfin=\AMC@premierecopie%
2325 \message{^^JAMC: copies: total=1^^J}%
2326 \fi
2327 \ifAMC@pdfform\begin{Form}\fi%
2328 \loop{%
2329 \ifAMC@calibration\protected@write\AMC@XYFILE{}{%
2330 \string\rngstate{\the\AMCid@etud}{\the\AMC@SR}%
2331 }\fi%
2332 \AMC@zoneformulairefalse\setcounter{page}{1}\setcounter{section}{0}%
2333 \ifAMC@ensemble\ifAMC@automarks\pagestyle{AMCpageNoMarks}\fi\fi%
2334 \AMCnumero{1}%
2335 \ifAMC@calibration\AMCmessage{ETU=\the\AMCid@etud}\fi%
2336 \AMC@multiclear%
2337 \global\AMC@keepmemoryfalse%
2338 #2%
2339 \ifAMC@keepmemory\else\AMC@mem@clear\fi%
2340 \clearpage}%
2341 \message{^^JAMC: copies: add=1^^J}%
2342 \advance\AMCid@etud\@ne\ifnum\AMCid@etud<\AMCid@etudfin\repeat%
2343 \global\AMCid@etudstart=\AMCid@etud%

```

```

2344 \ifAMC@pdfform\end{Form}\fi%
2345 \AMC@multi@report%
2346 }

```

\AMCaddpagesto In some situations, one needs all question sheets to have the same number of pages. The command **\AMCaddpagesto{<n>}** adds enough (white) pages to get at least <n> pages in the current question sheet.

```

2347 \newcount\AMC@addpages
2348 \newcommand{\AMCaddpagesto}[1]{%
2349   \AMC@addpages=#1\advance\AMC@addpages\@ne%
2350   \clearpage%
2351   \@whilenum\thepage<\AMC@addpages\do{%
2352     \ifAMC@automarks\pagestyle{AMCpageEmpty}\fi%
2353     \hbox{}\clearpage%
2354   }%
2355 }

```

\AMCcleardoublepage If you want to print the subject all at one time in duplex mode, it is necessary to end each subject with an even number of pages. This can be achieved using **\AMCcleardoublepage** at the end of the copy definition. This command is also useful inserted before the separate answer sheet (if any).

```

2356 \def\AMCcleardoublepage{%
2357   \clearpage%
2358   \ifodd\thepage\else%
2359     \ifAMC@automarks\pagestyle{AMCpageEmpty}\fi%
2360     \hbox{}\clearpage%
2361   \fi%
2362 }

```

\exemplairepair To make some differences in the copies, checking if the student sheet number is odd, with **\exemplairepair** construct, can be useful.

```

2363 \def\exemplairepair{\ifodd\AMCid@etud}

```

\AMClabel Commands **\AMClabel**, **\AMCref** and **\AMCpageref** replaces L^AT_EX's **\label**, **\ref** and **\pageref** **\AMCref** to be able to use different labels for different sheets.

```

\AMCref
2364 \newcommand\AMCstudentlabel[1]{\the\AMCid@etud-#1}
2365 \def\AMClabel#1{\expandafter\label{\AMCstudentlabel{#1}}}
2366 \def\AMCref#1{\expandafter\ref{\AMCstudentlabel{#1}}}
2367 \def\AMCpageref#1{\expandafter\pageref{\AMCstudentlabel{#1}}}

```

\AMCqlabel A label can be created for current question with **\AMCqlabel{<label>}**. This label can be used with **\AMCref** and **\AMCpageref**. This command is defined for backward compatibility only, since **\AMClabel** can also be used.

```

2368 \newcommand{\AMCqlabel}[1]{%
2369   \AMClabel{#1}%
2370 }

```

4.18 Pre-association

\AMCassociation Association between sheets and students can be made before the exam with the **\AMCassociation[<filename>]{<id>}** command. The optional argument <filename> will be used when printing student sheets to files.

```

2371 \newcommand{\AMCassociation}[2][]{%
2372   \ifAMC@calibration%
2373   \immediate\write\AMC@XYFILE{\string\association{\the\AMCid@etud}{#2}{#1}}%
2374   \fi%
2375 }

```

AMCstudentslistfile You can also pass AMC the path to the CSV file with students, and the unique key that can be used, with `\AMCstudentslistfile{<path>}{<key>}`.

```

2376 \newcommand{\AMCstudentslistfile}[2]{%
2377   \ifAMC@calibration%
2378   \immediate\write\AMC@XYFILE{\string\with{studentslistfile=#1}}%
2379   \immediate\write\AMC@XYFILE{\string\with{studentslistkey=#2}}%
2380   \fi%
2381 }

```

4.19 Package options

See section 3.1 for the options descriptions.

```

2382 \def\AMC@lang@code{}
2383 \DeclareOptionX{noshuffle}{\AMC@ordretrue}
2384 \DeclareOptionX{noshufflegroups}{\AMC@shuffleGfalse}
2385 \DeclareOptionX{fullgroups}{\AMC@fullGroupstrue}
2386 \DeclareOptionX{answers}{\AMC@corretheadtrue\AMC@correcttrue}
2387 \DeclareOptionX{indivanswers}{\AMC@correcttrue}
2388 \DeclareOptionX{textpos}{\AMC@textPostrue}
2389 \DeclareOptionX{extractonly}{\AMC@extractOnlytrue\AMC@textPostrue\AMC@boxStyle{shape=none}\AMC@boxedAnswer}
2390 \DeclareOptionX{box}{\AMC@qbloctrue}
2391 \DeclareOptionX{asbox}{\AMC@asqbloctrue}
2392 \DeclareOptionX{separateanswersheet}{\AMC@ensembletrue}
2393 \DeclareOptionX{digits}{\AMC@inside@digittrue}
2394 \DeclareOptionX{ordre}{\AMC@ordretrue}
2395 \DeclareOptionX{correc}{\AMC@corretheadtrue\AMC@correcttrue}
2396 \DeclareOptionX{modele}{\AMC@corretheadtrue\AMC@correcfalse\AMC@ordretrue}
2397 \DeclareOptionX{correcindiv}{\AMC@correcttrue}
2398 \DeclareOptionX{init}{\AMC@SR@time}
2399 \DeclareOptionX{bloc}{\AMC@qbloctrue}
2400 \DeclareOptionX{completemulti}{\AMC@complete@multitrue}
2401 \DeclareOptionX{insidebox}{\AMC@inside@boxtrue}
2402 \DeclareOptionX{ensemble}{\AMC@ensembletrue}
2403 \DeclareOptionX{chiffres}{\AMC@inside@digittrue}
2404 \DeclareOptionX{outsidebox}{\AMC@outside@boxtrue}
2405 \DeclareOptionX{calibration}{\AMC@calibrationtrue}
2406 \DeclareOptionX{nowatermark}{\AMC@watermarkfalse}
2407 \newcommand\AMC@catalogMode{%
2408   \AMC@catalogtrue%
2409   \AMC@watermarkfalse\AMC@corretheadtrue%
2410   \AMC@correcttrue\AMC@ordretrue\AMC@shuffleGfalse%
2411   \AMC@fullGroupstrue%
2412   \def\AMC@intituleHead{\AMC@loc@catalog}\AMC@affichekeystrue}
2413 \newcommand\AMC@keys@next{\AMC@keyslinefalse}
2414 \newcommand\AMC@keys@line{\AMC@keyslinetrue}
2415 \DeclareOptionX{catalog}{\AMC@catalogMode}
2416 \DeclareOptionX{keys}[next]{\csname AMC@keys@#1\endcsname{}}

```

```

2417 \DeclareOptionX{francais}{\def\AMC@lang@code{FR}\AMC@loc@FR}
2418 \DeclareOptionX{lang}{\def\AMC@lang@code{#1}\csname AMC@loc@#1\endcsname}
2419 \DeclareOptionX{versionA}{%
2420   \def\AMCid@checkmax{31}\def\AMC@NCBetud{9}\def\AMC@NCBpage{4}%
2421   \def\AMC@NCBcheck{5}\setlength{\AMC@CBtaille}{4cm}%
2422   \def\AMC@premierecopie{100}}
2423 \DeclareOptionX{plain}{\AMC@plaintrue}
2424 \DeclareOptionX{nopage}{\AMC@pagelayoutfalse}
2425 \DeclareOptionX{postcorrect}{\AMC@postcorrecttrue}
2426 \DeclareOptionX{automarks}{\AMC@automarkstrue}
2427 \newif\ifAMCneeds@storebox\AMCneeds@storeboxfalse
2428 \DeclareOptionX{storebox}{\AMCneeds@storeboxtrue}
2429 \DeclareOptionX{pdfform}{\AMC@pdfformtrue}
2430 \DeclareOptionX{codedigit}{\AMCcodeID@{#1}}
2431 \newif\ifAMC@survey\AMC@surveyfalse
2432 \DeclareOptionX{survey}{\AMC@surveytrue}
2433 \ProcessOptionsX
2434 \ifAMCneeds@storebox
2435   \RequirePackage{storebox}\AtBeginDocument{{}}%
2436 \fi
2437 \ifAMC@pdfform
2438   \AMCmessage{VAR:project:pdfform=1}%
2439   \AMCboxStyle{shape=form}%
2440   \RequirePackage[pageanchor=false]{hyperref}%
2441 \else%
2442   \AMCmessage{VAR:project:pdfform=0}%
2443 \fi
2444 \AtBeginDocument{%
2445   \ifAMCneeds@storebox%
2446     \let\AMC@new@savebox=\newstorebox%
2447     \let\AMC@save@box=\storebox%
2448     \let\AMC@use@box=\usestorebox%
2449   \fi%
2450   \AMC@new@savebox{\AMC@ovalbox@R}%
2451   \AMC@new@savebox{\AMC@ovalbox@RF}%
2452   \AMC@new@savebox{\AMC@ovalbox@}%
2453   \AMC@new@savebox{\AMC@ovalbox@F}%
2454   \AMC@shapeprepare%
2455 }

```

4.20 Survey add-on

Some code and *tikz* settings to help handling surveys, see https://survey.codes/pdf/surveyamc_manual.pdf for more details. This survey add-on is originally written by Claudia Saalbach.

```

questionnaires (env.)
  auto (env.) 2456 \ifAMC@survey
question-auto (env.) 2457 \NewEnviron{Questionnaires}[1]{
  values (env.) 2458 \onecopy{#1}{
  values-auto (env.) 2459 \BODY
variable-auto (env.) 2460 }
  \answer 2461 }

```

```

2462 \NewEnviron{auto}[1]{
2463 \csvreader[head to column names, separator=tab]{#1}{}{
2464 \BODY
2465 }
2466 }
2467 \NewEnviron{question-auto}[3]{
2468 \csvreader[head to column names, separator=tab]{#1}{}{
2469 \ifcsvstrcmp{#2}{#3}{\BODY \\\}{}
2470 }
2471 }
2472 \newenvironment{values}{}{}
2473 \NewEnviron{values-auto}[5]{
2474 \csvreader[head to column names, separator=tab]{#1}{}{
2475 \ifcsvstrcmp{#2}{#3}{
2476 \ifcsvstrcmp{#4}{#5}{\BODY \\\
2477 }{}
2478 }{}
2479 }
2480 }
2481 \NewEnviron{variable-auto}[3]{
2482 \foreach \x in {#3}{
2483 \csvreader[head to column names, separator=tab]{#1}{}{
2484 \ifcsvstrcmp{#2}{\x}{\BODY}{}
2485 }
2486 }
2487 }
2488 \newcommand{\answer}[5][\global\advance\AMCrep@count\@ne\relax%
2489 \ifAMC@calibration\AMCmessage{REP=\the\AMCrep@count:B}\fi%
2490 \global\AMCune@bonnettrue%
2491 \AMCload@reponse{\une@rep{\ifAMC@correc\AMC@box{#1}{\AMC@checkbox}%
2492 \else\AMC@box{#1}{\fi}{#2}{#3}{#4}{#5}}{\the\AMCrep@count}\ignorespaces}
2493 \RequirePackage{tikz}
2494 \usetikzlibrary{positioning, shapes, arrows, tikzmark, decorations.pathreplacing}
2495 \tikzset{
2496 checkbox-sc/.style={
2497 right=of lab\thecsvrow
2498 },
2499 vallab-sc/.style={
2500 text width=4cm,
2501 align=left,
2502 },
2503 checkbox-mc/.style={
2504 },
2505 vallab-mc/.style={
2506 above=of box\thecsvrow,
2507 text width=1.4cm,
2508 align=center,
2509 },
2510 varlab-mc/.style={
2511 text width=4cm,
2512 align=left,
2513 },
2514 node distance= 0mm,

```

```

2515 }
2516 \fi

```

4.21 Package Errors

`\AMC@error@explain` Error to display if `\explain` command is used outside question like environments

```

2517 \def\AMC@error@explain{\PackageError{automultiplechoice}{
2518     Command \protect\explain\space can only be used inside\MessageBreak question like environments}{Some
2519 }}

```

4.22 Optional features

This package tries to see if optional packages `environ` and `etex` are loadable, and load them if possible. This behaviour can be cancelled by using `plain` option.

```

2520 \ifAMC@plain
2521 \else
2522   \IfFileExists{environ.sty}{\RequirePackage{environ}}{}
2523   \ifx\TeXversion\@undefined
2524   \else
2525     \RequirePackage{etex}
2526   \fi
2527 \fi

```

`examcopy` (*env.*) Then, if `environ` package is loaded and defines command `\NewEnviron`, environment `examcopy` is defined.

Environment `{examcopy}[\langle n \rangle]` does the same as command `onecopy`: it encloses L^AT_EX code which makes *one* exam copy. Optional argument $\langle n \rangle$ gives the number of desired copies – this can also be modified redefinig `\AMCNombreCopies`.

```

2528 \@ifpackageloaded{environ}{%
2529   \ifx\NewEnviron\undefined\PackageWarning{automultiplechoice}%
2530   {Package environ loaded but too old version:
2531     environnement examcopy/copieexamen will NOT be defined.}%
2532   \else\NewEnviron{examcopy}[1][5]{\onecopy{#1}{\BODY}}\fi}%
2533 {\PackageWarning{automultiplechoice}%
2534   {Package environ not loaded: environnement
2535     examcopy/copieexamen will NOT be defined.}}

```

4.23 Use with recent LuaTeX versions

In recent LuaTeX versions, the commands `pdfsavepos`, `pdflastxpos` and `pdflastypos` has been renamed, stripping the `pdf` part. The following code tries to detect this situation and make the bindings between the old and new command names.

```

2536 \ExplSyntaxOn
2537
2538 \cs_if_exist:NTF \pdfsavepos { } {
2539   \cs_if_exist:NTF \savepos { \cs_new_eq:NN \pdfsavepos \savepos } { }
2540 }
2541 \cs_if_exist:NTF \pdflastxpos { } {
2542   \cs_if_exist:NTF \lastxpos { \cs_new_eq:NN \pdflastxpos \lastxpos } { }
2543 }
2544 \cs_if_exist:NTF \pdflastypos { } {

```

```

2545 \cs_if_exist:NTF \lastypos { \cs_new_eq:NN \pdflastypos \lastypos } { }
2546 }

```

In some situations, the *page* dimensions are different from the *paper* dimensions. This must be taken into account when computing coordinates.

```

2547
2548 \cs_if_exist:NTF \pdfpagewidth { } {
2549 \cs_new_eq:NN \pdfpagewidth \paperwidth
2550 }
2551 \cs_if_exist:NTF \pdfpageheight { } {
2552 \cs_new_eq:NN \pdfpageheight \paperheight
2553 }
2554
2555 \ExplSyntaxOff

```

4.24 External control

Some of the package options can be controlled defining `\xxxExterne` commands. For example, the following command will format the subject document, whatever options are used in the L^AT_EX file:

```

\pdfatex '\nonstopmode\def\SujetExterne{1}\def\NoWatermarkExterne{1}\input{mcq.tex}'
\ifx\SujetExterne\undefined\else
\message{***SUJET***^^J}
\AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse
\fi
\ifx\ScoringExterne\undefined\else
\message{***SCORING***^^J}
\AMC@calibrationtrue\AMC@correcfalse\AMC@corretheadfalse\AMC@watermarkfalse\AMC@invisibletrue
\fi
\ifx\CorrigeExterne\undefined\else
\message{***CORRIGE***^^J}
\AMC@calibrationfalse\AMC@corretheadtrue\AMC@correcttrue\AMC@watermarkfalse
\fi
\ifx\CorrigeIndivExterne\undefined\else
\message{***CORRIGE***^^J}
\AMC@calibrationfalse\AMC@corretheadfalse\AMC@correcttrue\AMC@watermarkfalse
\fi
\ifx\CatalogExterne\undefined\else
\message{***CATALOG***^^J}
\AMC@catalogMode
\fi
\ifx\NoWatermarkExterne\undefined\else
\AMC@watermarkfalse
\fi
\ifx\codeDigitExterne\undefined\else
\AMCcodeID@@{\codeDigitExterne}
\fi

```

4.25 Page layout

The following code sets the correct page layout to have room for signs for scan analysis, and prepares watermark printing:


```

2582 \@ifpackageloaded{geometry}{\usepackage{geometry}}
2583 \ifAMC@pagelayout
2584   \ifAMC@correthead
2585     \geometry{hmargin=3cm,vmargin={1cm,1cm},includeheadfoot,headheight=1cm,footskip=1cm}
2586   \else
2587     \geometry{hmargin=3cm,headheight=2cm,headsep=.3cm,footskip=1cm,top=3.5cm,bottom=2.5cm}
2588   \fi
2589   \ifAMC@watermark
2590     \ifAMC@correthead\else
2591       \def\AMC@note{\begin{minipage}{0.65\linewidth}
2592         \AMC@LR{\textcolor{blue}{\AMC@loc@message}}
2593       \end{minipage}}
2594     }
2595   \fi
2596 \fi
2597 \fi

```

4.26 Initialisation

Initialisation of the check counter:

```
2598 \AMCid@check=\AMCid@checkmax\advance\AMCid@check\@ne
```

Telling outside if separate answer sheet, and boxes labelling, are requested:

```

2599 \ifAMC@ensemble\AMCmessage{VAR:ensemble=1}\fi
2600 \ifAMC@inside@box\AMCmessage{VAR:insidebox=1}\fi
2601 \ifAMC@outside@box\AMCmessage{VAR:outsidebox=1}\fi
2602 \ifAMC@postcorrect\AMCmessage{VAR:postcorrect=1}\fi

```

Preparing writing to .xy file :

```

2603 \ifAMC@calibration
2604 \newwrite\AMC@XYFILE%
2605 \immediate\openout\AMC@XYFILE\jobname.xy%
2606 \immediate\write\AMC@XYFILE{\string\version{\AMC@VERSION}}
2607 \immediate\write\AMC@XYFILE{\string\with{codedigit=\AMCcodeID@mode}}
2608 \immediate\write\AMC@XYFILE{\string\with{version=\AMC@VERSION}}
2609 \immediate\write\AMC@XYFILE{\string\with{ensemble=\ifAMC@ensemble yes\else no\fi}}
2610 \immediate\write\AMC@XYFILE{\string\with{insidebox=\ifAMC@inside@box yes\else no\fi}}
2611 \immediate\write\AMC@XYFILE{\string\with{outsidebox=\ifAMC@outside@box yes\else no\fi}}
2612 \immediate\write\AMC@XYFILE{\string\with{postcorrect=\ifAMC@postcorrect yes\else no\fi}}
2613 \immediate\write\AMC@XYFILE{\string\with{extractonly=\ifAMC@extractOnly yes\else no\fi}}
2614 \immediate\write\AMC@XYFILE{\string\with{lang=\AMC@lang@code}}
2615 \ifx\AMCNombreCopies\undefined%
2616 \immediate\write\AMC@XYFILE{\string\with{ncopies=default}}}%
2617 \else%
2618 \immediate\write\AMC@XYFILE{\string\with{ncopies=\AMCNombreCopies}}}%
2619 \fi%
2620 \fi

```

4.27 French command names

For backward compatibility, a lot of commands have their french counterpart:

```

2621 \let\reponses=\choices\let\endreponses=\endchoices
2622 \let\reponseshoriz=\choiceshoriz\let\endreponseshoriz=\endchoiceshoriz

```

```

2623 \let\reponsesperso=\choicescustom\let\endreponsesperso=\endchoicescustom
2624 \let\bonne=\correctchoice
2625 \let\mauvaise=\wrongchoice
2626 \let\bareme=\scoring
2627 \let\baremeDefaultM=\scoringDefaultM
2628 \let\baremeDefaultS=\scoringDefaultS
2629 \def\exemplaire{\AMC@loc@FR\onecopy}
2630 \@ifpackageloaded{environ}{%
2631   \let\copieexamen=\examcopy\let\endcopieexamen=\endexamcopy}{%
2632   \let\melangegroupe=\shufflegroup
2633   \let\restituegroupe=\insertgroup
2634   \let\alafin=\lastchoices
2635   \let\formulaire=\AMCform
2636   \let\AMCdebutFormulaire=\AMCformBegin
2637   \let\champnom=\namefield
2638   \let\choixIntervalles=\AMCIntervals

```

5 Outputs

In the .xy file, 0/⟨*n*⟩ means student sheet number 0 (there is only one “student sheet” numbered 0 for this document as we did not use \onecopy) and page number ⟨*n*⟩ inside this student sheet. Then, each instance of the \tracepos command shows *x* and *y* positions as arguments #2 and #3 (unit is sp, such that $65536 \times 72.27 \text{ sp}$ is one inch). One has to take min and max of the *x*-values to determine the left and right position of the box, and min and max values of *y*-values to determine top and bottom position of the box.

5.1 namefield command

Lines in the .xy file from a \namefield command:

```

\tracepos{0/34: __zone: id: __n}{0sp}{25231091sp}{square}
\tracepos{0/34: __zone: id: __n}{5873801sp}{0sp}{square}
\tracepos{0/34: __zone: id: __n}{15861297sp}{0sp}{square}
\tracepos{0/34: __zone: id: __n}{0sp}{22245913sp}{square}

```

5.2 AMCboxedchar command

Lines in the .xy file from a \AMCboxedchar command:

```

\tracepos{0/35: test}{22855914sp}{48672399sp}{square}
\tracepos{0/35: test}{23561334sp}{47966979sp}{square}

```

5.3 AMCcode command

Lines in the .xy file from a \AMCcode command. Here, code[⟨*n*⟩]:⟨*q*⟩,⟨*v*⟩ relates to digit number ⟨*n*⟩ from the right (⟨*n*⟩=1 for units, ⟨*n*⟩=2 for tens, ⟨*n*⟩=3 for hundreds and so on), question number ⟨*q*⟩ (\AMCcode uses a fake question; this number can be ignored), and value ⟨*v*⟩-1 (box number ⟨*v*⟩ for the digit).

```

\tracepos{0/58: case: code[5]: 16, 1}{24875504sp}{43399484sp}{square}
\tracepos{0/58: case: code[5]: 16, 1}{25580924sp}{42694064sp}{square}

```

```

\boxchar{0/58:case:code[5]:16,1}{A}
\tracepos{0/58:case:code[5]:16,2}{24875504sp}{42285372sp}{square}
\tracepos{0/58:case:code[5]:16,2}{25580924sp}{41579952sp}{square}
\boxchar{0/58:case:code[5]:16,2}{B}
\tracepos{0/58:case:code[5]:16,3}{24875504sp}{41171260sp}{square}
\tracepos{0/58:case:code[5]:16,3}{25580924sp}{40465840sp}{square}
\boxchar{0/58:case:code[5]:16,3}{C}
\tracepos{0/58:case:code[5]:16,4}{24875504sp}{40057148sp}{square}
\tracepos{0/58:case:code[5]:16,4}{25580924sp}{39351728sp}{square}
\boxchar{0/58:case:code[5]:16,4}{D}
\tracepos{0/58:case:code[4]:17,1}{26540303sp}{45627708sp}{square}
\tracepos{0/58:case:code[4]:17,1}{27245723sp}{44922288sp}{square}
\boxchar{0/58:case:code[4]:17,1}{0}
\tracepos{0/58:case:code[4]:17,2}{26540303sp}{44513596sp}{square}
\tracepos{0/58:case:code[4]:17,2}{27245723sp}{43808176sp}{square}
\boxchar{0/58:case:code[4]:17,2}{1}
\tracepos{0/58:case:code[4]:17,3}{26540303sp}{43399484sp}{square}
\tracepos{0/58:case:code[4]:17,3}{27245723sp}{42694064sp}{square}
\boxchar{0/58:case:code[4]:17,3}{2}
\tracepos{0/58:case:code[4]:17,4}{26540303sp}{42285372sp}{square}
\tracepos{0/58:case:code[4]:17,4}{27245723sp}{41579952sp}{square}
\boxchar{0/58:case:code[4]:17,4}{3}
\tracepos{0/58:case:code[4]:17,5}{26540303sp}{41171260sp}{square}
\tracepos{0/58:case:code[4]:17,5}{27245723sp}{40465840sp}{square}
\boxchar{0/58:case:code[4]:17,5}{4}
\tracepos{0/58:case:code[4]:17,6}{26540303sp}{40057148sp}{square}
\tracepos{0/58:case:code[4]:17,6}{27245723sp}{39351728sp}{square}
\boxchar{0/58:case:code[4]:17,6}{5}
\tracepos{0/58:case:code[3]:18,1}{28032160sp}{45627708sp}{square}
\tracepos{0/58:case:code[3]:18,1}{28737580sp}{44922288sp}{square}
\boxchar{0/58:case:code[3]:18,1}{0}
\tracepos{0/58:case:code[3]:18,2}{28032160sp}{44513596sp}{square}
\tracepos{0/58:case:code[3]:18,2}{28737580sp}{43808176sp}{square}
\boxchar{0/58:case:code[3]:18,2}{1}
\tracepos{0/58:case:code[3]:18,3}{28032160sp}{43399484sp}{square}
\tracepos{0/58:case:code[3]:18,3}{28737580sp}{42694064sp}{square}
\boxchar{0/58:case:code[3]:18,3}{2}
\tracepos{0/58:case:code[3]:18,4}{28032160sp}{42285372sp}{square}
\tracepos{0/58:case:code[3]:18,4}{28737580sp}{41579952sp}{square}
\boxchar{0/58:case:code[3]:18,4}{3}
\tracepos{0/58:case:code[3]:18,5}{28032160sp}{41171260sp}{square}
\tracepos{0/58:case:code[3]:18,5}{28737580sp}{40465840sp}{square}
\boxchar{0/58:case:code[3]:18,5}{4}
\tracepos{0/58:case:code[3]:18,6}{28032160sp}{40057148sp}{square}
\tracepos{0/58:case:code[3]:18,6}{28737580sp}{39351728sp}{square}
\boxchar{0/58:case:code[3]:18,6}{5}
\tracepos{0/58:case:code[2]:19,1}{29524017sp}{45627708sp}{square}
\tracepos{0/58:case:code[2]:19,1}{30229437sp}{44922288sp}{square}
\boxchar{0/58:case:code[2]:19,1}{0}

```

```

\tracepos{0/58:case:code[2]:19,2}{29524017sp}{44513596sp}{square}
\tracepos{0/58:case:code[2]:19,2}{30229437sp}{43808176sp}{square}
\boxchar{0/58:case:code[2]:19,2}{1}
\tracepos{0/58:case:code[2]:19,3}{29524017sp}{43399484sp}{square}
\tracepos{0/58:case:code[2]:19,3}{30229437sp}{42694064sp}{square}
\boxchar{0/58:case:code[2]:19,3}{2}
\tracepos{0/58:case:code[2]:19,4}{29524017sp}{42285372sp}{square}
\tracepos{0/58:case:code[2]:19,4}{30229437sp}{41579952sp}{square}
\boxchar{0/58:case:code[2]:19,4}{3}
\tracepos{0/58:case:code[2]:19,5}{29524017sp}{41171260sp}{square}
\tracepos{0/58:case:code[2]:19,5}{30229437sp}{40465840sp}{square}
\boxchar{0/58:case:code[2]:19,5}{4}
\tracepos{0/58:case:code[2]:19,6}{29524017sp}{40057148sp}{square}
\tracepos{0/58:case:code[2]:19,6}{30229437sp}{39351728sp}{square}
\boxchar{0/58:case:code[2]:19,6}{5}
\tracepos{0/58:case:code[1]:20,1}{31015874sp}{45627708sp}{square}
\tracepos{0/58:case:code[1]:20,1}{31721294sp}{44922288sp}{square}
\boxchar{0/58:case:code[1]:20,1}{0}
\tracepos{0/58:case:code[1]:20,2}{31015874sp}{44513596sp}{square}
\tracepos{0/58:case:code[1]:20,2}{31721294sp}{43808176sp}{square}
\boxchar{0/58:case:code[1]:20,2}{1}
\tracepos{0/58:case:code[1]:20,3}{31015874sp}{43399484sp}{square}
\tracepos{0/58:case:code[1]:20,3}{31721294sp}{42694064sp}{square}
\boxchar{0/58:case:code[1]:20,3}{2}
\tracepos{0/58:case:code[1]:20,4}{31015874sp}{42285372sp}{square}
\tracepos{0/58:case:code[1]:20,4}{31721294sp}{41579952sp}{square}
\boxchar{0/58:case:code[1]:20,4}{3}
\tracepos{0/58:case:code[1]:20,5}{31015874sp}{41171260sp}{square}
\tracepos{0/58:case:code[1]:20,5}{31721294sp}{40465840sp}{square}
\boxchar{0/58:case:code[1]:20,5}{4}
\tracepos{0/58:case:code[1]:20,6}{31015874sp}{40057148sp}{square}
\tracepos{0/58:case:code[1]:20,6}{31721294sp}{39351728sp}{square}
\boxchar{0/58:case:code[1]:20,6}{5}

```

type	English	French
command	<code>\namefield</code>	<code>\champnom</code>
environment	<code>choices</code>	<code>reponses</code>
environment	<code>choiceshoriz</code>	<code>reponseshoriz</code>
environment	<code>choicescustom</code>	<code>reponsesperso</code>
command	<code>\correctchoice</code>	<code>\bonne</code>
command	<code>\wrongchoice</code>	<code>\mauvaise</code>
command	<code>\lastchoices</code>	<code>\alafin</code>
command	<code>\AMCIntervals</code>	<code>\choixIntervalles</code>
command	<code>\scoring</code>	<code>\bareme</code>
command	<code>\scoringDefaultM</code>	<code>\baremeDefautM</code>
command	<code>\scoringDefaultS</code>	<code>\baremeDefautS</code>
command	<code>\onecopy</code>	<code>\exemplaire</code>
environment	<code>examcopy</code>	<code>copieexamen</code>
command	<code>\shufflegroup</code>	<code>\melangegroupe</code>
command	<code>\insertgroup</code>	<code>\restituegroupe</code>
command	<code>\AMCform</code>	<code>\formulaire</code>
command	<code>\AMCformBegin</code>	<code>\AMCdebutFormulaire</code>
option	<code>noshuffle</code>	<code>ordre</code>
option	<code>answers</code>	<code>correc</code>
option	<code>indivanswers</code>	<code>correcindiv</code>
option	<code>box</code>	<code>bloc</code>
option	<code>separateanswersheet</code>	<code>ensemble</code>
option	<code>digits</code>	<code>chiffres</code>

Table 1: French equivalent commands

Contents

1	Introduction	1
2	Samples	1
2.1	Standard layout	4
2.2	Separate answer sheet	5
2.3	Without markers	6
3	Usage	10
3.1	Package options	10
3.2	Questions and answers	11
3.3	Scoring	13
3.4	Groups of questions	14
3.5	Students identification	15
3.6	Separate answer sheet	16
3.7	Random computation questions	17
3.8	French command names	20
3.9	Customisation	21
3.9.1	Boxes	21
3.9.2	Codes	21
3.9.3	Answers	22
4	Implementation	22
4.1	Variables	23
4.2	Dimensions	25
4.3	Human readable sheet ID position	26
4.4	Localisation	26
4.4.1	English	26
4.4.2	Catalan	27
4.4.3	Dutch	27
4.4.4	French	28
4.4.5	German	28
4.4.6	Italian	28
4.4.7	Norwegian	29
4.4.8	Portuguese	29
4.4.9	Spanish	29
4.4.10	Japanese	30
4.4.11	Other languages	30
4.5	Interaction with other packages	30
4.5.1	cleveref	30
4.6	Random	30
4.6.1	Random pseudo-generator	30
4.6.2	Uniform random deviates	31
4.6.3	Tokens shuffling	31
4.7	Keys numbering	32
4.8	Boxes	32
4.8.1	Character logging	32
4.8.2	Position logging	32
4.8.3	Boxes to be checked by students	34

4.8.4	Scoring zones	40
4.8.5	Binary boxes	40
4.9	Checking Environment	42
4.10	Handling groups of questions	42
4.11	Questions	46
4.11.1	Managing answers	47
4.11.2	Separate answer sheet	47
4.11.3	Formatting answers	51
4.11.4	Score zones	52
4.11.5	Formatting questions	55
4.11.6	Explanations	57
4.12	Scoring	57
4.13	Numerical data	58
4.13.1	Codes	58
4.13.2	Numerical questions	61
4.13.3	Intervals	75
4.14	Open questions	76
4.15	Boxes with letters only	79
4.16	Page formatting	80
4.16.1	Watermark	80
4.16.2	Signs for scan analysis	80
4.17	Defining a single exam copy content	82
4.18	Pre-association	83
4.19	Package options	84
4.20	Survey add-on	85
4.21	Package Errors	87
4.22	Optional features	87
4.23	Use with recent LuaTeX versions	87
4.24	External control	88
4.25	Page layout	88
4.26	Initialisation	89
4.27	French command names	89
5	Outputs	90
5.1	namefield command	90
5.2	AMCboxedchar command	90
5.3	AMCcode command	90

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in *roman* refer to the code lines where the entry is used.

Symbols			1397, 1398, 1418,	1822, 1829, 1839,
\"	148, 154	1419, 1424, 1425,	1840, 1841, 1842,	
\@aucune	839, 843, 844	1426, 1427, 1428,	1843, 1844, 1845,	
\@firstoftwo	659	1429, 1434, 1436,	1846, 1847, 1848,	
\@ifstar	1003, 1004	1437, 1438, 1439,	1850, 1855, 1856,	
\@secondoftwo	661	1440, 1442, 1444,	1859, 1865, 1867,	
\@skiphyperreffalse	1172	1445, 1446, 1447,	1869, 1870, 1873,	
\@skiphyperreftrue	1168, 1172	1450, 1457, 1458,	1874, 1878, 1879,	
\@tempboxa	2235, 2239, 2240	1459, 1461, 1463,	1880, 1882, 1883,	
\@tempdimb	2224, 2226	1464, 1466, 1468,	1885, 1886, 1887,	
\@tempdimc	2225, 2226	1470, 1473, 1474,	1888, 1889, 1891,	
_	1207	1476, 1478, 1479,	1892, 1895, 1897,	
\~	189, 190, 195, 196	1480, 1482, 1488,	1902, 1903, 1904,	
A			1493, 1505, 1539,	1905, 1907, 1908,
\aa	175	1541, 1543, 1545,	1909, 1910, 1911,	
\alafin	21, 2634	1547, 1550, 1553,	1912, 1913, 1916,	
\amc	866, 877,	1556, 1559, 1562,	1917, 1918, 1919,	
	879, 881, 882, 884,	1565, 1568, 1571,	1923, 1925, 1927,	
	887, 888, 890, 893,	1574, 1576, 1578,	1930, 1935, 1936,	
	894, 897, 898, 899,	1581, 1590, 1592,	1937, 1938, 1939,	
	900, 902, 904, 905,	1600, 1604, 1605,	1940, 1941, 1943,	
	907, 909, 910, 912,	1606, 1612, 1614,	1944, 1945, 1946,	
	914, 915, 918, 919,	1626, 1627, 1628,	1950, 1951, 1953,	
	921, 922, 924, 925,	1629, 1630, 1631,	1959, 1966, 1971,	
	927, 928, 930, 931,	1632, 1633, 1636,	1973, 1974, 1980,	
	933, 936, 937, 939,	1639, 1643, 1646,	1989, 1991, 1992,	
	941, 945, 946, 947,	1649, 1653, 1656,	1993, 1994, 1998,	
	948, 1270, 1271, 1272,	1660, 1663, 1668,	1999, 2000, 2004,	
	1273, 1274, 1275,	1670, 1672, 1679,	2005, 2006, 2007,	
	1276, 1278, 1285,	1681, 1684, 1693,	2009, 2010, 2011,	
	1288, 1293, 1297,	1694, 1695, 1696,	2024, 2026, 2032,	
	1305, 1308, 1309,	1698, 1700, 1703,	2041, 2044, 2045,	
	1310, 1313, 1318,	1708, 1709, 1711,	2051, 2052, 2053,	
	1320, 1323, 1324,	1715, 1717, 1720,	2054, 2055, 2056,	
	1325, 1326, 1328,	1721, 1722, 1723,	2057, 2059, 2060, 2063	
	1330, 1332, 1333,	1725, 1726, 1727,	\AMC@addpages	2347, 2349, 2351
	1335, 1336, 1340,	1730, 1733, 1738,	\AMC@affecte	279, 1183
	1341, 1342, 1344,	1740, 1743, 1747,	\AMC@amclog	17
	1345, 1346, 1348,	1748, 1749, 1751,	\AMC@answerBox	478
	1353, 1355, 1357,	1754, 1759, 1765,	\AMC@answerBox@	359,
	1365, 1370, 1371,	1767, 1769, 1772,		486, 533, 535, 551,
	1372, 1374, 1376,	1780, 1781, 1788,		553, 619, 621, 629, 631
	1379, 1380, 1381,	1789, 1791, 1792,	\AMC@binaryBoxes	652
	1382, 1384, 1386,	1793, 1795, 1798,	\AMC@binaryCode	602,
	1389, 1390, 1392,	1799, 1802, 1803,		653, 2255, 2256, 2257
	1393, 1395, 1396,	1805, 1811, 1815,	\AMC@box	520, 1053,
		1816, 1818, 1821,		1054, 1057, 2491, 2492

\AMC@boxcolor	377, 503, 2146	\AMC@lang@code	2382, 2417, 2418, 2614	\AMC@mem@add	907, 953, 960, 967, 974, 1404
\AMC@boxcolor@	377, 378, 379, 381, 399, 408, 420, 424, 441	\AMC@loc@CA	105	\AMC@mem@add@ifneeded	864, 1213
\AMC@boxeddown	391, 491, 502	\AMC@loc@catalog	99, 112, 126, 139, 153, 167, 180, 192, 206, 218, 2412	\AMC@mem@addsingle@ifneeded	956, 996, 998, 1000, 1002
\AMC@boxedheight	404, 418, 419, 421, 422, 425, 426, 470, 493, 497, 498, 510, 513	\AMC@loc@corrected	98, 111, 125, 138, 152, 166, 179, 191, 205, 217, 2251	\AMC@mem@addvar	912
\AMC@boxedrule	396, 418, 419, 420, 489, 500	\AMC@loc@DE	146	\AMC@mem@aid	931, 966
\AMC@boxedwidth	407, 418, 419, 421, 422, 425, 426, 470, 492, 497, 499, 510, 511, 1716	\AMC@loc@draft	93, 106, 120, 133, 147, 161, 174, 187, 200, 213, 2222	\AMC@mem@answer	963, 1026, 1033, 1034, 1035, 1040, 1046
\AMC@catalogMode	2407, 2415, 2574	\AMC@loc@ES	199	\AMC@mem@category	925, 959, 2036, 2182, 2218
\AMC@CBtaille	600, 2279, 2421	\AMC@loc@explain	100, 113, 140, 154, 193, 219, 1244	\AMC@mem@clear	882, 2339
\AMC@checkbox	359, 380, 383, 433, 435, 445, 451, 461, 619, 621, 1053, 1617, 1637, 1649, 1653, 2491	\AMC@loc@FR	132, 2417, 2629	\AMC@mem@next	902, 958, 972
\AMC@chiffres	1258	\AMC@loc@IT	160	\AMC@mem@openQuestion	970, 1212
\AMC@crosschar	402, 505	\AMC@loc@JA	212	\AMC@mem@qidaffname	919, 973
\AMC@crossrule	424, 490, 506	\AMC@loc@message	94, 107, 121, 134, 148, 162, 175, 188, 201, 214, 2592	\AMC@mem@show	946, 983, 992
\AMC@definitnumero	280, 284	\AMC@loc@namesurname	104, 117, 130, 144, 158, 171, 184, 197, 210	\AMC@mem@show@filter	947, 987
\AMC@draw@crossfalse	382	\AMC@loc@NL	119	\AMC@mn@leftmargin	1063, 1071, 1074, 1080
\AMC@draw@crosstrue	384	\AMC@loc@NO	173	\AMC@mn@rightmargin	1064, 1072, 1075, 1078
\AMC@error@explain	1244, 1246, 2517	\AMC@loc@none	101, 114, 127, 141, 155, 168, 181, 194, 207, 220, 839	\AMC@mn@sep	1062, 1078, 1080
\AMC@fillcolor@	380, 398, 399, 415, 420	\AMC@loc@PT	186	\AMC@mn@test	1061, 1068, 1077
\AMC@fin@rep	826, 1011, 1015, 1019, 1022, 1025	\AMC@loc@q	97, 110, 124, 137, 151, 165, 178, 190, 204, 216, 1175	\AMC@multi@report	1323, 2345
\AMC@formBox	520	\AMC@loc@qf	96, 109, 123, 136, 150, 164, 177, 189, 203, 215, 848	\AMC@multiclear	1328, 2336
\AMC@formBox@	520	\AMC@loc@question	102, 115, 128, 142, 156, 169, 182, 195, 208, 221, 227	\AMC@NCBcheck	596, 2257, 2421
\AMC@fullGroupsfalse	34	\AMC@loc@questions	103, 116, 129, 143, 157, 170, 183, 196, 209, 222, 227	\AMC@NCBetud	596, 2255, 2420
\AMC@fullGroupstrue	2385, 2411	\AMC@logchar	287, 388	\AMC@NCBpage	596, 2256, 2420
\AMC@if@separate@question	877, 952, 957, 965, 971, 1403, 2036, 2182, 2218	\AMC@logfile	17, 18, 19, 288	\AMC@new@savebox	360, 2446, 2450, 2451, 2452, 2453
\AMC@imax	713, 725, 726, 727	\AMC@LR	21, 390, 2227, 2274, 2275, 2276, 2277, 2278, 2592	\AMC@note	2252, 2253, 2287, 2297, 2591
\AMC@intituleHead	2251, 2268, 2412	\AMC@makeovalbox	413, 432, 433, 434, 435	\AMC@numeric@alsocorrect	1596, 1962, 1966, 1976, 1980
\AMC@keepmemoryfalse	2337			\AMC@numeric@keepas	1594, 1955, 1956
\AMC@keepmemorytrue	993			\AMC@numeric@scoreapprox	1586, 1921, 1931
\AMC@keyBox@	549, 1296, 1619, 1622			\AMC@numeric@scoreexact	1584, 1920, 1926
\AMC@keys@line	2414			\AMC@numeric@scorewrong	1588, 1928, 1931
\AMC@keys@next	2413			\AMC@numeration	279, 283, 284
				\AMC@outside@sep	495, 501
				\AMC@oval@radius	420, 494, 511, 513
				\AMC@ovalbox@	434, 448, 2452

\AMC@ovalbox@F	435, 446, 2453	\AMC@SRadvance	232, 239, 240	\AMC@sza@init@margin	1129
\AMC@ovalbox@R	\AMC@SRbit 239	\AMC@sza@init@margins	1133
.....	431, 432, 454, 2450	\AMC@SRconst	.. 230, 234, 237	\AMC@sza@init@none	1121
\AMC@ovalbox@RF	433, 452, 2451	\AMC@SRmax 245, 273	\AMC@sza@init@question	1125
\AMC@pagepos 293, 2264	\AMC@SRnextByte 245	\AMC@sza@width
\AMC@premierecopie	\AMC@SRnum	247, 248, 250,	1119, 1137, 1142
..	601, 2321, 2324, 2422	251, 255, 258, 273, 274		\AMC@tempenv 657, 658
\AMC@prepare	.. 282, 285, 286	\AMC@SRset	231, 243, 244, 246	\AMC@tracebox
\AMC@prepare@element	...	\AMC@SRtest 240, 251	..	293, 347, 440, 466,
.....	676, 684, 799	\AMC@SRvalue 242	584, 586, 589, 1042, 2245	
\AMC@printformoutside@false	\AMC@stepQuestion	\AMC@tracechar	335, 537, 555
.....	524	1165, 1199, 1237	\AMC@tracepos
\AMC@printformoutside@true	\AMC@sti	260, 268, 272, 275, 276	294, 405, 411,
.....	526, 527	\AMC@stil 261,	1028, 1031, 1205, 1213	
\AMC@printkeyoutside@false	269, 270, 271, 273, 277		\AMC@traceposx 303, 323
.....	541	\AMC@surveyfalse 2431	\AMC@traceposy	312, 322, 324
\AMC@printkeyoutside@true	\AMC@surveytrue 2432	\AMC@unnumero 279
.....	543, 545	\AMC@sz@box 1084,	\AMC@use@box 362,
\AMC@qaff	849, 1165, 1207, 1240	1086, 1088, 1091, 1134		446, 448, 452, 454, 2448	
\AMC@save@box	361, 416, 2447	\AMC@sz@callin	\AMC@VERSION 2606, 2608
\AMC@setcolors@	1096, 1101, 1109,	\AMC@watertext	.. 2222, 2233
....	376, 397, 414, 439	1111, 1176, 1208, 1209		\AMC@XYFILE 296,
\AMC@shape@form 473	\AMC@sz@callin@question	1086	305, 314, 326, 331,	
\AMC@shape@form@base	460, 474	\AMC@sz@callout	332, 333, 337, 343,	
\AMC@shape@form@ticked	1095, 1100,	345, 1186, 1320, 2329,	
.....	462, 464, 467	1104, 1106, 1202, 1203		2373, 2378, 2379,	
\AMC@shape@none 477	\AMC@sz@callout@margin	1088	2604, 2605, 2606,	
\AMC@shape@oval 438	\AMC@sz@callout@margins	1091	2607, 2608, 2609,	
\AMC@shape@square 395	\AMC@sz@depth	1084, 1094, 1099	2610, 2611, 2612,	
\AMC@shapename	\AMC@sz@height	2613, 2614, 2616, 2618	
..	293, 301, 310, 319, 496	1084, 1093, 1098	\AMC@addpagesto 2347
\AMC@shapename@	293, 391, 507	\AMC@sz@init@margins	.. 1090	\AMC@answer
\AMC@shapeprepare	\AMC@sz@width	1084, 1092, 1097	..	1046, 1047, 2135, 2197
.....	507, 515, 2454	\AMC@sza@box	1119, 1127, 1130	\AMC@association 2371
\AMC@shapeprepare@form	459	\AMC@sza@callin	858, 859,	\AMC@beforeQuestion
\AMC@shapeprepare@none	476	1141, 1146, 1154, 1156		1174, 1201, 1280
\AMC@shapeprepare@oval	430	\AMC@sza@callin@margin	1131	\AMC@beginAnswer
\AMC@shapeprepare@square	394	\AMC@sza@callin@margins	1135	..	1018, 1047, 2134, 2196
\AMC@shuffletoks	\AMC@sza@callin@none	.. 1123	\AMC@beginQuestion
....	260, 746, 749, 819	\AMC@sza@callin@question	1174, 1207,
\AMC@smashbox	.. 364, 367,	1127	1220, 1226, 1240, 1279	
368, 369, 370, 371, 374		\AMC@sza@callout	854, 855,	\AMC@bin@begin 651
\AMC@smashboxheight	1140, 1145, 1149, 1151		\AMC@bin@did	606, 614, 617,
..	365, 368, 369, 370, 373	\AMC@sza@callout@margin	1130	619, 624, 627, 629, 635	
\AMC@smashcentered	\AMC@sza@callout@margins	\AMC@bin@digit
..	366, 408, 409, 441, 442	1134	..	604, 637, 640, 646, 649
\AMC@SR 229,	\AMC@sza@callout@none	1122	\AMC@bin@hsep	608, 611, 615, 625
231, 234, 235, 236,		\AMC@sza@callout@question	\AMC@bin@id 605,
237, 239, 241, 242, 2330		1126	610, 618, 619, 628, 629	
\AMC@SR@count 234,	\AMC@sza@depth	\AMC@bin@endigits
235, 237, 245, 249,		1119, 1139, 1144	607, 609, 646, 649
252, 255, 256, 257, 258		\AMC@sza@height	\AMC@bin@number
\AMC@SR@time 246, 2398	1119, 1138, 1143	..	603, 636, 639, 641, 643

\AMCbin@one	613, 641	\AMCexternalQuestion . .	1189	1183, 1186, 1213,
\AMCbin@sequence . .	602,	\AMCform	16, 864, 2635	1296, 1619, 1622, 2078
636, 641, 642, 647, 648		\AMCformAfterQuestion . .		\AMCid@quest 26, 331, 332,
\AMCbin@style	612, 636	847, 1213	333, 565, 568, 570,
\AMCbin@zero . .	623, 642, 647	\AMCformAnswer	846	574, 576, 584, 586,
\AMCbloc	1181	\AMCformAnswerA . . .	863, 967	589, 915, 973, 1028,
\AMCbo@help .	2186, 2187, 2200	\AMCformatChoices		1031, 1042, 1183,
\AMCboHide	2213, 2219	1401, 2037, 2183, 2219		1185, 1186, 1205,
\AMCboOpts	2190	\AMCformBeforeQuestion .		1213, 1296, 1620,
\AMCboShow	2191, 2219	846, 852	1623, 1852, 2117, 2193
\AMCbotextGoto . .	2185, 2214	\AMCformBegin .	16, 864, 2636	\AMCIDBoxesA
\AMCboxColor	518, 2279	\AMCformFilter	985	2255, 2259
\AMCboxDimensions .	519, 636	\AMCformHSpace .	66, 862, 2197	\AMCIDBoxesABC . .
\AMCBoxedAnswers .	1005, 2389	\AMCformQuestion	846	2258, 2281
\AMCBoxOnly	2185	\AMCformQuestionA .	850, 974	\AMCIDBoxesB
\AMCboxOutsideLetter . .		\AMCformQuestionN .	849, 857	2256, 2260
.....	520, 2136, 2198	\AMCformS	864	\AMCIDBoxesC
\AMCboxStyle		\AMCformVSpace	66, 846	2257, 2260
.....	21, 489, 2389, 2439	\AMCgroup@pre	742, 765	\AMCids@height .
\AMCccircle	2241, 2244	\AMCgrouploop@next		77, 88, 2280
\AMCchoiceLabel . . .	478, 559	767, 780, 798	\AMCids@sidefalse
\AMCchoiceLabelFormat . .		\AMCgrouploop@prep		80, 82
.....	392, 478	753, 778, 796	\AMCids@sidetrue
\AMCcleardoublepage .	16, 2356	\AMCgrouppre@cyclic . . .	736	84
\AMCcode	1397	\AMCgrouppre@fixed	698	\AMCids@topfalse
\AMCcodeGrid	15, 1258	\AMCgrouppre@withoutreplacement		80, 84
\AMCcodeGridInt . . .	15, 1258	714	\AMCids@toptrue
\AMCcodeH	1398	\AMCgrouppre@withreplacement		82
\AMCcodeHspace	705	\AMCids@width . .
.....	1259, 1300, 1359	\AMChorizAnswerSep		76, 87, 2283
\AMCcodeID	1264, 1339	1036, 1037, 1045	\AMCidsPosition
\AMCcodeID@@		\AMChorizBoxSep		74
1263, 1267, 2430, 2580		1038, 1039, 1042, 1044		\AMCidsVar
\AMCcodeID@dot	1262	\AMCid@check		78
\AMCcodeID@mode .	1265, 2607	27, 328, 2257, 2262,		\AMCidsVarN
\AMCcodeID@squarebrackets		2263, 2280, 2284, 2598		78, 79
.....	1261	\AMCid@checkmax		\AMCif@env . .
\AMCcodeVspace		596, 2263, 2420, 2598		656, 1244, 1246
1260, 1298, 1358, 1361		\AMCid@etud	28, 290,	\AMCifcategory
\AMCcompleteMulti . .	12, 63	298, 307, 316, 328,		948
\AMCcurrentenv .	655, 658, 1198	331, 332, 333, 338,		\AMCinterBquest . . .
\AMCdebutFormulaire .	21, 2636	353, 474, 2254, 2255,		71, 1213
\AMCdecimalPoint		2280, 2284, 2292,		\AMCinterBrep
.....	1527, 1712, 1744	2320, 2321, 2323,		66, 1032
\AMCdefault@groupmode . .		2330, 2335, 2342,		\AMCinterIquest . . .
.....	673, 687, 688	2343, 2363, 2364, 2373		70, 1213
\AMCdontAnnotate .	331, 2151	\AMCid@etudfin	30,	\AMCinterIrep
\AMCdontScan	331, 2149	2322, 2323, 2324, 2342		66, 1009
\AMCdump@reponses .	819, 833	\AMCid@etudstart		\AMCIntervalFormat .
\AMCemptybox .	1059, 1084, 1119	29, 2320, 2343	2048, 2059
\AMCendAnswer		\AMCid@name .	65, 565, 568,	\AMCIntervals .
1019, 1047, 2134, 2196		570, 574, 576, 916,		17, 2048, 2638
\AMCexponent .	1529, 1996, 2008	973, 1028, 1031, 1042,		\AMClabel
				2364, 2369
				\AMCload@reponse .
				830,
				832, 1053, 1057, 2491
				\AMCload@counter
				25, 808, 809, 810,
				811, 814, 815, 819,
				822, 823, 824, 825, 828
				\AMCload@reponse . .
				813, 832
				\AMClocalized
				92
				\AMCloop@k
				719, 725,
				729, 731, 752, 760, 769
				\AMCmarginNote
			
				1065, 1091, 1134
				\AMCmem@elt@cat .
				922, 934, 938
				\AMCmessage .
				17, 280, 592,
				992, 1051, 1056, 1185,
				1192, 1193, 1194,
				1213, 1217, 1254,
				1255, 1256, 1257,
				1295, 1409, 1616,
				1648, 1650, 1655,
				1657, 1662, 1664,

1673, 1686, 1702, 1794, 1797, 1830, 1832, 1852, 1917, 1924, 1941, 1943, 1946, 1948, 1951, 1953, 1956, 1960, 1963, 1965, 1972, 1977, 1979, 2019, 2117, 2174, 2193, 2210, 2318, 2335, 2438, 2442, 2489, 2599, 2600, 2601, 2602	2145, 2146, 2156, 2159	1290, 1294, 1295, 1296, 1402, 1404, 1615, 1616, 1620, 1623, 2488, 2489, 2492
\AMCncol@Background	\AMCocol@FrameRule	\AMCrep@fini 830, 833, 837, 845
1537, 1988	2070, 2094, 2167	\AMCrep@init . . 826, 1010, 1013, 1017, 1021, 1024
\AMCncol@Border . 1533, 1988	\AMCOpen 2066	\AMCrep@itemize . 1007, 1026
\AMCncol@BorderWidth	\AMCOpen@answer	\AMCrep@ligne . . . 1013, 1026
1535, 1987	. 2072, 2079, 2108, 2124	\AMCrep@o 827, 829
\AMCneeds@storeboxfalse 2427	\AMCOpen@boxframerule	\AMCrep@perso . . . 1017, 1026
\AMCneeds@storeboxtrue 2428	2091, 2092, 2139	\AMCrep@r 831
\AMCnobloc 1180, 1284	\AMCOpen@boxmargin	\AMCrep@tikz 1021, 1026
\AMCnoCompleteMulti	2089, 2090, 2138	\AMCrep@tikzmat . 1024, 1026
12, 64, 2133	\AMCOpen@contentcommand	\AMCreTick 331, 2150
\AMCNombreCopies	2080, 2168	\AMCrien@deux 813, 830
. 2316, 2317, 2615, 2618	\AMCOpen@framerule	\AMCscoreZone 580, 1059
\AMCnoScoreZone . 1164, 1281	2095, 2096, 2166	\AMCscoreZoneAnswerSheet 1059
\AMCncontextGoto . . . 1518, 2028	\AMCOpen@Hspace . . 2081, 2082, 2137, 2142, 2154	\AMCsection 995
\AMCncontextSign 1525, 1763, 1764	\AMCOpen@LineHeight	\AMCsectionNumbered 995, 1003
\AMCncontextVHead	2085, 2086, 2107	\AMCsectionStar . . 999, 1003
1519, 1716, 1862	\AMCOpen@Lines	\AMCsetFoot 2253
\AMCnum@copies . 31, 2316, 2317, 2318, 2319, 2322	2087, 2088, 2112	\AMCsetScoreZone 1117, 1118, 1164
\AMCnum@questions . 820, 822	\AMCOpen@lines 2105	\AMCsetScoreZoneAnswerSheet 1162, 1163, 1164
\AMCnumeric@Hspace	\AMCOpen@lineuptext 2074, 2097, 2122, 2125, 2128	\AMCshowSignificantDigits 1466
. 1520, 1532, 1674, 1676, 1712, 1731, 2008	\AMCOpen@question	\AMCsignificantDigits . 1461
\AMCnumeric@Vspace 2073, 2078, 2141, 2142	\AMCstartWithQuestion 1182, 1190, 1200
1521, 1531, 1647, 1654, 1661, 1688, 1704, 1718, 1752, 1764, 1995, 1997	\AMCOpen@Width	\AMCstudentlabel 2364, 2365, 2366, 2367
\AMCnumericChoices . 18, 1401	2083, 2084, 2106	\AMCStudentNumber 2254
\AMCnumericChoicesPlain	\AMCOpenHide 2177, 2183	\AMCstudentslistfile . . 2376
2035, 2042	\AMCOpen@Opts 2104	\AMCsubjectPageTag 2291, 2296
\AMCnumericHide . 2032, 2037	\AMCOpen@Show 2115, 2183	\AMCsubsection 995
\AMCnumericOpts 1612	\AMCotextGoto . . . 2066, 2178 997, 1004
\AMCnumericShow . 2024, 2037	\AMCotextReserved 2067, 2077, 2153, 2157, 2159	\AMCsubsectionStar 1001, 1004
\AMCnumero 1166, 2334	\AMCoutsideLabelFormat 520	\AMCsw@p 260
\AMCocol@Background	\AMCpageref 2367	\AMCsw@p@ 262, 264, 266
2068, 2075, 2140	\AMCpostNquest 72, 2017	\AMCsz@loggedfalse 580
\AMCocol@BoxFrameRule	\AMCpostOquest 73, 2170	\AMCsz@loggedtrue 593
2069, 2093, 2140	\AMCqlabel 2368	\AMCtext 91
\AMCocol@Foreground	\AMCquestionaff 1165	\AMCtok@ik 719, 720, 722, 727, 728, 729, 730, 731, 751, 759, 772, 781, 800
2071, 2076,	\AMCquestionNumberfalse 1282	\AMCtok@k 664, 679, 680, 681, 685, 800
	\AMCquestionNumbertrue . 45	\AMCtok@max 665
	\AMCrandomseed 243	
	\AMCref 2364, 2364	
	\AMCrep@count 834, 836, 838	
	\AMCrep@bloc 1008, 1026	
	\AMCrep@count . . 565, 568, 570, 574, 576, 807, 816, 836, 838, 842, 928, 966, 1007, 1013, 1017, 1021, 1024, 1028, 1031, 1042, 1050, 1051, 1054, 1055, 1056, 1057,	

<code>\AMCtok@size</code>	<code>\clist</code>	D
. 666, 754, 755, 756,	1270,	<code>\define@boolkey</code>
757, 765, 773, 782, 801	1276, 1285, 1320,	... 504, 2098, 2099,
<code>\AMCw@termark</code> ... <u>2221</u> , 2265	1333, 1337, 1371,	2100, 2101, 2102, 2188
<code>\AMCw@terprint</code> .. <u>2221</u> , 2265	1380, 1381, 1475,	<code>\define@choicekey</code>
<code>amcxyfile</code> (env.) <u>342</u>	1478, 1489, 1490, 78, 496, 1102, 1147
<code>\AMCzone</code>	1574, 1575, 1709,	<code>digits</code> (option)
<u>347</u> , 348	1710, 1740, 1741,	10
<code>\answer</code>	1841, 1842, 1859, 1867	<code>\ding</code>
289, <u>1050</u> , <u>2456</u>	<code>\codeDigitExterne</code> 2579, 2580	468
<code>answers</code> (option)	<code>completemulti</code> (option) ..	<code>\dontannotate</code>
10	10	332
<code>asbox</code> (option)	<code>\coordinate</code>	<code>\dontscan</code>
10	1067	331
<code>\association</code>	<code>\copieexamen</code>	<code>\dotfill</code> 356, 2110, 2126
2373	2631	<code>\draw</code> ... 420, 424, 1078, 1080
<code>auto</code> (env.)	<code>copieexamen</code> (env.)	
<u>2456</u>	21	E
<code>automarks</code> (option)	<code>\copygroup</code>	<code>\element</code>
11	14, <u>788</u>	14, 664
B	<code>\copygroupfrom</code>	<code>\endchoices</code>
<code>\bareme</code>	14, <u>788</u>	2621
21, 2626	<code>correc</code> (option)	<code>\endchoicescustom</code>
<code>\baremeDefaultM</code>	21	2623
21, 2627	<code>correcindiv</code> (option)	2622
<code>\baremeDefaultS</code>	21	<code>\endchoicexamen</code>
21, 2628	<code>\correctchoice</code>	2631
<code>\bf</code>	13, 844, <u>1050</u> , 2058, 2624	<code>\endexamcopy</code>
1528	<code>\CorrigeExterne</code>	2631
<code>bloc</code> (option)	2556	<code>\endreponses</code>
21	<code>\CorrigeIndivExterne</code> ..	2621
<code>\bonne</code>	2556	<code>\endreponseshoriz</code>
21, 2624	<code>\crefalias</code>	2622
<code>\bool</code> 940, 1273, 1274, 1275,	226	<code>\endreponsesperso</code>
1297, 1308, 1309,	<code>\crefname</code>	2623
1332, 1335, 1339,	227	<code>ensemble</code> (option)
1346, 1348, 1357,	<code>\cs</code> 877, 881, 882, 884, 887,	21
1605, 1670, 1681,	890, 893, 897, 902,	environments:
1696, 1715, 1720,	904, 907, 909, 912,	<code>amcxyfile</code>
1761, 1765, 1780,	914, 918, 919, 921,	342
1793, 1799, 1803,	924, 925, 927, 930,	<code>auto</code>
1818, 1828, 1829,	931, 933, 936, 945,	2456
1869, 1873, 1882,	946, 947, 948, 1278,	<code>choices</code>
1923, 1959, 1971, 1989	1288, 1293, 1318,	12, <u>1005</u>
<code>box</code> (option)	1323, 1325, 1328,	<code>choicescustom</code> ..
10	1330, 1370, 1374,	12, <u>1005</u>
<code>\boxchar</code>	1379, 1384, 1389,	<code>choiceshoriz</code> ...
338	1392, 1395, 1396,	12, <u>1005</u>
<code>\boxput</code>	1397, 1398, 1416,	<code>copieexamen</code>
6, 401, 440	1424, 1434, 1437,	21
C	1442, 1446, 1458,	<code>examcopy</code>
<code>\c</code>	1461, 1463, 1466,	2528
945, 1575	1468, 1474, 1488,	<code>question</code>
<code>calibration</code> (option) ..	1493, 1505, 1600,	11, <u>1179</u>
5, 10	1604, 1612, 1614,	<code>question-auto</code>
<code>catalog</code> (option)	1628, 1643, 1668,	2456
10	1679, 1694, 1708,	<code>questionmult</code> ...
<code>\CatalogExterne</code>	1738, 1759, 1788,	11, <u>1179</u>
2572	1850, 2024, 2026,	<code>Questionnaires</code>
<code>\champnom</code>	2032, 2041, 2044,	2456
21, 2637	2045, 2053, 2063,	<code>questionouverte</code> ...
<code>\char</code>	2538, 2539, 2541,	1179
1421	2542, 2544, 2545,	<code>reponses</code>
<code>\CheckBox</code>	2548, 2549, 2551, 2552	21
467	<code>\csvreader</code>	<code>reponseshoriz</code>
<code>chiffres</code> (option)	2463, 2468, 2474, 2483	21
21		<code>reponsesperso</code>
<code>\choices</code>		21
2621		<code>tikz-multi</code>
<code>choices</code> (env.)		<u>1005</u>
12, <u>1005</u>		<code>tikz-single</code>
<code>\choicescustom</code>		<u>1005</u>
2623		<code>values</code>
<code>choicescustom</code> (env.)		2456
12, <u>1005</u>		<code>values-auto</code>
<code>\choiceshoriz</code>		2456
2622		<code>variable-auto</code>
<code>choiceshoriz</code> (env.)		2456
12, <u>1005</u>		<code>variable-multi</code> ...
<code>\choixIntervalles</code> ..		1179
21, 2638		<code>variable-single</code> ...
<code>\cleargroup</code>		1179
14, <u>788</u>		<code>\evensidemargin</code> ..
		1072, 1074
		<code>\examcopy</code>
		2631
		<code>examcopy</code> (env.)
		2528
		<code>\exemplaire</code>
		21, 2629
		<code>\exemplairepair</code>
		2363
		<code>\explain</code>
		1242, 2518
		<code>\explaincontext</code>
		1249

\ExplSyntaxOff	\ifAMC@correc	\ifAMC@watermark
. . . 950, 1400, 1517,	38, 379, 1053, 1250, 51, 2265, 2589
2034, 2047, 2065, 2555	1618, 2108, 2124, 2491	\ifAMC@zoneformulaire . .
\ExplSyntaxOn	\ifAMC@correchead 57, 527, 564, 868
. . . 864, 1268, 1414, 35, 1243, 2265,	\ifAMCcomplete@multi 44, 841
1522, 2039, 2049, 2536	2308, 2324, 2584, 2590	\ifAMCformulaire@dedans
F	\ifAMC@draw@cross 56, 526,
\fancypagestyle 363, 402, 423	567, 583, 1851, 2018,
. 2267, 2272, 2294, 2301	\ifAMC@ensemble	2116, 2173, 2192, 2209
\fbox 2292 54, 525, 542,	\ifAMCids@side 75, 2283
\footrulewidth	563, 582, 867, 979,	\ifAMCids@top 74, 2280
. 2270, 2289, 2299, 2304	982, 986, 991, 1207,	\ifAMCneeds@storebox . .
\foreach 2482	1407, 1851, 2017, 2427, 2434, 2445
\formulaire 21, 2635	2018, 2116, 2121,	\ifAMCquestionNumber 45, 1172
\fp 1428, 1436,	2135, 2141, 2173,	\ifAMCsz@logged . . . 580, 591
1438, 1440, 1444,	2192, 2197, 2200,	\ifAMCtype@multi . . . 50, 841
1449, 1451, 1453,	2209, 2333, 2599, 2609	\ifAMCune@bonne 49, 843
1457, 1464, 1469,	\ifAMC@extractOnly	\ifcase 79
1476, 1494, 1497, 40, 1985, 2613	\ifcsname . . . 1103, 1108,
1839, 1840, 1878,	\ifAMC@fullGroups . . 34, 755	1113, 1148, 1153, 1158
1879, 1888, 1916,	\ifAMC@inside@box	\ifcsvstrcmp
1917, 1943, 2051, 52, 545, 573,	. 2469, 2475, 2476, 2484
2052, 2054, 2055,	2136, 2198, 2600, 2610	\ifdim 1077
2056, 2057, 2059, 2060	\ifAMC@inside@digit . 55, 479	\ifKV@AMCBoxOnly@ordered
francais (option) 10	\ifAMC@invisible . . . 61, 293 2201
fullgroups (option) 11	\ifAMC@keepmemory 989, 2339	\ifKV@AMCdim@cross
G	\ifAMC@keyline 37, 1206, 1207 383, 398, 415
\group 1420, 1432	\ifAMC@ordre 32, 827	\ifKV@AMCOpen@annotate 2151
H	\ifAMC@outside@box	\ifKV@AMCOpen@dots . . . 2109
\he@dbas . . . 2249, 2274, 2275	53, 525, 543, 2601, 2611	\ifKV@AMCOpen@lineup . .
\he@dhaut 2250, 2278	\ifAMC@pagelayout 2120, 2163
\he@dtaille . 2246, 2249, 2250	. . . 58, 2262, 2307, 2583	\ifKV@AMCOpen@retick . . 2150
\hfuzz 370	\ifAMC@pdfform	\ifKV@AMCOpen@scan . . . 2149
\ht 368, 1060	62, 351, 2327, 2344, 2437	indivanswers (option) . . 6, 10
I	\ifAMC@plain 48, 2520	init (option) 10
\ifAMC@affichekeys	\ifAMC@postcorrect	\InputIfFileExists 15
. 36, 1206, 1207 59, 844, 2602, 2612	\insertgroup . . . 14, 745, 2633
\ifAMC@asqbloc . 42, 847, 853	\ifAMC@printformoutside	\insertgroupfrom . . . 14, 745
\ifAMC@automarks 523, 532	insidebox (option) 10
60, 979, 2333, 2352, 2359	\ifAMC@printformoutside@	\int 879, 881, 885,
\ifAMC@calibration 522, 529	891, 898, 937, 1272,
. 46, 295,	\ifAMC@printkeyoutside .	1285, 1324, 1326,
304, 313, 326, 331, 540, 550	1335, 1341, 1342,
332, 333, 336, 1051,	\ifAMC@printkeyoutside@	1365, 1429, 1445,
1056, 1184, 1191, 539, 547	1473, 1476, 1478,
1216, 1254, 1255,	\ifAMC@qbloc . . . 41, 1174,	1479, 1480, 1482,
1256, 1257, 1295,	1205, 1213, 1239,	1495, 1498, 1500,
1319, 2329, 2335,	1241, 2029, 2179, 2215	1506, 1507, 1509,
2372, 2377, 2489, 2603	\ifAMC@rbloc . 43, 1008, 1011	1510, 1512, 1606,
\ifAMC@catalog 47, 387	\ifAMC@shuffleG 33, 746, 749	1626, 1629, 1631,
	\ifAMC@survey . . . 2431, 2456	1632, 1633, 1635,
	\ifAMC@textPos . 39, 1028,	1644, 1669, 1680,
	1031, 1041, 1205, 1213	1687, 1693, 1695,

1697, 1703, 1709, 1711, 1716, 1722, 1726, 1730, 1733, 1740, 1742, 1748, 1751, 1754, 1766, 1791, 1792, 1795, 1798, 1802, 1805, 1811, 1815, 1816, 1821, 1822, 1843, 1844, 1845, 1848, 1855, 1856, 1863, 1864, 1870, 1873, 1874, 1880, 1885, 1887, 1891, 1904, 1905, 1910, 1918, 1919, 1925, 1927, 1930, 1938, 1945, 1946, 1950, 1951, 1953, 1966, 1973, 1974, 1980, 1994, 2007		noshufflegroups (option) . 10 \nouveaugroupe 664, 789 nowatermark (option) . . 4, 10 \NoWatermarkExterne . . . 2556		\pgfpointdiff 1068 \pgfpointorigin 1068 plain (option) 11 postcorrect (option) . . . 11 \prg 866, 869, 871, 874, 1381, 1477, 1490
	K		O	Q
\keys 1304, 1331, 1524, 1601, 1854, 2027 keys (option) 10		\oddsidemargin . . 1071, 1075 \onecopy 2315, 2458, 2532, 2629 options: answers 10 asbox 10 automarks 11 bloc 21 box 10 calibration 5, 10 catalog 10 chiffres 21 completemulti 10 correc 21 correcindiv 21 digits 10 ensemble 21 francais 10 fullgroups 11 indivanswers 6, 10 init 10 insidebox 10 keys 10 nopage 6, 11 noshuffle 10 noshufflegroups 10 nowatermark 4, 10 ordre 21 outsidebox 10 pdfform 11 plain 11 postcorrect 11 separateanswersheet 5, 10, 16 storebox 11 \or 81, 83 ordre (option) 21 outsidebox (option) 10 \ouverte@vs 1179		\question 1179, 1186 question (env.) 11, 1179 question-auto (env.) . . . 2456 \QuestionIndicative 13, 1254, 1289 questionmult (env.) . . 11, 1179 Questionnaires (env.) . . 2456 questionouverte (env.) . . 1179
	L			R
\l 1863, 1867 \lastchoices 826, 2634 \lastxpos 2542 \lastypos 2545 \linebreak 2131				\raisebox 1528 \refstepcounter 1172 \reponses 2621 reponses (env.) 21 \reponseshoriz 2622 reponseshoriz (env.) . . . 21 \reponsesperso 2623 reponsesperso (env.) . . . 21 \restituegroupe . . . 21, 2633 \retick 333 \rngstate 2330
	M			S
\m@rque 2245, 2274, 2275, 2276, 2277 \m@rqueCalage . . . 2244, 2245 \marginpar 1088, 1130 \mauvaise 21, 2625 \melangegroupe 21, 2632 \MessageBreak 2518 \multiSymbole 1174, 1215, 1233				\savebox 361 \savepos 2539 \sbox 1060 \scoring 13, 1221, 1227, 1254, 2626 \scoringDefaultM 13, 1254, 2627 \scoringDefaultS 13, 1254, 2628 \ScoringExterne 2556 \section 996, 1000 separateanswersheet (op- tion) 5, 10, 16 \seq 1271, 1345, 1353, 1419, 1427, 1428, 1429 \setdefaultgroupmode . . 687 \setgroupmode 673, 687 \shuffle@it 819, 833 \shufflegroup 14, 711, 723, 745, 2632 \shufflegroupslice 728, 731, 748 \smash 2108, 2124
	N		P	
\namefield 15, 348, 2637 \namefielddots 349 \newbox 364 \newline 1206 \newsavebox 360 \newstorebox 2446 \nobreak 521, 2164 \node 1033, 1034, 1229 nopage (option) 6, 11 noshuffle (option) 10		\PackageError 649, 691, 762, 2517 \pageref 2367 pdfform (option) 11 \pdfpageheight 330, 2551, 2552 \pdfpagewidth 330, 2548, 2549 \pgfextractx 1068 \pgfpointanchor 1069		

